

100%



PRODUCED
RAN & OWNED

FTP Data Model

for use with Invantive SQL

24.0



Copyright

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

Important Safety and Usage Information

Intended Use and Limitations: This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting and sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weapon control, military strategy planning, or any other aspects of national defense.
- Aviation: The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- Healthcare and Medicine Production: This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- Transportation and Traffic Control Systems: The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- Energy Grid and Utility Control Systems: This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

User Responsibility: Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.

Disclaimer of Liability: Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

Contents

1	Provider Ftp: FTP.	1
2	Catalog: FTP	3
2.1	Schemas	3
2.1.1	Schema:	3
	Index	6

1 Provider Ftp: FTP.

FTP.

Code for use in settings.xml: Ftp

Alias: ftp

Abbreviation: ftp

Status: Production

Available in Editions: Paid

String-comparison is Case-sensitive: true

Use Catalog in Full Name: true

Use Schema in Full Name: true

Updated: 23-06-2019 19:40 using Invantive SQL version 17.33.48-BETA+2173.

Provider Attributes

The following provider attributes are available for Ftp:

Code	Description	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Providers File	Set from Log On
site	{res:itgen_ftp_site_description}		✓		✓	✓
port	{res:itgen_ftp_port_description}	21	✓		✓	✓
use-ssl	Use SSL for the connection (FTPS).	False	✓		✓	✓
use-passive	Use passive FTP(S) instead of active.	True	✓		✓	✓
use-binary	Use binary mode (true) or ASCII mode (false) transfers by default.	True	✓		✓	✓
timeout-connection-sec	Seconds to wait for a connection attempt to succeed before giving up.	30	✓		✓	✓
timeout-data-connection-sec	Seconds for a data connection to be established before giving up.	30	✓		✓	✓
timeout-data-read-sec	Seconds the data channel should wait for the server to send data.	30	✓		✓	✓
timeout-read-sec	Seconds for data to be read from the underlying stream.	30	✓		✓	✓
socket-poll-interval-sec	Seconds between two poll intervals when enabled.	15	✓		✓	✓
socket-keep-alive	Whether to keep the connection alive by polling.	False	✓		✓	✓
special-connection-type	Special connection types for specialized use.		✓		✓	✓
ssl-protocols	Comma-separated list of SSL protocols, defaults to TLS 1.1 and TLS 1.2.		✓		✓	✓
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	False	✓	✓	✓	

Code	Description	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Providers File	Set from Log On
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Lower, Upper and Mixed.		✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	True	✓	✓	✓	
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	False	✓	✓	✓	
invantive-use-cache	Whether to cache the results of a query.	True	✓	✓	✓	
maximum-length-identifiers	Non-default maximum length in characters of identifier names.		✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	8000	✓	✓	✓	
partition-slot-based-rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	0	✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	32	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in ms across all slots of a slot-based rate limit.	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit		✓		✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	True	✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	True	✓	✓	✓	
trace-native-calls	Trace native calls to data container backend.	False	✓	✓	✓	

2 Catalog: FTP

2.1 Schemas

2.1.1 Schema:

2.1.1.1 Tables

DIRECTORIES: Directories

Name: DIRECTORIES

Catalog: FTP

Label: Directories

Documentation:

Directories.

Partition-specific: false

Select: true

Insert: true

Update: false

Delete: false

Table Columns

Name	Data Type	Label	Required	Documentation
remote_directory_path	string		<input type="checkbox"/>	

FILE_CONTENTS: File Contents

Name: FILE_CONTENTS

Catalog: FTP

Label: File Contents

Documentation:

File contents.

Partition-specific: false

Select: true

Insert: true

Update: false

Delete: false

Parameters

Name	Data Type	Required	Default Value	Documentation
remote_directory_path	string	<input type="checkbox"/>		
remote_file_name	string	<input type="checkbox"/>		

Table Columns

Name	Data Type	Label	Required	Documentation
contents	byte[]		<input type="checkbox"/>	
remote_directory_path	string		<input type="checkbox"/>	
remote_file_name	string		<input type="checkbox"/>	

FILES_PER_FOLDER: Files per Folder

Name: FILES_PER_FOLDER

Catalog: FTP

Label: Files per Folder

Documentation:

Scan directory for file and directory names.

Partition-specific: false

Select: true

Insert: false

Update: false

Delete: false

Parameters

Name	Data Type	Required	Default Value	Documentation
remote_directory_path	string	<input checked="" type="checkbox"/>		

Table Columns

Name	Data Type	Label	Required	Documentation
chmod	int32			File permissions.
date_created	datetime		<input type="checkbox"/>	
date_last_modified	datetime		<input type="checkbox"/>	
directory_name	string		<input type="checkbox"/>	
file_name	string		<input type="checkbox"/>	
group_permissions	string			Group permissions, combination of None, Execute, Read and Write.
link_count	int32			Number of files pointing to this file.
link_object_name	string			Full name of the link target.
link_target	string			Link target.
other_permissions	string			Other user permissions, combination of None, Execute,

Name	Data Type	Label	Required	Documentation
				Read and Write.
owner_permissions	string			Owner permissions, combination of None, Execute, Read and Write.
raw_input	string			Input string parsed to generate this row .
raw_permissions	string			Input string parsed to generate the permissions.
size_bytes	int64		<input type="checkbox"/>	
special_permissions	string			Special permissions, such as sticky, SUID and SGID.
type	string			Type of file system object (file, directory or link).

Index

- C -

chmod 4
contents 3

- D -

date_created 4
date_last_modified 4
DIRECTORIES 3
directory_name 4

- F -

File Contents 3
FILE_CONTENTS 3
file_name 4
Files per Folder 4
FILES_PER_FOLDER 4
force-case-sensitive-identifiers 1
forced-casing-identifiers 1
FTP 1, 3, 4

- G -

group_permissions 4

- I -

invantive-sql-forward-filters-to-data-containers 1
invantive-sql-shuffle-fetch-results-data-containers 1
invantive-use-cache 1

- L -

link_count 4
link_object_name 4
link_target 4

- M -

maximum-length-identifiers 1
max-url-length-accepted 1
max-url-length-desired 1

- O -

other_permissions 4
owner_permissions 4

- P -

partition-slot-based-rate-limit-length-ms 1
partition-slot-based-rate-limit-slots 1
port 1
pre-request-delay-ms 1

- R -

raw_input 4
raw_permissions 4
remote_directory_path 3, 4
remote_file_name 3
requests-parallel-max 1

- S -

site 1
size_bytes 4
slot-based-rate-limit-length-ms 1
slot-based-rate-limit-slots 1
socket-keep-alive 1
socket-poll-interval-sec 1
special_permissions 4
special-connection-type 1
ssl-protocols 1
standardize-identifiers 1
standardize-identifiers-casing 1

- T -

timeout-connection-sec 1
timeout-data-connection-sec 1
timeout-data-read-sec 1
timeout-read-sec 1
trace-native-calls 1
type 4

- U -

use-binary 1
use-passive 1
use-ssl 1



invantive the **SQL** company

Invantive B.V.
Biesteweg 11
3849 RD Hierden
the Netherlands

Tel: +31 88 00 26 500
Fax: +31 84 22 58 178
info@invantive.com
invantive.com

IBAN NL25 BUNQ 2098 2586 07
Chamber of Industry and Commerce
13031406
VAT NL812602377B01
RSIN 8122602377
Managing Director: Guido Leenders
Registered office: Roermond