



# KeePass Data Model

*for use with Invantive SQL*

24.0



# Copyright

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

## Important Safety and Usage Information

**Intended Use and Limitations:** This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting and sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weapon control, military strategy planning, or any other aspects of national defense.
- Aviation: The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- Healthcare and Medicine Production: This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- Transportation and Traffic Control Systems: The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- Energy Grid and Utility Control Systems: This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

**User Responsibility:** Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.

**Disclaimer of Liability:** Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

---

# Contents

|            |  |           |
|------------|--|-----------|
| <b>1</b>   | <b>SQL Driver for KeePass</b>  | <b>1</b>  |
| <b>2</b>   | <b>SQL Driver Attributes</b>   | <b>2</b>  |
| <b>3</b>   | <b>Catalog: KeePass</b>  | <b>4</b>  |
| <b>3.1</b> | <b>Schemas</b> .....   | <b>4</b>  |
| 3.1.1      | keepass_entities: KeePass Entities .....                                   | 4         |
| 3.1.2      | keepass_entry_custom_sequences: KeePass Entry Custom Sequences .....       | 6         |
| 3.1.3      | keepass_entry_file_attachments: KeePass Entry File Attachments .....       | 6         |
| 3.1.4      | keepass_entry_history: KeePass Entries History .....                       | 7         |
| 3.1.5      | keepass_entry_string_fields: KeePass Entry String Fields .....             | 9         |
| 3.1.6      | keepass_file_metadata: KeePass File Metadata .....                         | 10        |
| 3.1.7      | keepass_file_metadata_binaries: KeePass File Metadata Binaries .....       | 11        |
| <b>4</b>   | <b>Package: dcr_metadata</b>   | <b>12</b> |
| <b>4.1</b> | <b>Procedures</b> .....  | <b>12</b> |
| 4.1.1      | dcr_metadata.get_partitions: KeePass Data container metadata package ..... | 12        |
|            | <b>Index</b>   | <b>13</b> |

## 1 SQL Driver for KeePass

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the [user community](#). Invantive Support or other users will try to help you.

Security-sensitive storage of keys and other confidential information.

The KeePass driver covers 7 tables and 67 columns.

### KeePass Clients

Invantive UniversalSQL is available on many user interfaces ("clients" in traditional server-client paradigm). All Invantive UniversalSQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL.

### Specifications

The SQL driver for KeePass does not support partitioning.

An introduction into the concepts of Invantive UniversalSQL such as databases, data containers and partitioning can be found in the [Invantive UniversalSQL grammar](#).

The configuration can be changed using various attributes from the database definition, on log on and during use. A full list of configuration options is listed in the [driver attributes](#)<sup>2</sup>.

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On KeePass the comparison of two texts is case sensitive by default.

Changes and bug fixes on the KeePass SQL driver can be found in the [release notes](#). There is currently no specific section on the [Invantive forums](#) for KeePass. Please reach out to other users of KeePass by leaving a question or contact request.

Driver code for use in settings.xml: `KeePass`

Alias: `KeePass`

Recommended alias: `kp`

Status: Non-production

Technical support (URL): <https://forums.invantive.com>

Function documentation (URL): <https://cloud.invantive.com/data-models>

Function support (URL): <https://forums.invantive.com>

## 2 SQL Driver Attributes

The SQL driver for KeePass has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the KeePass server or high volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The KeePass driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings\*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for KeePass can be found in the settings\*.xml file used for the database. The reference manuals contain instructions how to relocate the settings\*.xml files. Settings\*.xml files are typically located in the %USERPROFILE%\invariant folder in most deployment scenarios. Each data container of a database in the connection string can have a `connectionString` element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: `set NAME VALUE`, or for a distributed database: `set NAME@ALIAS VALUE`. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The KeePass driver can be configured using the following attributes:

| Code                            | Description   | Origin | Default Value | Set from Connection String | Set from Set SQL-Statement | Set from Drivers File | Set from Log On |
|---------------------------------|---|--------|---------------|----------------------------|----------------------------|-----------------------|-----------------|
| analysis-enforce-row-uniqueness | Enforce rows to be unique for software analysis. A fingerprint is calculated from the whole row of data when the primary key column is unknown. | Shared | False         | ✓                          | ✓                          | ✓                     |                 |
| bulk-delete-page-size-rows      | Number of rows to delete per batch when bulk deleting.  | Shared | 10000         | ✓                          | ✓                          | ✓                     |                 |
| bulk-insert-page-size-bytes     | Approximate maximum size in bytes of batch when bulk inserting.   | Shared | 10000000      | ✓                          | ✓                          | ✓                     |                 |
| bulk-insert-page-size-rows      | Number of rows to insert per batch when bulk inserting.   | Shared | 10000         | ✓                          | ✓                          | ✓                     |                 |

| Code  | Description   | Origin        | Default Value | Set from Connection String | Set from Set SQL-Statement | Set from Driver's File | Set from Log On |
|---|---|---------------|---------------|----------------------------|----------------------------|------------------------|-----------------|
| force-case-sensitive-identifiers                    | Consider identifiers as case-sensitive independent of the platform capabilities.  | Shared        | False         | ✓                          | ✓                          | ✓                      |                 |
| forced-casing-identifiers                           | Forced casing of identifiers. Choose from: Unset, Lower, Upper and Mixed.   | Shared        |               | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-compress-sparse-arrays                | Whether to compress sparse arrays in result sets during compression.  | SQL Engine V1 | True          | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-correct-invalid-date                  | Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753. | SQL Engine V1 | False         | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-execution-profile-disk-path           | {res:itgen_pae_invantive_sql_execution_profile_disk_path}   | SQL Engine V1 |               | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-execution-profile-to-disk             | {res:itgen_pae_invantive_sql_execution_profile_to_disk}   | SQL Engine V1 | False         | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-forward-filters-to-data-containers    | Whether to forward filters to data containers.  | SQL Engine V1 | True          | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-share-byte-arrays                     | Whether to share the memory used by identical byte arrays in result sets during compression.  | SQL Engine V1 | True          | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-share-strings                         | Whether to share the memory used by identical strings in result sets during compression.  | SQL Engine V1 | True          | ✓                          | ✓                          | ✓                      |                 |
| invantive-sql-shuffle-fetch-results-data-containers | Whether to shuffle results fetched from data containers.  | SQL Engine V1 | False         | ✓                          | ✓                          | ✓                      |                 |
| invantive-use-cache                                 | Whether to cache the results of a query.  | SQL Engine V1 | True          | ✓                          | ✓                          | ✓                      |                 |
| log-native-calls-to-disk-max-events                 | Maximum number of call events to register from last activation.   | Shared        |               | ✓                          | ✓                          | ✓                      |                 |
| log-native-calls-to-disk-max-seconds                | Maximum number of seconds to register calls from last activation.   | Shared        |               | ✓                          | ✓                          | ✓                      |                 |
| log-native-calls-to-disk-on-error                   | Registers native calls to data container backend as disk files when the call raised an error.   | Shared        | False         | ✓                          | ✓                          | ✓                      |                 |
| log-native-calls-to-disk-on-success                 | Registers native calls to data container backend as disk files when the call raised no error.   | Shared        | False         | ✓                          | ✓                          | ✓                      |                 |
| log-native-calls-to-trace                           | Log native calls to data container backend on the trace.  | Shared        | False         | ✓                          | ✓                          | ✓                      |                 |
| maximum-length-identifiers                          | Non-default maximum length in characters of identifier names.   | Shared        |               | ✓                          | ✓                          | ✓                      |                 |

| Code                                      | Description   | Origin | Default Value | Set from Connection String | Set from Set SQL-Statement | Set from Driver's File | Set from Log On |
|---|---|--------|---------------|----------------------------|----------------------------|------------------------|-----------------|
| partition-slot-based-rate-limit-length-ms | Total length in milliseconds across all slots of a partition-based rate limit.  | Shared | 60000         | ✓                          |                            | ✓                      |                 |
| partition-slot-based-rate-limit-slots     | Number of slots per partition-based rate limit. Null means no slot-based rate limit.  | Shared |               | ✓                          |                            | ✓                      |                 |
| pre-request-delay-ms                      | Pre-request delay in milliseconds per request.  | Shared | 0             | ✓                          | ✓                          | ✓                      |                 |
| requested-maximum-usable-partitions       | Requested Maximum Usable Partitions   | Shared |               | ✓                          | ✓                          | ✓                      |                 |
| requested-page-size                       | Preferred number of rows to exchange per round trip; only effective on limited platforms such as AFAS Online.                         | Shared |               | ✓                          | ✓                          | ✓                      |                 |
| requests-parallel-max                     | Maximum number of parallel data requests from individual partitions on the data container.  | Shared | 32            | ✓                          | ✓                          | ✓                      |                 |
| slot-based-rate-limit-length-ms           | Total length in milliseconds across all slots of a slot-based rate limit.   | Shared | 60000         | ✓                          |                            | ✓                      |                 |
| slot-based-rate-limit-slots               | Number of slots of a slot-based rate limit. Null means no slot-based rate limit.  | Shared |               | ✓                          |                            | ✓                      |                 |
| standardize-identifiers                   | Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.    | Shared | True          | ✓                          | ✓                          | ✓                      |                 |
| standardize-identifiers-casing            | Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform. | Shared | True          | ✓                          | ✓                          | ✓                      |                 |

## 3 Catalog: KeePass

### 3.1 Schemas

#### 3.1.1 keepass\_entities: KeePass Entities

Catalog: KeePass

Schema: KeePass

Label: Entities

This is a read-only table function. The KeePass API may not support changing the data or the Invantive UniversalSQL driver for KeePass does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the KeePass API.

### Parameters of Table Function

The following parameters can be used to control the behaviour of the table function keepass\_entities. A value must be provided at all times for required parameters, but optional

parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

| Name     | Data Type | Required                            | Default Value | Documentation  |
|----------|-----------|-------------------------------------|---------------|--|
| keyfile  | varchar2  | <input type="checkbox"/>            |               | Key file for the KDBX file. Either password or key file must be specified. |
| password | varchar2  | <input type="checkbox"/>            |               | Password for the KDBX file. Either password or key file must be specified. |
| path     | varchar2  | <input checked="" type="checkbox"/> |               | Full path to the KDBX file with password entries.                          |

## Columns of Table Function

The columns of the table function `keepass_entities` are shown below. Each column has an SQL data type.

| Name                  | Data Type | Label | Required                 | Documentation |
|-----------------------|-----------|-------|--------------------------|---------------|
| AutoType              | boolean   |       | <input type="checkbox"/> |               |
| CustomBackgroundColor | varchar2  |       | <input type="checkbox"/> |               |
| CustomForegroundColor | varchar2  |       | <input type="checkbox"/> |               |
| Expires               | boolean   |       | <input type="checkbox"/> |               |
| ExpiryTime            | datetime  |       | <input type="checkbox"/> |               |
| IconId                | int32     |       | <input type="checkbox"/> |               |
| id                    | varchar2  |       | <input type="checkbox"/> |               |
| name                  | varchar2  |       | <input type="checkbox"/> |               |
| notes                 | varchar2  |       | <input type="checkbox"/> |               |
| OverrideUrl           | varchar2  |       | <input type="checkbox"/> |               |
| parent_entry_id       | varchar2  |       | <input type="checkbox"/> |               |
| password              | varchar2  |       | <input type="checkbox"/> |               |
| Tags                  | varchar2  |       | <input type="checkbox"/> |               |
| title                 | varchar2  |       | <input type="checkbox"/> |               |
| type                  | varchar2  |       | <input type="checkbox"/> |               |
| url                   | varchar2  |       | <input type="checkbox"/> |               |
| username              | varchar2  |       | <input type="checkbox"/> |               |

### 3.1.2 keepass\_entry\_custom\_sequences: KeePass Entry Custom Sequences

Catalog: KeePass

Schema: KeePass

Label: Entry Custom Sequences

This is a read-only table function. The KeePass API may not support changing the data or the Invantive UniversalSQL driver for KeePass does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the KeePass API.

## Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `keepass_entry_custom_sequences`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

| Name       | Data Type | Required                            | Default Value | Documentation  |
|------------|-----------|-------------------------------------|---------------|--|
| entry_uuid | varchar2  | <input checked="" type="checkbox"/> |               | UUID of the entry to query.  |
| keyfile    | varchar2  | <input type="checkbox"/>            |               | Key file for the KDBX file. Either password or key file must be specified. |
| password   | varchar2  | <input type="checkbox"/>            |               | Password for the KDBX file. Either password or key file must be specified. |
| path       | varchar2  | <input checked="" type="checkbox"/> |               | Full path to the KDBX file with password entries.                          |

## Columns of Table Function

The columns of the table function `keepass_entry_custom_sequences` are shown below. Each column has an SQL data type.

| Name          | Data Type | Label | Required                 | Documentation |
|---------------|-----------|-------|--------------------------|---------------|
| Sequence      | varchar2  |       | <input type="checkbox"/> |               |
| Target_window | varchar2  |       | <input type="checkbox"/> |               |

### 3.1.3 keepass\_entry\_file\_attachments: KeePass Entry File Attachments

Catalog: KeePass

Schema: KeePass

Label: Entry File Attachments

This is a read-only table function. The KeePass API may not support changing the data or the Invantive UniversalSQL driver for KeePass does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the KeePass API.

## Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `keepass_entry_file_attachments`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

| Name       | Data Type | Required                            | Default Value | Documentation  |
|------------|-----------|-------------------------------------|---------------|--|
| entry_uuid | varchar2  | <input checked="" type="checkbox"/> |               | UUID of the entry to query.  |
| keyfile    | varchar2  | <input type="checkbox"/>            |               | Key file for the KDBX file. Either password or key file must be specified. |
| password   | varchar2  | <input type="checkbox"/>            |               | Password for the KDBX file. Either password or key file must be specified. |
| path       | varchar2  | <input checked="" type="checkbox"/> |               | Full path to the KDBX file with password entries.                          |

## Columns of Table Function

The columns of the table function `keepass_entry_file_attachments` are shown below. Each column has an SQL data type.

| Name | Data Type | Label | Required                 | Documentation |
|------|-----------|-------|--------------------------|---------------|
| file | varchar2  |       | <input type="checkbox"/> |               |

### 3.1.4 keepass\_entry\_history: KeePass Entries History

Catalog: KeePass

Schema: KeePass

Label: Entries History

This is a read-only table function. The KeePass API may not support changing the data or the Invantive UniversalSQL driver for KeePass does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the KeePass API.

## Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `keepass_entry_history`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

| Name                    | Data Type             | Required                            | Default Value | Documentation  |
|-------------------------|-----------------------|-------------------------------------|---------------|--|
| <code>entry_uuid</code> | <code>varchar2</code> | <input checked="" type="checkbox"/> |               | UUID of the entry to query.  |
| <code>keyfile</code>    | <code>varchar2</code> | <input type="checkbox"/>            |               | Key file for the KDBX file. Either password or key file must be specified. |
| <code>password</code>   | <code>varchar2</code> | <input type="checkbox"/>            |               | Password for the KDBX file. Either password or key file must be specified. |
| <code>path</code>       | <code>varchar2</code> | <input checked="" type="checkbox"/> |               | Full path to the KDBX file with password entries.                          |

## Columns of Table Function

The columns of the table function `keepass_entry_history` are shown below. Each column has an SQL data type.

| Name                               | Data Type             | Label | Required                 | Documentation |
|------------------------------------|-----------------------|-------|--------------------------|---------------|
| <code>AutoType</code>              | <code>boolean</code>  |       | <input type="checkbox"/> |               |
| <code>CustomBackgroundColor</code> | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>CustomForegroundColor</code> | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>Expires</code>               | <code>boolean</code>  |       | <input type="checkbox"/> |               |
| <code>ExpiryTime</code>            | <code>datetime</code> |       | <input type="checkbox"/> |               |
| <code>IconId</code>                | <code>int32</code>    |       | <input type="checkbox"/> |               |
| <code>id</code>                    | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>name</code>                  | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>notes</code>                 | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>OverrideUrl</code>           | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>parent_entry_id</code>       | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>password</code>              | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>Tags</code>                  | <code>varchar2</code> |       | <input type="checkbox"/> |               |
| <code>title</code>                 | <code>varchar2</code> |       | <input type="checkbox"/> |               |

| Name     | Data Type | Label | Required                 | Documentation |
|----------|-----------|-------|--------------------------|---------------|
| type     | varchar2  |       | <input type="checkbox"/> |               |
| url      | varchar2  |       | <input type="checkbox"/> |               |
| username | varchar2  |       | <input type="checkbox"/> |               |

### 3.1.5 keepass\_entry\_string\_fields: KeePass Entry String Fields

Catalog: KeePass

Schema: KeePass

Label: Entry String Fields

This is a read-only table function. The KeePass API may not support changing the data or the Invantive UniversalSQL driver for KeePass does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the KeePass API.

## Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `keepass_entry_string_fields`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

| Name       | Data Type | Required                            | Default Value | Documentation  |
|------------|-----------|-------------------------------------|---------------|--|
| entry_uuid | varchar2  | <input checked="" type="checkbox"/> |               | UUID of the entry to query.  |
| keyfile    | varchar2  | <input type="checkbox"/>            |               | Key file for the KDBX file. Either password or key file must be specified. |
| password   | varchar2  | <input type="checkbox"/>            |               | Password for the KDBX file. Either password or key file must be specified. |
| path       | varchar2  | <input checked="" type="checkbox"/> |               | Full path to the KDBX file with password entries.                          |

## Columns of Table Function

The columns of the table function `keepass_entry_string_fields` are shown below. Each column has an SQL data type.

| Name | Data Type | Label | Required                 | Documentation |
|------|-----------|-------|--------------------------|---------------|
| key  | varchar2  |       | <input type="checkbox"/> |               |

| Name  | Data Type | Label | Required                 | Documentation |
|-------|-----------|-------|--------------------------|---------------|
| value | varchar2  |       | <input type="checkbox"/> |               |

### 3.1.6 keepass\_file\_metadata: KeePass File Metadata

Catalog: KeePass

Schema: KeePass

Label: File Metadata

This is a read-only table function. The KeePass API may not support changing the data or the Invantive UniversalSQL driver for KeePass does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the KeePass API.

## Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `keepass_file_metadata`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with ``select * from table(name1 => value1, name3 => value3)`` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

| Name     | Data Type | Required                            | Default Value | Documentation  |
|----------|-----------|-------------------------------------|---------------|--|
| keyfile  | varchar2  | <input type="checkbox"/>            |               | Key file for the KDBX file. Either password or key file must be specified. |
| password | varchar2  | <input type="checkbox"/>            |               | Password for the KDBX file. Either password or key file must be specified. |
| path     | varchar2  | <input checked="" type="checkbox"/> |               | Full path to the KDBX file with password entries.                          |

## Columns of Table Function

The columns of the table function `keepass_file_metadata` are shown below. Each column has an SQL data type.

| Name                | Data Type | Label | Required                 | Documentation |
|---------------------|-----------|-------|--------------------------|---------------|
| Color               | varchar2  |       | <input type="checkbox"/> |               |
| DatabaseDescription | varchar2  |       | <input type="checkbox"/> |               |
| DatabaseName        | varchar2  |       | <input type="checkbox"/> |               |
| DatabaseNameChanged | datetime  |       | <input type="checkbox"/> |               |

| Name                       | Data Type | Label | Required                 | Documentation |
|----------------------------|-----------|-------|--------------------------|---------------|
| DefaultUsername            | varchar2  |       | <input type="checkbox"/> |               |
| DefaultUsernameChanged     | datetime  |       | <input type="checkbox"/> |               |
| EntryTemplatesGroup        | varchar2  |       | <input type="checkbox"/> |               |
| EntryTemplatesGroupChanged | datetime  |       | <input type="checkbox"/> |               |
| Generator                  | varchar2  |       | <input type="checkbox"/> |               |
| HeaderHash                 | varchar2  |       | <input type="checkbox"/> |               |
| HistoryMaxItems            | int32     |       | <input type="checkbox"/> |               |
| HistoryMaxSize             | int32     |       | <input type="checkbox"/> |               |
| LastSelectedGroup          | varchar2  |       | <input type="checkbox"/> |               |
| LastTopVisibleGroup        | varchar2  |       | <input type="checkbox"/> |               |
| MaintenanceHistoryDays     | int32     |       | <input type="checkbox"/> |               |
| MasterKeyChanged           | datetime  |       | <input type="checkbox"/> |               |
| MasterKeyChangeForce       | int32     |       | <input type="checkbox"/> |               |
| MasterKeyChangeRec         | int32     |       | <input type="checkbox"/> |               |
| ProtectNotes               | boolean   |       | <input type="checkbox"/> |               |
| ProtectPassword            | boolean   |       | <input type="checkbox"/> |               |
| ProtectURL                 | boolean   |       | <input type="checkbox"/> |               |
| ProtectUsername            | boolean   |       | <input type="checkbox"/> |               |
| RecycleBinChanged          | datetime  |       | <input type="checkbox"/> |               |
| RecycleBinEnabled          | boolean   |       | <input type="checkbox"/> |               |
| RecycleBinUUID             | varchar2  |       | <input type="checkbox"/> |               |

### 3.1.7 keepass\_file\_metadata\_binaries: KeePass File Metadata Binaries

Catalog: KeePass

Schema: KeePass

Label: File Metadata Binaries

This is a read-only table function. The KeePass API may not support changing the data or the Invantive UniversalSQL driver for KeePass does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the KeePass API.

## Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `keepass_file_metadata_binaries`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a ``select * from table(value1, value2, value3)`` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select \* from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

| Name     | Data Type | Required                            | Default Value | Documentation  |
|----------|-----------|-------------------------------------|---------------|--|
| keyfile  | varchar2  | <input type="checkbox"/>            |               | Key file for the KDBX file. Either password or key file must be specified. |
| password | varchar2  | <input type="checkbox"/>            |               | Password for the KDBX file. Either password or key file must be specified. |
| path     | varchar2  | <input checked="" type="checkbox"/> |               | Full path to the KDBX file with password entries.                          |

## Columns of Table Function

The columns of the table function `keepass_file_metadata_binaries` are shown below. Each column has an SQL data type.

| Name       | Data Type | Label | Required                 | Documentation |
|------------|-----------|-------|--------------------------|---------------|
| Compressed | varchar2  |       | <input type="checkbox"/> |               |
| Id         | varchar2  |       | <input type="checkbox"/> |               |
| Value      | varchar2  |       | <input type="checkbox"/> |               |

## 4 Package: dcr\_metadata

### 4.1 Procedures

#### 4.1.1 `dcr_metadata.get_partitions`: KeePass Data container metadata package

Get all partitions.

Documentation:

List all partitions.

# Index

## - A -

analysis-enforce-row-uniqueness 2  
AutoType 4, 7

## - B -

bulk-delete-page-size-rows 2  
bulk-insert-page-size-bytes 2  
bulk-insert-page-size-rows 2

## - C -

Color 10  
Compressed 11  
CustomBackgroundColor 4, 7  
CustomForegroundColor 4, 7

## - D -

Database Driver 1  
DatabaseDescription 10  
DatabaseName 10  
DatabaseNameChanged 10  
DefaultUsername 10  
DefaultUsernameChanged 10

## - E -

Entities 4  
Entries History 7  
Entry Custom Sequences 6  
Entry File Attachments 6  
Entry String Fields 9  
entry\_uuid 6, 7, 9  
EntryTemplatesGroup 10  
EntryTemplatesGroupChanged 10  
Expires 4, 7  
ExpiryTime 4, 7

## - F -

file 6  
File Metadata 10  
File Metadata Binaries 11

force-case-sensitive-identifiers 2  
forced-casing-identifiers 2

## - G -

Generator 10

## - H -

HeaderHash 10  
HistoryMaxItems 10  
HistoryMaxSize 10

## - I -

IconId 4, 7  
invantive-sql-compress-sparse-arrays 2  
invantive-sql-correct-invalid-date 2  
invantive-sql-execution-profile-disk-path 2  
invantive-sql-execution-profile-to-disk 2  
invantive-sql-forward-filters-to-data-containers 2  
invantive-sql-share-byte-arrays 2  
invantive-sql-share-strings 2  
invantive-sql-shuffle-fetch-results-data-containers 2  
invantive-use-cache 2

## - K -

KeePass 1, 4, 6, 7, 9, 10, 11  
keepass\_entities 4  
keepass\_entry\_custom\_sequences 6  
keepass\_entry\_file\_attachments 6  
keepass\_entry\_history 7  
keepass\_entry\_string\_fields 9  
keepass\_file\_metadata 10  
keepass\_file\_metadata\_binaries 11  
key 9  
keyfile 4, 6, 7, 9, 10, 11

## - L -

LastSelectedGroup 10  
LastTopVisibleGroup 10  
log-native-calls-to-disk-max-events 2  
log-native-calls-to-disk-max-seconds 2  
log-native-calls-to-disk-on-error 2  
log-native-calls-to-disk-on-success 2  
log-native-calls-to-trace 2

## - M -

MaintenanceHistoryDays 10  
MasterKeyChanged 10  
MasterKeyChangeForce 10  
MasterKeyChangeRec 10  
maximum-length-identifiers 2

## - N -

name 4, 7  
notes 4, 7

## - O -

OverrideUrl 4, 7

## - P -

parent\_entry\_id 4, 7  
partition-slot-based-rate-limit-length-ms 2  
partition-slot-based-rate-limit-slots 2  
password 4, 6, 7, 9, 10, 11  
path 4, 6, 7, 9, 10, 11  
pre-request-delay-ms 2  
ProtectNotes 10  
ProtectPassword 10  
ProtectURL 10  
ProtectUsername 10

## - R -

RecycleBinChanged 10  
RecycleBinEnabled 10  
RecycleBinUUID 10  
requested-maximum-usable-partitions 2  
requested-page-size 2  
requests-parallel-max 2

## - S -

Sequence 6  
slot-based-rate-limit-length-ms 2  
slot-based-rate-limit-slots 2  
standardize-identifiers 2  
standardize-identifiers-casing 2

## - T -

Tags 4, 7  
Target\_window 6  
title 4, 7  
type 4, 7

## - U -

url 4, 7  
username 4, 7

## - V -

Value 9, 11



# *invantive* the **SQL** company

Invantive B.V.  
Biesteweg 11  
3849 RD Hierden  
the Netherlands

Tel: +31 88 00 26 500  
Fax: +31 84 22 58 178  
info@invantive.com  
invantive.com

IBAN NL25 BUNQ 2098 2586 07  
Chamber of Industry and Commerce  
13031406  
VAT NL812602377B01  
RSIN 8122602377  
Managing Director: Guido Leenders  
Registered office: Roermond