

CB62-E Bullet Camera

Prominent 4K coverage
in outdoor environments



Overview

The CB62-E Bullet Camera features a 1 / 2.8" progressive CMOS image sensor, varifocal lens with 2.86x optical zoom, and IR LEDs with 98 feet / 30 meters of range for detailed 4K coverage in various lighting conditions as well as in inclement weather. The CB62-E features an onboard CV22S Ambarella processor for advanced, privacy-sensitive analytics like AI-powered search, [occupancy trends](#), line crossing, loitering, and person of interest (POI) alerts. In addition, the CB62-E supports [license plate recognition](#) (LPR), enabling the device to capture license plates from vehicles traveling at speeds of up to 80 mph / 128 kph across as many as three lanes of traffic. With its highly visible form factor, the CB62-E also serves as a deterrent to potential threats. Its LPR capabilities can also be used to grant access at vehicle gates, providing seamless entry to known vehicles while keeping out unauthorized ones.

The CB62-E is constructed with a robust aluminum unibody and withstands extreme conditions with an IP67 weather rating and IK10 impact rating. The camera's design includes a built-in pigtail connector that expedites PoE cabling without requiring disassembly. Installation and setup are easy to track using the LED status indicator.

Key features

Superior image quality

- 1 / 2.8" progressive CMOS image sensor
- 4K resolution
- Varifocal lens with 2.86x optical zoom
- 98 feet / 30 meters of IR range for optimal nighttime viewing

Advanced analytics

- Onboard CV22S Ambarella processor enables people and vehicle analytics
- License plate recognition capabilities capture license plates at speeds up to 80 mph / 128 kph
- AI-powered search and AI-powered alerts
- Occupancy trends for operational insights

Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 90 days (512GB - 2TB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

Easy installation

- Built-in pigtail connector for simplified PoE cabling
- Mounting plate and screw pack included
- LED light status indicator

Durability and weather protection

- Factory-sealed robust aluminum unibody
- IP67 weather rating
- IK10 impact rating
- Operability between -40°F to 122°F / -40°C to 50°C



CB62-E

Tech specs

Camera features

Image sensor	1 / 2.8" progressive CMOS	Shutter speed	1 / 30 sec. to 1 / 10,000 sec.
Sensor resolution¹	4K (3840 x 2160)	Day/night	IR-cut filter for day and night function
Lens type	Varifocal; motorized zoom	IR-cut filter	Yes
Focal length	2.8mm – 8mm	IR range	98ft / 30m
Aperture	F1.3 – F2.4	Minimum illumination	0.009 lux @ F1.9 (color) 0 lux with IR illuminators on
Iris	P-Iris	Onboard storage	Capacity: from 512GB to 2TB Card: microSD, SDXC
Field of view (after LDC²)	Horizontal: 107° - 43° (106° - 41°) Vertical: 62° - 24° (62° - 24°) Diagonal: 126° - 49° (119° - 48°)	CPU	Ambarella CV22S66
Camera movement	Tilt: 0° to 90° Pan: 360° Rotation: 360°		

Standard video settings

Compression	H.265, H.264	Historical video settings	Adaptive quality ¹
Frame rate³	24fps	Live streaming settings	High quality (HQ): up to 4,500 kbps (default) Standard quality (SQ): up to 600 kbps

Standard audio settings

Audio	Not supported
--------------	---------------

Power and network

Power input⁴	With IR: IEEE 802.3at Type 2 PoE+ Without IR: IEEE 802.3af Type 1 PoE Extended temperature range: IEEE 802.3at Type 2 PoE+	Connectivity	RJ-45 cable connector for network/PoE connection; 10 / 100 Mbps
Power consumption⁴	With IR: 37-57V, 0.40-0.26A, 14.9W Without IR: 37-57V, 0.11-0.08A, 4.3W Extended temperature range: 37-57V, 0.64-0.39A, 23.7W	RTSP	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio: not supported

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>.

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below 14°F / -10°C and assumes IR will be enabled.



CB62-E

Tech specs



General

Operating temperature	-40°F to 122°F / -40°C to 50°C	LED indicator	System power and status indicator
Humidity	0 to 90%	Warranty	10 years
Certifications	FCC, ICES, CE, UKCA, RCM, VCCI, KCC, BIS, NOM, NTRA, UL/cUL/IEC 62368-1, IP67 weather rating, IK10 impact rating, FY2019 NDAA compliant	Included accessories	4x M4x8 screws, 4x TP4x30 mount screws, mount plate, junction box adapter, junction box cover, T25 hand tool

Mechanical

Weight	Camera: 51.64oz / 1464g Mount plate: 1.16oz / 33g	Body	Aluminum
Dimensions	L: 10.00in / 254.0mm, Ø: 3.35in / 85.0mm		

Dimensions



Software capabilities

Alerts	Camera status, motion detection, people detection, vehicle detection, person of interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts	Streaming and storage	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
People analytics	People search, attribute search, face search, occupancy trends, motion search, trajectory analysis, selective face blurring, AI-powered search	Sharing and privacy	Live links, live face blur, privacy regions, audit log
Vehicle analytics	Vehicle search, attribute search, motion search, trajectory analysis, occupancy trends, AI-powered search	License plate recognition	License plate of interest alerts, license plate indexing



Ordering Information

CB62-E pricing

Model number	MP ¹	WDR	Lens	IR range	Onboard storage	Maximum SQ onboard retention ¹	People/vehicle analytics
CB62-512E-HW	4K	✓	Zoom	98ft / 30m	512GB	30 Days	✓
CB62-1TBE-HW	4K	✓	Zoom	98ft / 30m	1TB	60 Days	✓
CB62-2TBE-HW	4K	✓	Zoom	98ft / 30m	2TB	90 Days	✓

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>.