

CD32-E Outdoor Dome Camera

Advanced 3MP coverage for monitoring outdoor environments



Overview

The CD32-E outdoor dome camera features a 1 / 2.8" progressive CMOS image sensor and 49 feet / 15 meters of IR range to provide supplemental 3MP coverage in a variety of lighting conditions. The CD32-E includes an onboard CV25S Ambarella processor for advanced analytics like AI-powered search, [occupancy trends](#), line crossing, loitering, and person of interest (POI) alerts. The CD32-E excels in exterior areas with moderate foot and vehicle traffic where advanced analytics and alerts deliver valuable insights into specific events.

Certified with IP67 weather and IK10 impact ratings, the CD32-E can withstand extreme temperatures and excessive precipitation without compromising aesthetics. Installation and setup are easy to track using the LED status indicator, while the included mount plate makes the device straightforward to install on exterior walls or flat overhangs.

Key features

Clear image quality

- 1 / 2.8" progressive CMOS image sensor
- 3MP resolution
- 49 feet / 15 meters of IR range for well-defined nighttime viewing

Durability and weather protection

- IP67 weather rating
- IK10 impact rating
- Operability between -40°F to 122°F / -40°C to 50°C

Easy installation

- Mounting plate and screw pack included
- LED light status indicator
- Digital mute switch to quickly enable or disable audio

Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 90 days (256GB - 768GB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

Advanced analytics

- Onboard CV25S Ambarella processor enables people and vehicle analytics
- AI-powered search and AI-powered alerts
- Occupancy trends for operational insights



CD32-E

Tech specs

Camera features

Image sensor	1 / 2.8" progressive CMOS	Shutter speed	1 / 30 sec. to 1 / 10,000 sec.
Sensor resolution¹	3MP (2048 x 1536)	Day/night	IR-cut filter for day and night function
Lens type	Fixed	IR-cut filter	Yes
Focal length	2.8mm	IR range	49ft / 15m
Aperture	F1.6	Minimum illumination	0.009 lux @ F1.9 (color) 0 lux with IR illuminators on
Iris	Fixed	Onboard storage	Capacity: from 256GB to 768GB Card: microSD, SDXC
Field of view (after LDC²)	Horizontal: 97° (78°) Vertical: 71° (63°) Diagonal: 128° (91°)	CPU	Ambarella CV25S88
Sensor movement	Tilt: 60° Pan: 355° Rotation: 180°		

Standard video settings

Compression	H.265, H.264	Historical video settings	Adaptive quality ¹
Frame rate³	24fps	Live streaming settings	High quality (HQ): up to 3,000 kbps (default) Standard quality (SQ): up to 600 kbps

Standard audio settings

Audio	Supported	Interface	Built-in microphone
Audio capacity	One-way audio	Effective range	16ft / 5m

Power and network

Power input⁴	With IR: IEEE 802.3af Type 1 PoE Without IR: IEEE 802.3af Type 1 PoE Extended temperature range: IEEE 802.3at Type 2 PoE+	Connectivity	RJ-45 cable connector for network/PoE connection; 10 / 100 Mbps
Power consumption⁴	With IR: 37-57V, 0.23-0.15A, 8.6W Without IR: 37-57V, 0.11-0.07A, 4.3W Extended temperature range: 37-57V, 0.46-0.30A, 16.9W	RTSP	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio: supported

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>.

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below 14°F / -10°C and assumes IR will be enabled.



CD32-E

Tech specs



General

Operating temperature	-40°F to 122°F / -40°C to 50°C	LED indicator	System power and status indicator
Humidity	0 to 90%	Warranty	10 years
Certifications	FCC, ICES, CE, UKCA, RCM, VCCI, KCC, BIS, NOM, UL/cUL/IEC 62368-1, CB, IP67 weather rating, IK10 impact rating, FY2019 NDAA compliant	Included accessories	Setup guide, wall mount screws and anchors (4x), T10 security torx screwdriver, mounting template, cable gland wrench, desiccant pack, conduit adapter

Mechanical

Weight	Camera: 29.88oz / 847g Mount plate: 6.14oz / 174g	Body	Aluminum, plastic dome trim
Dimensions	Ø: 6.10in / 155.0mm, H: 4.51in / 114.6mm with mount plate Ø: 6.10in / 155.0mm, H: 4.24in / 107.6mm without mount plate		

Dimensions



Software capabilities

Alerts	Camera status, motion detection, people detection, vehicle detection, person of interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts	Streaming and storage	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
People analytics	People search, attribute search, face search, occupancy trends, motion search, trajectory analysis, selective face blurring, AI-powered search	Sharing and privacy	Live links, live face blur, privacy regions, audit log
Vehicle analytics	Vehicle search, attribute search, motion search, trajectory analysis, occupancy trends, AI-powered search		



Ordering information

CD32-E pricing

Model number	MP ¹	WDR	Lens	IR range	Onboard storage	Maximum SQ onboard retention ¹	People/ vehicle analytics	US cost (MSRP) ^{USD}	WW cost (MSRP) ^{USD}
CD32-256E-HW	3MP	✓	Fixed	49ft / 15m	256GB	30 Days	✓	\$1,199	\$1,099
CD32-512E-HW	3MP	✓	Fixed	49ft / 15m	512GB	60 Days	✓	\$1,899	\$1,799
CD32-768E-HW	3MP	✓	Fixed	49ft / 15m	768GB	90 Days	✓	\$2,599	\$2,499

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>.



Ordering information

Video Security software license pricing (new/capacity increase)

Model number	Description	US cost (MSRP) ^{USD}	WW cost (MSRP) ^{USD}
LIC-CAM-1Y-CAP	Verkada 1-Year Camera License, Capacity Increase	\$249	\$249
LIC-CAM-3Y-CAP	Verkada 3-Year Camera License, Capacity Increase	\$659	\$659
LIC-CAM-5Y-CAP	Verkada 5-Year Camera License, Capacity Increase	\$1,099	\$1,099
LIC-CAM-10Y-CAP	Verkada 10-Year Camera License, Capacity Increase	\$2,199	\$2,199

Video Security software license pricing (renewal)

Model number	Description	US cost (MSRP) ^{USD}	WW cost (MSRP) ^{USD}
LIC-CAM-1Y-RNW	Verkada 1-Year Camera License, Renewal	\$249	\$249
LIC-CAM-3Y-RNW	Verkada 3-Year Camera License, Renewal	\$659	\$659
LIC-CAM-5Y-RNW	Verkada 5-Year Camera License, Renewal	\$1,099	\$1,099
LIC-CAM-10Y-RNW	Verkada 10-Year Camera License, Renewal	\$2,199	\$2,199



Accessories

Recommended accessories

Model number	Description
ACC-CAM-SHIELD-1	Verkada Camera Weather Shield
ACC-MNT-ANGLE-1	Verkada Angle Mount
ACC-MNT-ARM-1	Verkada Arm Mount
ACC-MNT-CJBOX-1	Verkada Circle Junction Box Mount
ACC-MNT-CLIP-1	Verkada Tile Clips Mount
ACC-MNT-CORNER-1	Verkada Corner Mount
ACC-MNT-LBRAC-1	Verkada L-Bracket Mount
ACC-MNT-PEND-1	Verkada Pendant Cap Mount
ACC-MNT-POLE-1	Verkada Pole Mount
ACC-MNT-UPEND-1	Verkada Umbrella Pendant Cap Mount
INJ-POE-PLUS	Verkada PoE+ (802.3at Type 2) Injector, GigE