



Product Catalog

Version 3.62

This catalog includes components for IronRidge® solar mounting systems.

Our products are supported with powerful online tools and experienced sales and service teams—ready to help. Call **1-800-227-9523** or email support@ironridge.com.

Overview

- 1 Overview

Aire[®] Racking System

- 2 Aire[®] Components
- 3 Aire[®] Components, US

XR Rail[®] Racking System

- 4 Overview
- 5 XR Rail[®]
- 6 BOSS[®] Splices
- 7 UFO[®] Mid Clamps
- 8 XR Mid Clamps (US)
- 9 EFO[™] End Clamps
- 10 Eclipse Hidden End Clamps
- 11 CAMO[™]
- 12 Calculating Rail Length
- 13 End Caps
- 14 Wire Clips
- 15 Grounding Lugs
- 16 Microinverter / Power Optimizer Bonding Hardware

Flush Mount Attachments

- 17 Overview
- 18 FlashFoot2[®]
- 19 FlashVue[®]
- 20 Comp Shingle Flashing (US)
- 21 Knockout Tile
- 22 Flat Tile Fly
- 23 Slotted L-Foot
- 24 Bonding Attachment Hardware
- 25 Contour[™] Trim
- 44 HUG[™] Halo UltraGrip[™]
- 44 BUG[™] Conduit Mount

Tilt Mount

- 26 Overview
- 27 Fixed Tilt Legs
- 28 Flat Roof Attachment

BX[™] Ballasted Mount

- 29 Overview
- 30 BX Chassis
- 31 BX Clamps
- 32 BX Bonding Jumpers
- 33 BX MLPE Mounting Hardware
- 34 BX PV Module Grounding Lug
- 35 BX Cable Ties
- 36 BX Flat Roof Mounting Assembly

Ground Mount

- 37 Overview
- 38 Top Caps
- 39 Bonded Rail Connectors
- 40 Hex Head Set Screws
- 41 Diagonal Braces
- 42 Schedule 40 Pipe Summary

QuickMount[®] Components

- 43 RockIt[®] Rail-Less System
- 44 ClickFit[®] Racking System
- 45 L-Feet Options
- 45 Comp Shingle Mounts
- 45 HUG[™] Halo UltraGrip[™]
- 45 BUG[™] Conduit Mount
- 46 All Tile Hook & Tile Roof Mounts
- 47 Lynx[™] Metal Roof Clamp
- 47 JayBox[™] Junction Box
- 47 Other Mounts & Accessories

Overview



The **IronRidge® Flush Mount Systems** are rail-based system for mounting solar modules on pitched roofs. The system utilizes IronRidge Aire® Rails or XR Rails® with a variety of roof attachments to support extreme wind and snow loads. Each system uses only aluminum and stainless steel components to ensure complete corrosion resistance.



The **IronRidge® Tilt Mount System** is an attached, fixed-tilt assembly for mounting solar modules on flat roofs. The system pairs IronRidge XR Rails® with North & South Tilt Legs to achieve a wide range of mounting angles, while also supporting extreme wind and snow loads.



The **IronRidge® Ground Mount System** scales to support a wide range of site and terrain challenges. This system consists of components that allow for installer-supplied steel pipe or mechanical tubing to combine with our XR100® or XR1000® Rail assembly for simple, rapid, cost effective ground mounting.



The **IronRidge® BX Ballasted System** delivers superior power density and design flexibility to flat roof solar arrays. Made of a glass reinforced composite, the BX Chassis is engineered for extreme structural loading, yet is also shaped to be roof-friendly and easy to install.

QuickMount®




QuickMount® roof attachments and accessories are a part of the IronRidge® solar mounting family of components. Respect the roof!

Aire® Racking System

IronRidge.com/Aire

Aire® Rails

Item Number	Description
AE-A1-170M	Aire Rail A1, Mill, 170"
AE-A1-170B	Aire Rail A1, Black, 170"
AE-A2-170M	Aire Rail A2, Mill, 170"
AE-A2-170B	Aire Rail A2, Black, 170"



Aire® Rail Ties

Item Number	Description
AE-A1TIE-01-M1	Aire Tie, A1 (Bonded Splice)
AE-A2TIE-01-M1	Aire Tie, A2 (Bonded Splice)



Aire Lock® Clamps

Item Number	Description
AE-MID-01-B1	Aire Lock Mid, Black (30mm - 40mm)
AE-END-01-B1	Aire Lock End, Black (30mm - 40mm)
AE-STLTH-01-M1	Aire Lock Stealth (Hidden End Clamp)



Attachment Hardware

Item Number	Description
AE-DOCK-02-B1	Aire Dock, Black (for all approved attachments)
AE-DOCK-TM02-B1	Aire Dock, Tilt Mount, Black (N-S Tilt Leg Dock Pair)



Electrical & Grounding

Item Number	Description
AE-MLPE-01-M1	20mm T-Bolt w/ Nut, Patch, SS (6 Bags of 50)
AE-LUG-01-M1	Aire Lug
AE-CLIP-01-B1	Aire Clip (10 Bags of 120 Aire Clips)



End Caps

Item Number	Description
AE-A1CAP-01-B1	Aire Cap, A1
AE-A2CAP-01-B1	Aire Cap, A2



Aire Tile Attachment

Item Number	Description
AE-ATH-02-M1	Aire All Tile Hook (Incl. 2 Lags)



Aire® Racking System, US Production

IronRidge.com/Aire

Aire® Rails

Item Number	Description
AE-A1-170M-US	Aire Rail A1, Mill, 170", US Production
AE-A1-170B-US	Aire Rail A1, Black, 170", US Production



Aire® Rail Ties

Item Number	Description
AE-A1TIE-01-M1-US	Aire Tie, A1 (Bonded Splice), US Production



Aire Lock® Clamps

Item Number	Description
AE-USMID-01-B1-US	Aire Lock Mid, Black (30mm - 40mm), US Production
AE-END-01-B1-US	Aire Lock End, Black (30mm - 40mm), US Production



Electrical & Grounding

Item Number	Description
AE-MLPE-01-M1-US	Aire MLPE Mount, US Production



XR Rail® Racking System



Our product development team strives to keep things simple and intuitive for installers while accommodating a wide range of mounting scenarios. As a result, we offer three complementary types of rail within the XR Rail® Family. Please refer to our website or contact our customer service team so that we can best assist in determining which rail assembly is best for you and your specific project.

XR Rail®


Item Number	Description	Item Number	Description
XR-10-168M	XR10, Rail 168", Mill	XR-100-184M	XR100, Rail 184", Mill
XR-10-168B	XR10, Rail 168", Black	XR-100-184B	XR100, Rail 184", Black
XR-10-184M	XR10, Rail 184", Mill	XR-100-204M	XR100, Rail 204", Mill
XR-10-184B	XR10, Rail 184", Black	XR-100-204B	XR100, Rail 204", Black
XR-100-168M	XR100, Rail 168", Mill	XR-1000-170M	XR1000, Rail 170", Mill
XR-100-168B	XR100, Rail 168", Black	XR-1000-210M	XR1000, Rail 210", Mill

Item Number	Description
XR-10-168M-US	XR10, Rail 168" (14 Feet) Mill, US Production
XR-10-168B-US	XR10, Rail 168" (14 Feet) Black, US Production
XR-100-168M-US	XR100, Rail 168" (14 Feet) Mill, US Production
XR-100-168B-US	XR100, Rail 168" (14 Feet) Black, US Production



The XR Rail Family offers the strength of a curved rail in three targeted sizes. Each size supports specific design loads, while minimizing material costs. Depending on your location, there is an XR Rail to match. XR1000® is a heavyweight among solar mounting rails. It's built to handle extreme climates, spanning 12 feet or more for commercial applications. XR100® is the ultimate residential mounting rail. It supports a range of wind and snow conditions, while maximizing spans. XR10® is a sleek, low-profile mounting rail, perfectly matched to regions with light or no snow. It achieves 6 foot spans, while also staying light and economical.

BOSS® Bonded Structural Splices




Item Number	Description
XR10-BOSS-01-M1	Bonded Structural Splice, XR10
XR100-BOSS-01-M1	Bonded Structural Splice, XR100
XR1000-BOSS-01-M1	Bonded Structural Splice, XR1000

Item Number	Description
XR10-BOSS-01-M1-US	Bonded Splice, XR10 , US Production
XR100-BOSS-01-M1-US	Bonded Splice, XR100, US Production



The BOSS® (Bonded Structural Splice) provides a truly seamless, hidden connection for XR Rails®. Built-in, one-piece springs feature bonding teeth that bite inside the rail, creating a bonded rail connection and meeting all UL standards without any extra tools or hardware. In addition, BOSS® eliminates installation restrictions. Place it anywhere except the outside cantilever.

UFO® Mid Clamps



Item Number	Description
UFO-CL-01-A1	Universal Module Clamp, Clear
UFO-CL-01-B1	Universal Module Clamp, Black

The IronRidge UFO® (Universal Fastening Object) is a single-size, single-piece fastener, built to quickly and securely bond any solar modules to XR Rails. It comes fully-lubricated and fully-assembled, and it looks just as good as it performs. It comes in two finishes: Clear and Black.

XR Mid Clamps (US)



Item Number	Description
XR-MID-01-B1-US	XR Mid Clamp (30-40mm), Black, US Production



The XR Mid Clamp is a domestically-produced mid clamp for XR Rails. It can be used instead of the UFO® to meet domestic content requirements for XR Flush Mount system customers that need “Structural Fasteners” for Notice 2025-08. This can help to to comply with most financing entity requirements (TPO).

EFO™ End Clamps


Item Number	Description
UFO-END-01-A1	End Fastening Object (End Clamp, 30-40MM), Mill
UFO-END-01-B1	End Fastening Object (End Clamp, 30-40MM), Black

Item Number	Description
UFO-END-01-A1-US	End Fastening Object (End Clamp, 30-40MM), Mill, US Production
UFO-END-01-B1-US	End Fastening Object (End Clamp, 30-40MM), Black, US Production



The IronRidge EFO™—End Fastening Objects—provide enhanced engagement on modules and support frame heights of 30 to 40mm. This universal end clamp is a single-piece component that speeds up installation times, especially when modules vary by project.

Eclipse



Item Number	Description
ECL-01-A1	Eclipse (XR Hidden End Clamp), Clear

Eclipse is a hidden end clamp for XR Rails[®]. It stays hidden, out of sight, while securing solar modules flush to rail ends. This creates a clean and sleek appearance that homeowners are fond of. Eclipse works with nearly all solar modules and installs with a simple 7/16" socket.

CAMO™


Item Number	Description
CAMO-01- M1	Hidden End Cam (Universal Clamp)

CAMO™ is a tool-less, end-cam clamp, designed to bond and secure while staying completely hidden under the solar module. It comes as one piece, fully assembled, and has been tested up to 5 times to ensure bonding after installation, removal, and re-installation. Certified to IBC ASCE/SEI-7 and UL 2703.

NOTE: CAMO™ is not intended for installation on any island or within 3 miles from any coastline and 2 miles from saltwater bays and inlets. CAMO™ installed in these regions will not be covered by the IronRidge Product Warranty. For a hidden end clamp for XR Rail® systems in these regions, please refer to Eclipse on the previous page.

Calculating Rail Length

Calculate the row lengths as follows:

1. Add module widths.
2. Add width of UFO® between modules.
3. Add allowances for UFO® and Stopper Sleeves on ends of rail.

Depending on the location of the UFO®, the clearance values will differ.

Location	UFO®
Mid Clamp	0.375"
End Clamp	1.0"

For example, to mount five modules that are each 40" wide (in portrait), the row length is calculated as follows:

Step	UFO®
1. Add module widths	$5 \times 40" = 200"$
2. Add width of mid clamps between modules	$4 \times 0.375" = 1.5"$
3. Add allowances for end clamps	$2 \times 1" = 2$
Total length of row	$203.5" = 16.96'$

Two 17' rails will be required to mount this row of five modules.

IronRidge stock rail lengths: 11', 14', 17'. Custom lengths available via special order. Contact IronRidge Customer Service for additional details at 800-227-9523, or support@ironridge.com.

End Caps



XR1000®



XR100®



XR10®

Item Number	Description
XR-1000-CAP01-B1	End Cap, XR1000® (L-R Pair)
XR-100-CAP01-B1	End Cap, XR100® (L-R Pair)
XR-10-CAP01-B1	End Cap, XR10® (L-R Pair)

End Caps provide a finished look to rails, while preventing the collection of water and debris inside the rail. End Caps are molded from black polycarbonate with UV protection.


Wire Clips



Item Number	Description
XR-WC-01-B1	Wire Clip, 20pcs

Wire Clips fit XR Rails®, and accommodate up to ten 5mm panel wires, or one MC4, one Enphase wire and one dual Enphase wire. Molded from black polycarbonate with UV protection.


Grounding Lugs



Item Number	Description
XR-LUG-04-A1	Grounding Lug, Low Profile

A single Grounding Lug connects an entire row of PV modules to the grounding conductor.

Microinverter / Power Optimizer Bonding Hardware



Item Number	Description
BHW-M1-01-A1	Microinverter Bonding Hardware, T-Bolt

Use IronRidge® Microinverter Bonding Hardware to bond compatible microinverters and power optimizers to the racking system.

COMPATIBLE PRODUCTS

Enphase - M250-72, M250-60, M215-60, C250-72, S230, S280


Darfon - MIG240, MIG300, G320, G640

Solar Edge - P300, P320, P400, P405, P600, P700, P730, P800p, P800s

Flush Mount Overview



The IronRidge Flush Mount Systems are rail-based systems for mounting solar modules on pitched roofs. The systems utilize IronRidge XR Rails® or Aire® Rails with a variety of roof attachments to support extreme wind and snow loads. The entire system uses only aluminum and stainless steel components to ensure complete corrosion resistance.




[Download AutoCAD File](#)
[Download PDF Preview](#)

FlashFoot2®


Item Number	Description
FF2-02-M2	FlashFoot2®, Mill
FF2-02-B2	FlashFoot2®, Black

IronRidge FlashFoot2® features a completely redesigned seal that is both elevated and fully encapsulated, protecting against water intrusion. The flashing's profile minimizes interference with roofing nails. FlashFoot2® has alignment markers help to quickly align the flashing with pilot holes. Twisting on the Cap makes FlashFoot2® ready to mount XR Rails®. Comes with flashing, lag bolt, and Cap.

FlashVue®



GripCap+®
(Sold Separately)

Item Number	Description
FV-01-M1	FlashVue®, Mill (GripCap® Included)
FV-01-B1	FlashVue®, Black (GripCap® Included)
FV-GCP-01-B1	GripCap+®, Black

We set out to design a flashing that checked all the boxes: fully waterproof, fast and easy to install correctly, economical, and strong enough to handle every environmental condition. FlashVue® does it all. The optimized flashing design features a large viewport, for easy alignment with the pilot hole. And the GripCap® and GripCap+® sit snugly in place, so the lag can be driven single-handedly.

GripCap+® adds another full inch of height and replaces the standard GripCap® on FlashVue®. This is helpful on older roofs with varying undulations that can make low-profile mounts a challenge.

Comp Shingle Flashing (US Made)



Item Number	Description	
FLSH-01-B1-US	Flashing, 8x12 and Lag Screw, Comp Shingle, Black, US Production	
LFT-FLSH03-B1-US	Slotted L-Foot for Comp Shingle Mount, Black, US Production	

The Comp Shingle Flashing (US) is a domestically-produced, versatile solution for attaching solar to composition shingle roofs. The flashing installs quick and easy with a single fastener. Its patented watertight technology utilizes a grommet-integrated flashing that combines with the Slotted L-Foot (US) for a seal that maintains roof integrity.

Knockout Tile & Tile Replacement Flashings



Item Number	Description
KOB-1L02-B1	Tile Replacement Base (Incl. 1 Open-Slotted L-Foot (Black), 1 Lag and Hardware) - Knockout Tile
KOF-F01-B1	Tile Replacement Flashing Flat, Black
KOF-S01-T1	Tile Replacement Flashing S, Black
KOF-W01-T1	Tile Replacement Flashing W, Black
KODF-1L01-M1	Knockout Tile Deck Flashing (Optional)

IronRidge Knockout Tile is a tile replacement mount that installs fast and works on flat, S, or W tiles, as well as, on roofs with battens or roofs that are battenless. Its simple base allows you to put it anywhere within the flashing pad on the rafter, and just punch a small hole in the flashing where it is needed—with no cutting or grinding. Open-Slotted L-Foot included. Knockout Tile is fully tested to our rigorous standards, certified as a system with XR Rail® and covered by our 25-year warranty. The Knockout Tile Deck Flashing can add an extra layer of water protection, when necessary.

The Tile Replacement Flashing come in black-anodized aluminum and are sold separately. They can be used in combination with the Knockout Tile Base (Tile Replacement Base) or used with our other tile roof attachments: All Tile Hook and Flat Tile Fly.


Flat Tile Fly



Item Number	Description
FTH-01-M1	Flat Tile Fly (Incl. 2 Lags)

The Flat Tile Fly joins offers a cost-effective, flat-tile-hook solution with an open-slot for installation ease. It comes with 7/16-inch-head lag screws and is evaluated to TAS-100(A) and listed to UL 2703 for XR and Aire racking systems.

Slotted L-Foot



Item Number	Description
LFT-03-M1	Slotted L-Foot, Mill
LFT-03-B1	Slotted L-Foot, Black

Our Slotted L-feet are engineered for most roof mounting applications. Vertical slots allow for easily dropping in rails with pre-attached hardware and provide adjustability to account for roof irregularities. Our L-feet are manufactured using 6000 series aluminum and are available in mill or black-anodized finish.

Bonding Attachment Hardware



Item Number	Description
BHW-SQ-03-A1	Square Bolt Bonding Hardware, 1 pc
BHW-TB-03-A1	T-Bolt Bonding Hardware, 1 pc

Attachment bonding hardware available in both square bolt and t-bolt options, based on personal preference. Bonding hardware is used to attach and bond the rail to the FlashFoot2®, Slotted L-Foot, or a third-party roof attachment. The nut allows installers to use the same 7/16" socket as the rest of the system.

Contour™ Trim



Contour™ Trim



Contour™ Splice



Contour™ Clamp



Contour™ Outer Corner Cap



Contour™ Inner Corner Cap



Contour™ End Caps

Item Number	Description
CTR-TR84-01-B1	Contour Trim, 84"
CTR-SPLC-01-M1	Contour Splice
CTR-CL-01-B1	Contour Clamp
CTR-OUT-01-B1	Contour Corner Cap, Outer
CTR-IN-01-B1	Contour Corner Cap, Inner
CTR-CAP-01-B1	Contour End Caps (L-R Pair)

IronRidge Contour™ Trim elevates the look of any solar array by providing a sleek trim (or skirt) across the south edge or around the perimeter to hide components that are visible beneath the solar panels. Homeowners want the solar on their home to meet their energy needs, while not detracting from their home's aesthetics. Contour™ will make any array look great, and have your crew on and off the roof in a snap.

Fixed Tilt Legs



Item Number	Description
TM-FTL-010	Kit, Fixed Tilt Leg, 10", Mill
TM-FTL-015	Kit, Fixed Tilt Leg, 15", Mill
TM-FTL-020	Kit, Fixed Tilt Leg, 20", Mill
TM-FTL-030	Kit, Fixed Tilt Leg, 30", Mill

Fixed Tilt Leg Kits are available in multiple lengths to support a wide range of mounting angles. The Fixed Tilt Leg Kit includes a North & South Tilt Leg, plus hardware for attaching to XR Rails®. South Tilt Legs come assembled and feature angle indicator markings to simplify installation. North Tilt Legs consists of a slotted aluminum tube and a pivot bracket for full adjustability.

Flat Roof Attachment



Item Number	Description
FRA-BASE-01-M1	Flat Roof Attachment, Mill
FRA-M60T-GF-W1	Flat Roof Attachment, Membrane, 60 mil, TPO, GAF, White
FRA-M60P-GF-W1	Flat Roof Attachment, Membrane, 60 mil, PVC, GAF, White
FRA-M60T-JM-W1	Flat Roof Attachment, Membrane, 60 mil, TPO, Johns Manville, White
FRA-M60T-MH-W1	Flat Roof Attachment, Membrane, 60 mil, TPO, Mule Hide, White
FRA-M60P-MH-W1	Flat Roof Attachment, Membrane, 60 mil, PVC, Mule Hide, White
FRA-M60T-FS-W1	Flat Roof Attachment, Membrane, 60 mil, TPO, Firestone, White
FRA-M60T-CA-W1	Flat Roof Attachment, Membrane, 60 mil, TPO, Carlisle, White
FRA-M60K-CA-W1	Flat Roof Attachment, Membrane, 60 mil, KEE, Carlisle, White
FRA-M60P-SN-W1	Flat Roof Attachment, Membrane, 60 mil, PVC, Sarnafil, White
FRA-M60T-VS-W1	Flat Roof Attachment, Membrane, 60 mil, TPO, Versico, White


The IronRidge® Flat Roof Attachment combines a high-strength cast aluminum base with a 16-point fastening pattern to enable the widest range of design options on low-sloped roofs. In addition, it is compatible with most of the common low-slope roofing materials to ensure a system that is both easy to integrate and engineered down to the deck.

BX Overview



The IronRidge® BX System is designed to meet the needs of commercial solar—navigating complex roof layouts, while also handling the most extreme environmental conditions. At the very core of the system is the Chassis, a ballasted mount made of lightweight glass-reinforced composite and molded specifically for the needs and challenges of solar installations.

[Download AutoCAD File](#)
[Download PDF Preview](#)



Location	Installer	DRAWING INFO.
Installer	Installer	Date & Time
Job Contact/Main Contact		Person/Approved by
Email	Email	Sheet Name
Phone	Phone	SSD


BX Chassis



Item Number	Description
BX-5D-P1	BX Chassis, 5 Degrees
BX-10D-P1	BX Chassis, 10 Degrees

At the core of the BX system is the Chassis, a ballasted mount made of BASF Ultramid. Ultramid polyamides (nylon) are exceptional for their high mechanical strength, rigidity and thermal stability. Moreover, Ultramid polyamides afford good impact resistance even at low temperatures, advantageous sliding friction properties and problem-free processing. Chassis come in 5° and 10° options.

BX Clamps




Item Number	Description	Item Number	Description (Black)
BX-TCL-30MM-M1	BX Top Clamp, 30MM, Mill	BX-BCL-M1	BX Bottom Clamp, Mill
BX-TCL-32MM-M1	BX Top Clamp, 32MM, Mill		
BX-TCL-35MM-M1	BX Top Clamp, 35MM, Mill		
BX-TCL-40MM-M1	BX Top Clamp, 40MM, Mill		

The Top and Bottom Clamps of the BX System combine to create a multi-directional grip on the module from above and below, ensuring a strong connection regardless of force direction.

BX Bonding Jumpers



8" Module Bonding Jumper




38" Row Bonding Jumper

Item Number	Description
BX-MB8-M1	8" Module Bonding Jumper
BX-RB38-M1	38" Row Bonding Jumper

8" Module Bonding Jumper bonds adjacent modules in the array, while the 38" Row Bonding Jumper completes row-to-row bonding in the array. BX Bonding Jumpers use a press-on installation, being made of tin-plate copper wire and providing a factory-crimped connection.


BX MLPE Mounting Hardware



Item Number	Description
BX-CMA-MI-M1	BX MLPE Mounting Assembly

Optional mounting hardware for mounting MLPE devices to BX Chassis. Kit includes stainless steel 300 series cap screw and cage nut.

BX PV Module Grounding Lug



Item Number	Description
PV-LUG-01-A1	PV Module Grounding Lug

At the core of the BX system is the Chassis, a ballasted mount made of BASF Ultramid. Ultramid polyamides (nylon) are exceptional for their high mechanical strength, rigidity and thermal stability. Moreover, Ultramid polyamides afford good impact resistance even at low temperatures, advantageous sliding friction properties and problem-free processing. Chassis come in 5° and 10° options.

BX Cable Ties



Cable Tie



Cable Tie & Edge Clip

Item Number	Description
BX-CT-UV-P1	BX Cable Tie, UV Rated, Black
BX-CT-EC-P1	BX Cable Tie and Edge Clip, UV Rated, Black

Complete wire management with weatherproof ties that are made of UV stabilized polyamide. Cable Ties come in 12" length, bundles of 100. Cable Tie with Edge Clips help to manage wires underneath module and Chassis flange by clipping to module and Chassis.

BX Flat Roof Mounting Assembly




Item Number	Description
BX-MA-FRA-M1	BX Flat Roof Mounting Assembly

The BX Flat Roof Mounting Assembly provides parts (to be combined with the IronRidge Flat Roof Attachment and locally-sourced strut and channel nuts) to add Flat Roof Attachment anchors to the BX System.

Ground Mount Overview



The IronRidge® Ground Mount System scales to support a wide range of site and terrain challenges. This system consists of components that allow for installer-supplied steel pipe or mechanical tubing to combine with the XR100® or XR1000® rail assembly for simple, rapid, cost effective ground mounting.



[Download AutoCAD File](#)
[Download PDF Preview](#)

Top Caps



Item Number	Description
70-0200-SGA	SGA Top Cap at 2", Mill
70-0300-SGA	SGA Top Cap at 3", Mill

Our heavy duty cast aluminum IronRidge Top Caps secure quickly and easily to galvanized schedule 40 pipe (ASTM A53 Grade B) or mechanical tubing (i.e. Allied Flo-Coat, Gatorshield, Gatorshield-Plus) piers with with 2 set screws. Available in sizes that fit either 2" or 3" steel pipe and mechanical tubing, the top cap supports cross pipes with U-bolt hardware. The top caps are manufactured using cast aluminum ALMAG 535 and come with a mill finish. As a reminder, the substructure pipe and mechanical tubing are not included.

2" Pipe/Tubing Outside Diameter = 2.375" (2 3/8")

3" Pipe/Tubing Outside Diameter = 3.5"

2" Schedule 40 Pipe Wall Thickness = 0.154"

2" Allied Mechanical Tubing Wall Thickness = 0.109"

3" Schedule 40 Pipe Wall Thickness = 0.216"

3" Allied Mechanical Tubing Wall Thickness = 0.165"

Bonded Rail Connectors



Item Number	Description
GM-BRC2-01-M1	Ground Mount Bonded Rail Connector - 2"
GM-BRC3-01-M1	Ground Mount Bonded Rail Connector - 3"

Our Bonded Rail Connectors attaches and bonds horizontal cross pipes to XR100® or XR1000® Rails. Each rail requires two connectors to create a secure and bonded attachment. Available for both 2" and 3" sizes, these Rail Connectors are manufactured using extruded 6000 series aluminum. Review the images on the section overview for added context.


Hex Head Set Screws



Item Number	Description
GM-HSHW-01-M1	Hex Head Set Screw for Ground Screws

To connect the IronRidge® Ground Mount System to your ground screw, you simply insert the downtube pipe into the top of the installed ground screw and tighten the required number of hex head set screws to the appropriate torque.

Diagonal Braces



Item Number	Description
GM-DB2-SLV01-M1	GM 2" Sleeve, Diagonal Brace
GM-DB2-TB02-M1	GM Diagonal Brace, 2" Square Tube, 106.5" LG (For 2" Pipe)
GM-DB2-TB01-M1	GM Diagonal Brace, 2" Square Tube, 88.5" LG (For 2" Pipe)
GM-DB3-SLV01-M1	3" Sleeve, Diagonal Brace
GM-DB3-TB02-M1	GM Diagonal Brace, 2.5" Square Tube, 105.0" LG (For 3" Pipe)
GM-DB3-TB01-M1	GM Diagonal Brace, 2.5" Square Tube, 87.0" LG (For 3" Pipe)
GM-DB-HW01-M1	GM Diagonal Brace Hardware (For 2" & 3" Pipe)

This optional diagonal brace is for installations that require extra support. Pieces include the brace, sleeves, and hardware for installation between one north and south pair of support legs.

Pipe & Mechanical Tubing Summary

To save installers money, we have engineered the use of locally sourced 2" or 3" schedule 40 steel pipe or mechanical tubing as the primary substructure element of our Ground Mount System. By allowing customers to source these materials locally, installers benefit from reduced shipping, product and inventory costs, and shortened delivery times. We provide intuitive online tools that will help you quickly and easily craft a bill of materials to simplify substructure costing and purchasing.

When additional assistance is needed to address ground mounting your array, please contact our customer service team at 800-227-9523, or at support@ironridge.com. Many IronRidge customers prefer to use our online Design Assistant, found at www.ironridge.com/design.

A soils report is widely considered the most reliable and accurate method for determining the type and depth of piers for any Ground Mount System. Soils reports can be obtained through a Geotechnical Engineer. A commonly relied upon alternative to obtaining a site-specific soils report is to use the IBC 2006 Table 1804.2. The advantage of purchasing a site specific soils report is that the information provided often results in shorter embedment depths, thus lowering both material and installation cost.

In many cases installers rely on our easy to use PE stamped certification and post/pier installation guides that our engineering staff has made available for download. You will find these and other IronRidge Ground Mount System documents located at ironridge.com/products/groundmounting/resources.

Schedule 40 Pipe

ASTM A53 Grade B standard weight (schedule 40) steel pipes or structural equivalent, with minimum geometry and material properties of:

- 3" pipe: OD 3.5", wall thickness 0.216", 35ksi yield strength
- 2" pipe: OD 2.38", wall thickness 0.154", 35ksi yield strength

Mechanical Tubing

Steel mechanical tubing or structural equivalent, with minimum geometry and material properties of:

- 3" Tubing: OD 3.5", wall thickness 0.165", 45ksi yield strength
- 2" Tubing: OD 2.375", wall thickness 0.109", 50ksi yield strength

*Always check local building codes for pier mounting requirements specific to your location.



QuickMount® RockIt® System

RockIt®

Item Number	Description
2011020	RI MOUNT AL BLK
2011021	RI COUPLING AL BLK
2011013	RI COMP SLIDE AL BLK
2011024	RI SMART SLIDE BLK 6.75"
2011025	RI SMART SCRW #12X3"W/BW
QM-MLPE-01-M1	Frame MLPE Mount (6 boxes of 50)
QM-RI-SKT-01-B1	RockIt Skirt, 82", Black
QM-RI-SKTCAP-01-B1	RockIt Skirt, End Cap
QM-MNTS-SIDWC-01-M1	Mantis Side Panel Wire Clip, Universal (5 bags of 100 clips)



Item Number	Description
2011037	RI US MOUNT AL BLK
2011038	RI US COUPLING AL BLK
2011039	RI US SMART SLIDE BLK 6.75" (Includes 2 #12x3" SMART SCRW W/BW)
QM-RI-SKT-01-B1-US	RockIt Skirt, 82", Black, US Production
QM-MLPE-01-M1-US	Frame MLPE Mount, US Production



The innovative RockIt® System conforms to UL 2703 (UL 2703A when used with RockIt Smart Slide) and UL 3741, and is the solar industry's premier rail-less PV racking system for use on a variety of roof types including composition shingle, standing seam metal pitched rooftops, and low slope roofs. Designed in conjunction with solar installers, the RockIt® System quickly and easily installs with the use of just a single tool, speeding up the overall installation time.

RockIt® features an easy-to-position mount alignment and a top-down leveling system that gives the installer the ability to level the PV array during or after the initial installation. Solar installers appreciate the north-south adjustability, as it allows for greater flexibility and versatility. It is also logistically efficient—no need to ship, transport, or store long rails. Components are available in a black finish that complement both commercial and residential rooftop solar arrays.

QuickMount® ClickFit® System

ClickFit®

Item Number	Description
QM-CF-LT-165M	ClickFit LTE Rail, 165.4", Mill
QM-CF-SD-171M	ClickFit STD Rail, 171.5", Mill
QM-CF-CAP-01-B1	ClickFit End Cap
QM-CF-SPL-01-M1	ClickFit Splice (Bonded Splice)
QM-CF-MID-01-B1	ClickFit Mid Clamp (30-40mm), Black
QM-CF-END-01-B1	ClickFit End Clamp (30-40mm), Black
QM-CF-MLPE-01-M1	ClickFit MLPE Mount
QM-CF-WC-01-M1	ClickFit Wire Clip (10 bags of 100)
QM-CF-WCLMP-01-B1	ClickFit N-S Wire Clamp, Black
QM-CF-LFT-01-M1	ClickFit L-Foot, Mill (Incl. Clicker)
QM-CF-CLKR-01-M1	ClickFit Rail Clicker, Mill



Item Number	Description
QM-CF-LT-165M-US	ClickFit LTE Rail, 165.4", Mill, US Production
QM-CF-SD-171M-US	ClickFit STD Rail, 171.5", Mill, US Production
QM-CF-SPL01-M1-US	ClickFit Splice (Bonded Splice), US Production
QM-CF-MID01-B1-US	ClickFit Mid Clamp (30-40mm), Black, US Production
QM-CF-END01-B1-US	ClickFit End Clamp (30-40mm), Black, US Production
QM-CF-MLPE01-M1-US	ClickFit MLPE Mount US Production



ClickFit® Rails connect to the ClickFit® Rail Clicker, which comes pre-attached to the ClickFit® L-Foot. The Rail Clicker is also compatible with the QuickMount® HUG® and All Tile Hook (sold separately). This allows rails to click into the roof attachments without the need for bolts or fasteners. Mid and End Clamps simply click on to the top of the rail, self-standing and easy to slide. Two rails sizes: Standard Rail (STD) in 171.4" lengths and Light Rail (LTE) in 165.4" lengths.

QuickMount® L-Feet

L-Feet

Item Number	Description
QM-TLF5-M1	L-Foot, Fixed Tilt, 5 Degree, Mill
QM-TLF10-M1	L-Foot, Fixed Tilt, 10 Degree, Mill
QMC-LF-A-12	L-Foot, Mill
QMC-LF-B-12	L-Foot, Black



Composition Shingle Mounts

HUG™ Halo UltraGrip™

Item Number	Description
QM-HUG-01-M1	Halo Ultra Grip, Mill
QM-HUG-01-B1	Halo Ultra Grip, Black
HW-RD1430-01-M1	RD Structural Screw



Item Number	Description
QM-HUG-01-M1-US	Halo Ultra Grip (Includes 2 RD Screws), Mill, US Production
QM-HUG-01-B1-US	Halo Ultra Grip (Includes 2 RD Screws), Black, US Production



L-Mount®

Item Number	Description
QM-LM-01-M1	L-Mount, 9" x 12", Mill



Comp Mounts

Item Number	Description
QMNC-A-12	QBase Comp Mount, 3.25" Post - 3.75" Net, 12" x 12", Mill
3012020	GF1 Flashing, Black, 8x10"
QM-GF1-LFT-01-B1	L-Foot, GF1, Black
HW-5164-01-M1	Sealing Washer Lag Screw, 5/16, 4.0L



Conduit Mounts

Item Number	Description
QM-BUG-01-M1	BUG, Conduit Mount, Mill (10 Pairs Per Box)
QMCC-A-12	Classic Conduit Composition Mount, 9" x 12", Mill
QMCPA-A-12	Conduit Penetration Flashing, Mill



Tile Roof Mounts

All Tile Hook

Item Number	Description
QM-ATH-02-M1	All Tile Hook (Incl. 2 Lags)
QM-THDF-01-M1	Tile Hook Deck Flashing, Mill



QBase Universal Tile Mount

Item Number	Description
QMUTM-A-12	QBase Universal Mount, 6.5" Post - 7" Net, 18" x 18", Mill



Tile Replacement

Item Number	Description
QMTR-BM-A-12	Tile Replacement, Base Mount, Mill
QMTR-S3.25-A-12	Tile Replacement, S-Tile, 3-1/4" Post, Mill
QMTR-S3.25-B-12	Tile Replacement, S-Tile, 3-1/4" Post, Black
QMTR-F3.25-A-12	Tile Replacement, Flat Tile, 3-1/4" Post, Mill
QMTR-F3.25-B-12	Tile Replacement, Flat Tile, 3-1/4" Post, Black
QMTR-W4-A-12	Tile Replacement, W-Tile, 4" Post, Mill
QMTR-W4-B-12	Tile Replacement, W-Tile, 4" Post, Black



Tile Hook Deck Flashing

Item Number	Description
QM-THDF-01-M1	Tile Hook Deck Flashing, Mill



Conduit Mounts

Item Number	Description
QM-TCM-01-M1	Tile Conduit Mount, Mill
QMCPA-A-12	Conduit Penetration Flashing, Tile, Mill



Other Mounts & Accessories


Metal, Shake & Slate

Item Number	Description
QM-LYNX-SS-M1	Lynx™ Standing Seam Metal Roof Clamp
QM-CORR-01-M1	Corruslide Metal Clamp (Incl Screws)
QMNS-A-12	QBase Metal, Shake & Slate, 3.25" Post - 3.75" Net, Mill



SimpleGrip®

Item Number	Description
QM-SG-BASE-01-M1	SimpleGrip Base Mount, Mill
QM-SG-ADH-T01-M1	SimpleGrip Base Mount Adhesive, Top
QM-SG-ADH-B01-M1	SimpleGrip Base Mount Adhesive, Bottom
HW-DS1520-01-M1	Deck Screw, #15, 2.0L
HW-DS1530-01-M1	Deck Screw, #15, 3.0L



QBase® Mount (Low Slope Roof Attachment, No Flashing)

Item Number	Description
QM-QBB-01-M1	QBase Base (incl. base to post h/w), Mill
QM-QBP-3.25-M1	QBase 3.25" Post (incl. post to rack h/w), Mill (3.75" Net)
QM-QBP-4.5-M1	QBase 4.5" Post (incl. post to rack h/w), Mill (5" Net)
QM-QBP-6.5-M1	QBase 6.5" Post (incl. post to rack h/w), Mill (7" Net)
QM-QBP-8.5-M1	QBase 8.5" Post (incl. post to rack h/w), Mill (9" Net)
QM-QBP-11.5-M1	QBase 11.5" Post (incl. post to rack h/w), Mill (12" Net)
QM-QBP-12.5-M1	QBase 12.5" Post (incl. post to rack h/w), Mill (13" Net)
QM-QBP-14.5-M1	QBase 14.5" Post (incl. post to rack h/w), Mill (15" Net)
QM-QBP-17.5-M1	QBase 17.5" Post (incl. post to rack h/w), Mill (18" Net)



Accessories

Item Number	Description
QM-MLPE-01-M1	Frame MLPE Mount
QM-MLPE-01-M1-US	Frame MLPE Mount, US Production
QMAFBU-A-25	Accessory Frame Bracket, Universal, Mill
QM-JBX-RF02-B1	JayBox™ Junction Box, Roof Mount (Comp Shingle)
QM-JBX-RL02-B1	JayBox™ Junction Box, Rail Mount*
QM-MNTS-SIDWC-01-M1	Mantis Side Panel Wire Clip, Universal (5 bags of 100 clips)
QM-MNTS-MIDWC-01-M1	Mantis Mid Panel Wire Clip, Universal (10 bags of 50 clips)

