


# Bridge Rope Specification Chart (Metric)



Part #	Nominal Diameter (mm)	Approx Weight (kg/m)	Approx Metallic Area (mm <sup>2</sup> )	Minimum Breaking Strength (kN)
WBR - 10	10	42	0,36	58
WBR - 11	11	59	0,48	78
WBR - 13	13	77	0,63	102
WBR - 14	14	95	0,79	129
WBR - 16	16	117	0,97	160
WBR - 17	17	143	1,18	191
WBR - 19	19	173	1,42	231
WBR - 21	21	201	1,64	267
WBR - 22	22	233	1,91	311
WBR - 24	24	267	2,19	356
WBR - 25	25	304	2,49	407
WBR - 29	29	385	3,15	514
WBR - 32	32	481	3,94	642
WBR - 35	35	585	4,79	781
WBR - 38	38	694	5,70	925
WBR - 41	41	819	6,72	1094
WBR - 44	44	948	7,81	1272
WBR - 48	48	1090	8,99	1459
WBR - 51	51	1239	10,21	1655
WBR - 54	54	1400	11,52	1868
WBR - 57	57	1561	12,91	2091
WBR - 60	60	1735	14,33	2322
WBR - 64	64	1916	15,80	2562
WBR - 67	67	2110	17,32	2820
WBR - 70	70	2310	18,99	3087
WBR - 73	73	2523	20,72	3372
WBR - 76	76	2742	22,53	3665
WBR - 83	83	3252	26,84	4226
WBR - 89	89	3761	31,31	4938
WBR - 95	95	4303	35,78	5694
WBR - 102	102	4897	40,25	6494

Other diameters available upon request



2400 W. 75th Street  
Prairie Village, KS 66208  
T (816) 270-4700  
info@wireco.com  
www.wireco.com