


# AD64 Door Reader with Keypad



## Document Details

### Version

**v1.0** (20240924)

(v1.0 published 20240924)

### Firmware

Firmware version can be verified on Verkada Command command.verkada.com.

### Product Models

This install guide pertains to model AD64-HW.

### Caution



Only use with Verkada Access Controllers certified under UL62368-1 (compliant with LPS) and UL294

© Copyright 2024 Verkada Inc. All rights reserved.

Verkada and the Verkada logo are registered trademarks or service marks of Verkada Inc. ("Verkada"). All other trademarks are the property of their respective owners.

Verkada may make changes to this document at any time without notice. The information presented herein may be inaccurate or outdated, and Verkada is under no obligation to maintain it. ALL INFORMATION IS PROVIDED "AS-IS" AND WITHOUT ANY WARRANTIES, IMPLIED, EXPRESS, OR OTHERWISE. VERKADA DISCLAIMS LIABILITY FOR ALL DAMAGES, INCLUDING WITHOUT LIMITATION ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES, ARISING OUT OF USE OF THIS DOCUMENT.

Any intellectual property rights relating to Verkada products are and shall remain Verkada's exclusive property. Use of any Verkada product is subject to Verkada's end user agreement or other executed agreement with Verkada. No license, either expressed or implied, to use or distribute any Verkada product is granted under this document.

This document may not be sold, resold, licensed or sublicensed and may not be transferred without Verkada's prior written consent. No part of this document may be reproduced in whole or in part without the express written consent of Verkada.


## Introduction

### AD64 Technical Specifications


Dimensions	81 x 131.5 x 22.5mm (including mount plate)
Weight	215g
Supported Credential Technologies	Keypad for PIN and 2FA Low Frequency (125 kHz) High Frequency (13.56 MHz) Mobile NFC (13.56MHz) Bluetooth Low Energy (2.4GHz)
Ratings	IP65, IK08
Operating Temperature	-40° to 65°C (-40° to 149°F) 5-90% RH non-condensing
Controller Compatibility	Requires an RS-485 connection to a Verkada access controller
Power Consumption	12V, 250mA max
Included Accessories	Mount Plate, T10 screwdriver, 2 wall mount screws, 2 M3 machine screws
Mounting Options	Unit ships with standard single gang mounting plate

## Introduction

### What's in the box



Door Reader with Keypad



Mount Plate



T10 Security Torx Screwdriver



Wall Mount Screws (2pcs)



M3 Machine Screws (2pcs)

### What you'll need

- A working internet connection
- A smartphone or laptop
- A #2 Phillips driver (screwdriver or power drill)
- 1/8 inch (3mm) drill bit for pilot holes
- 1/2 inch (12.7mm) drill bit, or larger, for routing cable through wall

### Placement

Mount product on wall with RS485 cable routed and plugged into Verkada Access Controller.


### Connect

For easy registration and setup, scan the QR code on the product.

If you prefer to manually register your product, please proceed to:  
[verkada.com/start](http://verkada.com/start)

## Introduction

# Overview



## Keypad Functions

### Pin Input

Input the pin, using the numerical keypad. The '#' key is used to submit after a pin input.

### Timeout & Reset

If the keypad is left mid-input, the keypad will flash and beep twice when it resets.

To manually reset, press the '\*' key.

## LED Behaviors

### Keypad LEDs



#### Cascading

Booting up.



#### Static

Powered and connected to the ACU

#### Flash 2x

Pin reset from inactivity or correction.

#### Pulsing

For instances of *Two Factor* and *Quorum*. This signifies that the reader is ready to scan the second credential (badge or pin input).

### Feedback LED



#### Green, Temporarily

Successfully processed a user scan and granted access.

#### Green, Static

Unlock hold placed on door.

#### Green, Pulsing

Keypad LEDs dimly lit  
Emergency Release.



#### Red, Temporarily

Successfully processed a user scan and denied access.

#### Red, Static

Lock hold placed on door.

#### Red, Pulsing

Keypad LEDs dimly lit  
Emergency lockdown.

## Required Wires


The following diagram shows the recommended wire types:

Signal	AWG	Twisted Pair	Shielded	Max Length
Reader Option 1 (22 AWG)	22	Yes	Yes	250 ft
Reader Option 2 (20 AWG)	20	Yes	Yes	300 ft
Reader Option 3 (18 AWG)	18	Yes	Yes	500 ft


**Recommended use:** one twisted pair for GND and VIN (power) & one twisted pair for the data (D0/D1 or A/B). Wiring methods shall be in accordance with National Electrical Code, ANSI/NFPA 70.

## Excess Wire Trimming

Avoid pinching cables during install as that may affect performance. If excess cables, trim to reduce slack.




Avoid pinching the cable



Trim cable of excess

## Shield Wiring and Grounding



## Installation Best Practices


### Critical Wiring Requirements

You must use shielded wiring with the AD64:


- Connect the drain wire (bare metal) from the reader cable bundle to the drain wire in the shielded cabling. Then, connect the drain wire at the other end of the shielded cabling to Earth ground.
- Improper grounding and shielding may result in unintended product behavior.

It is recommended to connect one of the chassis grounding screws to the building ground at the installation site.


The drain wires from the shielded cabling can be connected to Earth ground on the following locations on the Verkada Access Controllers. See reference below.



AC12



AC62




AC42


## Installation

### Preparation

Pull keypad reader and pulp tray out of packaging. Mounting hardware can be found under IN card.




Use pull tab to remove mount from keypad reader in preparation for mounting.




## Installation

### Mounting (1/4)

Using the mount plate as your template, mark and drill two  $\frac{1}{8}$  inch (3mm) pilot holes at the top and bottom. Drill a  $\frac{1}{2}$  inch (12.7mm) center hole for cable routing.



Secure the mount plate to a single gang junction box using the 2 provided M3 machine screws. If you are installing on a wall, use the 2 provided wall mount screws instead.



## Installation

### Mounting (2/4)

Route the installed cable through center opening on mount plate.

Connect the wires using the diagram below or the table on the back of the AD64 Keypad Door Reader as reference.




### Wiring (RS-485 & Drain Wire)




AD64 Cable

Installed Cable

To ensure that the reader is receiving power, make sure that the number LEDs are cycling. The reader successfully connected to the ACU when all numbers are illuminated and static.



Booting Up




Connected


## Installation

### Mounting (3/4)

Tow in the AD64 keypad reader into mount plate, and rotate device down.




Once in position, press the AD64 keypad reader into the mount until an audible snap is heard.



## Installation

### Mounting (4/4)

Secure the security screw on the bottom of the reader using the provided T10 Security Torx hand tool. The screw is positioned at an angle for ease of install against a mullion frame or wall.



## Appendix

# AD64 Compliance

<b>FCC Statement</b>	<p>This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules.</p> <p>These limits are designed to provide reasonable protection against harmful interference in a residential installation.</p> <p>This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.</p> <p>However, there is no guarantee that interference will not occur in a particular installation.</p> <p>If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:</p> <ul style="list-style-type: none"><li>• Reorient or relocate the receiving antenna.</li><li>• Increase the separation between the equipment and receiver.</li><li>• Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.</li><li>• Consult the dealer or an experienced radio/TV technician for help.</li></ul> <p><b>FCC Caution:</b> Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.</p> <p>This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.</p> <p><b>Radiation Exposure Statement:</b> The product comply with the FCC portable RF exposure limit set forth for an uncontrolled environment and are safe for intended operation as described in this manual.</p> <p>The further RF exposure reduction can be achieved if the product can be kept as far as possible from the user body or set the device to lower output power if such function is available.</p>
<b>IC Statement</b>	<p>This device complies with ISED's licence-exempt RSSs. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>Le présent appareil est conforme aux CNR d' ISED applicables aux appareils radio exempts de licence.</p> <p>L'exploitation est autorisée aux deux conditions suivantes : (1) le dispositif ne doit pas produire de brouillage préjudiciable, et (2) ce dispositif doit accepter tout brouillage reçu, y compris un brouillage susceptible de provoquer un fonctionnement indésirable.</p> <p><b>Radiation Exposure Statement:</b> The product comply with the Canada portable RF exposure limit set forth for an uncontrolled environment and are safe for intended operation as described in this manual.</p> <p>The further RF exposure reduction can be achieved if the product can be kept as far as possible from the user body or set the device to lower output power if such function is available.</p> <p><b>Déclaration d'exposition aux radiations:</b> Le produit est conforme aux limites d'exposition pour les appareils portables RF pour les Etats-Unis et le Canada établies pour un environnement non contrôlé.</p> <p>Le produit est sûr pour un fonctionnement tel que décrit dans ce manuel.</p> <p>La réduction aux expositions RF peut être augmentée si l'appareil peut être conservé aussi loin que possible du corps de l'utilisateur ou que le dispositif est réglé sur la puissance de sortie la plus faible si une telle fonction est disponible.</p>

## Appendix

### AD64 Compliance

#### Caution

Only use with Verkada Access Controllers certified under UL62368-1 (compliant with LPS) and UL294

À utiliser uniquement avec les contrôleurs d'accès Verkada certifiés sous UL 62368-1 (conforme à LPS) et UL294.

<b>UL 294</b>	Attack Level/Grade: Level 1 Endurance Level/Grade: Level 1 Line Security Level/Grade: Level 1 Standby Power Level/Grade: Level 1
<b>CAN-ULC 60839-11-1</b>	Environmental Level: Outdoor Grade Assignment: Grade I

## Appendix

### **Support**

Thank you for purchasing this Verkada product. If for any reason you're experiencing issues or need assistance, please contact our 24/7 Technical Support Team immediately.

Sincerely,  
The Verkada Team  
[verkada.com/support](http://verkada.com/support)