

## CB62-TE Telephoto Bullet Camera

### Prominent 4K Coverage at Distance in Outdoor Environments



#### Overview

The CB62-TE telephoto bullet camera features a 1 / 2.8" progressive CMOS image sensor, an advanced optical lens with an adjustable focal length of 8mm - 20mm, and powerful long-range IR LEDs (50 meters / 164 feet) for 4K coverage in a variety of lighting and weather conditions. The CB62-TE features an onboard CV22S Ambarella processor for advanced analytics like AI-powered search, [occupancy trends](#), line crossing, loitering, and person of interest (POI) alerts. The CB62-TE also supports [license plate recognition](#) (LPR), enabling it to capture license plates from vehicles traveling up to 80 mph / 128 kph across as many as three lanes of traffic. The CB62-TE excels at covering high-traffic areas of interest such as stadiums and busy parking lot entrances and, because of its telephoto zoom capabilities, provides clear images even when installed far from an area of interest. The CB62-TE is also optimal for reading license plates at distance, and its LPR capabilities can be used to access control gated entrances to facilities.

The CB62-TE is constructed with a robust aluminum unibody and designed to withstand extreme conditions with an IP67 weather rating and IK10 impact rating. The camera's design includes a built-in pigtail connector that expedites PoE cabling by removing the need to disassemble the camera itself. Installation and setup are easy to track using the LED status indicator.

#### Key features

##### Superior image quality

- 1 / 2.8" progressive CMOS image sensor
- 4K resolution
- Varifocal lens with an adjustable focal length of 8mm - 20mm
- 50 meters / 164 feet of IR range for optimal nighttime viewing

##### Advanced analytics

- Onboard CV22S Ambarella processor enables people and vehicle analytics
- License plate recognition capabilities capture license plates at speeds up to 80 mph / 128 kph
- AI-powered search and AI-powered alerts
- Occupancy trends for operational insights

##### Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 90 days (512GB - 2TB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

##### Easy installation

- Built-in pigtail connector for simplified PoE cabling
- Mounting plate and screw pack included
- LED light status indicator

##### Durability and weather protection

- Factory-sealed robust aluminum unibody
- IP67 weather rating
- IK10 impact rating
- Operability between -40°C to 50°C / -40°F to 122°F



# CB62-TE

## Tech Specs

### Camera features

<b>Image Sensor</b>	1/2.8" Progressive CMOS	<b>Shutter Speed</b>	1 / 30 sec. to 1 / 10,000 sec.
<b>Sensor Resolution<sup>1</sup></b>	4K (3840 x 2160)	<b>Day/Night</b>	IR-cut filter for day and night function
<b>Lens Type</b>	Varifocal; motorized zoom	<b>IR Cut Filter</b>	Yes
<b>Focal Length</b>	8mm-20mm	<b>IR Range</b>	50m / 164ft
<b>Aperture</b>	F1.5-F2.8	<b>Minimum Illumination</b>	0.009 lux @ F1.9 (Color) 0 lux with IR Illuminators on
<b>Iris</b>	P-Iris	<b>Onboard Storage</b>	Capacity: From 512GB to 2TB Card: MicroSD, SDXC
<b>Field of View (after LDC<sup>2</sup>)</b>	Horizontal: 42° - 17° (41° - 17°) Vertical: 23° - 9° (23° - 9°) Diagonal: 48° - 19° (46° - 19°)	<b>CPU</b>	Ambarella CV22S66
<b>Camera Movement</b>	Tilt: 0° to 90° Pan: 360° Rotation: 360°		

### Standard video settings

<b>Compression</b>	H.265, H.264	<b>Historical Video Settings</b>	Adaptive quality <sup>1</sup>
<b>Frame Rate<sup>3</sup></b>	24fps	<b>Live Streaming Settings</b>	High quality (HQ): Up to 4,500 Kbps (default) Standard quality (SQ): Up to 600 Kbps

### Standard audio settings

<b>Audio</b>	Not supported
--------------	---------------

### Power and network

<b>Power Input<sup>4</sup></b>	With IR: IEEE 802.3at Type 2 PoE+ Without IR: IEEE 802.3af Type 1 PoE Extended temperature range: IEEE 802.3at Type 2 PoE+	<b>Connectivity</b>	RJ-45 cable connector for network/PoE connection; 10 / 100 Mbps
<b>Power Consumption<sup>4</sup></b>	With IR: 37-57V, 0.40-0.26A, 14.9W Without IR: 37-57V, 0.11-0.08A, 4.3W Extended temperature range: 37-57V, 0.64-0.39A, 23.7W	<b>RTSP</b>	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio support: No

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below -10°C / 14°F and assumes IR will be enabled.



## CB62-TE

# Tech Specs

### General

<b>Operating Temperature</b>	-40°C to 50°C / -40°F to 122°F	<b>LED Indicator</b>	System power and status indicator
<b>Humidity</b>	0 to 90%	<b>Warranty</b>	10 Years
<b>Certifications</b>	FCC, ICES, CE, UKCA, RCM, VCCI, KCC, BIS, NOM, CB, UL/cUL/IEC 62368-1, IP67 weather rating, IK10 impact rating, FY2019 NDAA compliant	<b>Included Accessories</b>	4x M4x8 screws, 4x TP4x30 mount screws, mount plate, junction box adapter, junction box cover, T25 hand tool

### Mechanical

<b>Weight</b>	Camera: 1478g / 52.13oz Mount plate: 33g / 1.16oz	<b>Body</b>	Aluminum
<b>Dimensions</b>	L: 254.0mm / 10.00in, Ø: 85.0mm / 3.35in		

### Dimensions



### Software capabilities

<b>Alerts</b>	Camera status, motion detection, people detection, vehicle detection, person of interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts	<b>Streaming and Storage</b>	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
<b>People Analytics</b>	People search, attribute search, face search, occupancy trends, motion search, trajectory analysis, selective face blurring, AI-powered search	<b>Sharing and Privacy</b>	Live links, live face blur, privacy regions, audit log
<b>Vehicle Analytics</b>	Vehicle search, attribute search, motion search, trajectory analysis, occupancy trends, AI-powered search	<b>License Plate Recognition</b>	License plate of interest alerts, license plate indexing



## Ordering Information

### CB62-TE pricing

Model Number	MP <sup>1</sup>	WDR	Lens	IR Range	Onboard Storage	Maximum SQ Onboard Retention <sup>1</sup>	People/Vehicle Analytics	Cost (MSRP) <small>USD</small>
CB62-512TE-HW	4K	✓	Zoom	50m / 164ft	512GB	30 Days	✓	\$2,199
CB62-1TBTE-HW	4K	✓	Zoom	50m / 164ft	1TB	60 Days	✓	\$2,999
CB62-2TBTE-HW	4K	✓	Zoom	50m / 164ft	2TB	90 Days	✓	\$4,299

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>



## Ordering Information

### Video Security Cloud License pricing (New/Capacity Increase)

Model Number	Description	Cost (MSRP) USD
LIC-CAM-1Y-CAP	1-Year Camera License, Capacity Increase	\$219
LIC-CAM-3Y-CAP	3-Year Camera License, Capacity Increase	\$599
LIC-CAM-5Y-CAP	5-Year Camera License, Capacity Increase	\$999
LIC-CAM-10Y-CAP	10-Year Camera License, Capacity Increase	\$1,999

### Video Security Cloud License pricing (Renewal)

Model Number	Description	Cost (MSRP) USD
LIC-CAM-1Y-RNW	1-Year Camera License, Renewal	\$219
LIC-CAM-3Y-RNW	3-Year Camera License, Renewal	\$599
LIC-CAM-5Y-RNW	5-Year Camera License, Renewal	\$999
LIC-CAM-10Y-RNW	10-Year Camera License, Renewal	\$1,999



## Ordering Information

### Accessories pricing

Model Number	Description	Cost (MSRP) USD
ACC-MNT-POLE-1	Pole Mount	\$209
ACC-MNT-CORNER-1	Corner Mount	\$199
ACC-MNT-SJBOX-1	Square Junction Box	\$89
INJ-POE-PLUS	PoE Plus (802.3at Type 2) Injector, GigE	\$129



## Ordering Information

### Viewing Station pricing

Model Number	Description	Cost (MSRP) USD
VX52-HW	VX52 Viewing Station	\$499

### Viewing Station License pricing (New/Capacity Increase)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-CAP	1-Year Viewing Station License, Capacity Increase	\$499
LIC-VX-3Y-CAP	3-Year Viewing Station License, Capacity Increase	\$1,299
LIC-VX-5Y-CAP	5-Year Viewing Station License, Capacity Increase	\$1,999
LIC-VX-10Y-CAP	10-Year Viewing Station License, Capacity Increase	\$3,999

### Viewing Station License pricing (Renewal)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-RNW	1-Year Viewing Station License, Renewal	\$499
LIC-VX-3Y-RNW	3-Year Viewing Station License, Renewal	\$1,299
LIC-VX-5Y-RNW	5-Year Viewing Station License, Renewal	\$1,999
LIC-VX-10Y-RNW	10-Year Viewing Station License, Renewal	\$3,999