

BH61

Wireless Alarm Hub

CLASSIC ALARMS**VLINK**

A PoE-powered hub that enables two-way communication with Verkada's wireless sensors.

Complete coverage

- Support for up to 60 wireless sensors at a range of up to 300 ft / 90 m (line-of-sight)
- Wall or ceiling mounted

Easy management

- Cloud-managed from Command for easy device configuration and monitoring

Stays connected

- Built-in backup battery to keep system online for at least 12 hours in the event of a power loss
- Compatible with the ACC-CEL-LTE accessory for plug-and-play backup cellular connectivity

Built to last

- Covered by our industry-leading 10-year warranty
- Automatic firmware updates keep systems secure



BH61 Wireless Alarm Hub Tech Specs

**BH61**

Power and network

Power Consumption	14W	Connectivity	10/100Mbps RJ-45 cable connector for network/PoE connection USB 2.0 for ACC-CEL-LTE Cellular Backup Module (not included)
Backup Battery (Internal)	7.3V/2850mAh 12 hours of backup with typical use	Wireless Communication	Proprietary 915 MHz (US, Canada) / 868 MHz (UK, Europe) / 916.8 MHz (ANZ)

General

Dimensions	Height: 155mm / 6.1in Width: 155mm / 6.1in Depth: 67mm / 2.6in	Operating Temperature	0°C to 45°C / 32°F to 113°F; 0-90% humidity
Weight	0.87kg / 1.91lbs	Warranty	10 years
		Certifications	FCC, IC, UKCA, RCM, NOM, NDAA, EN 50131 (Grade 2)

Installation

Included Accessories	QSG, 3x machine screws, 3x wing nuts, 3x washers, 4x wall screws, 4x wall anchors, torx wrench	Mounting Options	Drywall anchors (M8) and screws (M5)
-----------------------------	--	-------------------------	--------------------------------------



Ordering Information

BH61 Wireless Alarm Hub pricing

Model Number	Description	Cost (MSRP) USD
BH61-HW	BH61 Wireless Alarm Hub	\$599

BR31-BR35 Wireless Sensor pricing

BR31-HW	Wireless Door Sensor	\$99
BR32-HW	Wireless Motion Sensor	\$99
BR33-HW	Mounted Panic Button	\$99
BR34-HW	Wireless Glass Break Sensor	\$99
BR35-HW	Wireless Water Leak Sensor	\$99