

Combining Deep Reinforcement Learning and Search with Generative Models for Game-Theoretic Opponent Modeling

Zun Li¹, Marc Lanctot¹, Kevin R. McKee¹, Luke Marris¹, Ian Gemp¹, Daniel Hennes¹, Paul Muller¹, Kate Larson^{1,2}, Yoram Bachrach¹, Michael P. Wellman³

¹Google DeepMind

²University of Waterloo

³University of Michigan
{lizun,lanctot}@google.com

Abstract

Opponent modeling methods typically involve two crucial steps: building a belief distribution over opponents’ strategies, and exploiting this opponent model by playing a best response. However, existing approaches typically require domain-specific heuristics to come up with such a model, and algorithms for approximating best responses are hard to scale in large, imperfect information domains.

In this work, we introduce a scalable and generic multiagent training regime for opponent modeling using deep game-theoretic reinforcement learning. We first propose Generative Best Response (GenBR), a best response algorithm based on Monte-Carlo Tree Search (MCTS) with a learned deep generative model that samples world states during planning. This new method scales to large imperfect information domains and can be plug and play in a variety of multiagent algorithms. We use this new method under the framework of Policy Space Response Oracles (PSRO), to automate the generation of an *offline opponent model* via iterative game-theoretic reasoning and population-based training. We propose using solution concepts based on bargaining theory to build up an opponent mixture, which we find identifying profiles that are near the Pareto frontier. Then GenBR keeps updating an *online opponent model* and reacts against it during gameplay. We conduct behavioral studies where human participants negotiate with our agents in Deal-or-No-Deal, a class of bilateral bargaining games. Search with generative modeling finds stronger policies during both training time and test time, enables online Bayesian co-player prediction, and can produce agents that achieve comparable social welfare and Nash bargaining score negotiating with humans as humans trading among themselves.

1 Introduction

A central challenge for agent designers is how to build agents that can be well-adapted to unknown opponents in a dynamic multiagent environment. Opponent modeling methods [Al-

brecht and Stone, 2018] typically build a profile or a prior belief of opponent strategies and produce agents that are best response against such opponent models. These techniques have achieved success in fields like Poker [Johanson and Bowling, 2009; Bard *et al.*, 2013], automated negotiation [Baarslag *et al.*, 2016] and robotic soccer [Kitano *et al.*, 1998].

However, most of these approaches use domain-specific heuristics to handcraft an opponent model. Such knowledge is typically encoded in certain interpretations of game rules or experiences reflected by human plays. These techniques are hard to transfer to domains where relevant data are missing. Meanwhile, even if an opponent model is present, there is no existing best response method that work well in large imperfect information games where computing a posterior distribution over world state is intractable.

In this work, we propose a general-purpose training regime using multiagent reinforcement learning to address the above issues. We adopt extensive-form games (EFG) as a generic formulation for multiagent environments for our algorithmic developments, as opposed to a domain-specific ruleset. We propose Generative Best Response (GenBR), a best response method that extends AlphaZero-style RL and MCTS methods to large general-sum, imperfect information games. GenBR enhances best response strength by leveraging test-time computation and an approximate world model learned by deep neural nets. While GenBR can be plug and play in a variety of multiagent training algorithms, we focus on *Policy Space Response Oracles* (PSRO) [Lanctot *et al.*, 2017] as our training loop for *offline opponent modeling*. Our agent thereafter at test-time employs GenBR for both planning and updating an *online opponent model* via Bayesian learning.

Contributions. We provide three significant contributions. First, we propose enhanced version of AlphaZero-style MCTS to train a best response strategy, thereby equipping our agent with the capability to both plan and infer the environmental state as well as opponents’ strategic choices during online decision-making. This novel search method integrates deep RL with *Information Set MCTS* (IS-MCTS). To handle large imperfect information, we augment the policy-and-value network (PVN) in AlphaZero with a generative model that samples world states at the root of the search tree. This results in a novel policy-value-and-generative network (PVGn), which iteratively refines its quality using RL trajec-




Figure 1: Example negotiation game in extensive-form. In “Deal or No Deal”, the game starts at the empty history (\emptyset), chance samples a public pool of resources and private preferences (with some conditions; see Section 5.1) for three different items (books, hats, and basketballs). Then, players alternate proposals for how to split the resources. Rewards are defined by a dot product between received resources and preferences.

tory data during the training loop.

Second, we introduce several novel meta-strategy solvers in the PSRO framework based on the Nash bargaining solution [Nash, 1950]. Lastly, we show an empirical evaluation of several RL agents trained by the combined algorithm against humans in a negotiation game, finding the best ones to be as efficient as humans trading with other humans.

2 Preliminaries

An N -player **normal-form game** consists of a set of players $\mathcal{N} = \{1, 2, \dots, N\}$, N finite pure strategy sets Π_i (one per player) with a joint strategy set $\Pi = \Pi_1 \times \Pi_2 \times \dots \times \Pi_N$, and a utility tensor (one per player), $u_i : \Pi \rightarrow \mathbb{R}$, and we denote player i ’s utility as $u_i(\pi)$. Two-player (2P) normal-form games are called **matrix games**. A **two-player zero-sum** (purely adversarial) game is such that, $N = 2$ and for all joint strategies $\pi \in \Pi : \sum_{i \in \mathcal{N}} u_i(\pi) = 0$, whereas a **common-payoff** (purely cooperative) game: $\forall \pi \in \Pi, \forall i, j \in \mathcal{N} : u_i(\pi) = u_j(\pi)$. A **general-sum** game is one without any restrictions on the utilities. A **mixed strategy** for player i is a probability distribution over Π_i denoted $\sigma_i \in \Delta(\Pi_i)$, and a strategy profile $\sigma = \sigma_1 \times \dots \times \sigma_N$, and for convenience we denote $u_i(\sigma) = \mathbb{E}_{\pi \sim \sigma} [u_i(\pi)]$. By convention, $-i$ refers to player i ’s opponents. A **best response** is a strategy $b_i(\sigma_{-i}) \in \text{BR}(\sigma_{-i}) \subseteq \Delta(\Pi_i)$, that maximizes the utility against a specific opponent strategy: for example, $\sigma_1 = b_1(\sigma_{-1})$ is a best response to σ_{-1} if $u_1(\sigma_1, \sigma_{-1}) = \max_{\sigma'_1} u_1(\sigma'_1, \sigma_{-1})$. An approximate ϵ -**Nash equilibrium** is a profile σ such that for all $i \in \mathcal{N}$, $u_i(b_i(\sigma_{-i}), \sigma_{-i}) - u_i(\sigma) \leq \epsilon$, with $\epsilon = 0$ corresponding to an exact Nash equilibrium.

In an **extensive-form game**, play takes place over a sequence of actions $a \in \mathcal{A}$. Examples of such games include chess, Go, and poker. A **history** $h \in \mathcal{H}$ is a sequence of actions from the start of the game taken by all players. Legal actions are at h are denoted $\mathcal{A}(h)$ and the player to act at h as $\tau(h)$. Players only partially observe the state and hence have imperfect information. There is a special player called **chance** that plays with a fixed stochastic policy (selecting out-

comes that represent dice rolls or private preferences). Policies π_i (also called behavioral strategies) is a collection of distributions over legal actions, one for each player’s **information state**, $s \in \mathcal{S}_i$, which is a set of histories consistent with what the player knows at decision point s (e.g. all the possible private preferences of other players), and $\pi_i(s) \in \Delta(\mathcal{A}(s))$. An illustrative example of interaction in an extensive-form game is “Deal or No Deal” shown in Figure 1.

There is a subset of the histories $\mathcal{Z} \subset \mathcal{H}$ called **terminal histories**, and utilities are defined over terminal histories, e.g. $u_i(z)$ for $z \in \mathcal{Z}$ could be -1 or 1 in Go (representing a loss and a win for player i , respectively). As before, expected utilities of a joint profile $\pi = \pi_1 \times \dots \times \pi_N$ is defined as an expectation over the terminal histories, $u_i(\pi) = \mathbb{E}_{z \sim \pi} [u_i(z)]$, and best response and Nash equilibria are defined with respect to a player’s full policy space.

2.1 Combining MCTS and RL for Best Response

Computing approximate best responses is critical in a variety of multiagent training algorithms. There have been many previous works that consider enhancing best response strength via deep RL and game-tree search. For example, the original PSRO algorithm [Lanctot *et al.*, 2017] proposed using deep RL in place of value iteration in the double-oracle framework [McMahan *et al.*, 2003] which scales game solving in environments with large state spaces. Approximate Best Response (ABR) [Timbers *et al.*, 2022; Wang *et al.*, 2023] uses MCTS as a best response method which identifies weakness in human-level Go playing agents. However, they only focus on domain where a posterior world belief can be computed exactly. Another relevant work is Best Response Expert Iteration (BRExIT) [Hernandez *et al.*, 2023], which uses MCTS to exploit an opponent mixture trained with an auxiliary loss. However, they only concern perfect information games.

In general, using deep RL+MCTS as a best response method leverages both generalization capability of neural nets and test-time computation by the search method. We elaborate this by explaining how ABR algorithm works. When computing an approximate best response in imperfect information games, ABR uses a variant of Information Set Monte Carlo tree search [Cowling *et al.*, 2012] called IS-MCTS-BR. At the root of the IS-MCTS-BR search (starting at information set s), the posterior distribution over world states, $\Pr(h \mid s, \pi_{-i})$ is computed explicitly, which requires both (i) enumerating every history in s , and (ii) computing the opponents’ reach probabilities for each history in s . Then, during each search round, a world state is sampled from this belief distribution, then the game-tree regions are explored in a similar way as in the vanilla MCTS, and finally the statistics are aggregated on the information-set level. Steps (i) and (ii) are prohibitively expensive in games with large belief spaces.

Algorithm 1 GenBR Training Loop

```

function GenBR( $i, \sigma, num\_eps$ )
  Initialize value nets  $v, v'$ , policy nets  $p, p'$ , generative nets  $g, g'$ , data buffers  $D_v, D_p, D_g$ 
  for  $eps = 1, \dots, num\_eps$  do
     $h \leftarrow$  initial state.  $\mathcal{T} = \{s_i(h)\}$ 
    Sample opponents  $\pi_{-i} \sim \sigma_{-i}$ .
    while  $h$  not terminal do
      if  $\tau(h) = \text{chance}$  then
        Sample chance event  $a \sim \pi_c$ 
      else if  $\tau(h) \neq i$  then
        Sample  $a \sim \pi_{\tau(h)}$ 
      else
         $a, \pi \leftarrow \text{Search}(s_i(h), \sigma, v', p', g')$ 
         $D_p \leftarrow D_p \cup \{(s_i(h), \pi)\}$ 
         $D_g \leftarrow D_g \cup \{(s_i(h), h)\}$ 
      end if
       $h \leftarrow h.apply(a), \mathcal{T} \leftarrow \mathcal{T} \cup \{s_i(h)\}$ 
    end while
     $D_v \leftarrow D_v \cup \{(s, r) \mid s \in \mathcal{T}\}$ , where  $r$  is the payoff of  $i$  in this trajectory
     $v, p, g \leftarrow \text{Update}(v, p, g, D_v, D_p, D_g)$ 
    Replace parameters of  $v', p', g'$  by the latest parameters of  $v, p, g$  periodically.
  end for
  return  $\text{Search}(\cdot, \sigma, v, p, g)$ 
end function

```

Algorithm 2 GenBR Search

```

function Search( $s, \sigma, v, p, g$ )
  for  $iter = 1, \dots, num\_sim$  do
     $\mathcal{T} = \{\}$ 
    Sample a world state (gen. model):  $h \sim g(h \mid s)$ 
    Sample an opponent profile using Bayes' rule:  $\pi'_{-i} \sim \Pr(\pi_{-i} \mid h, \sigma_{-i})$ . Replace opponent nodes with chance events according to  $\pi'_{-i}$ 
    while do
      if  $h$  is terminal then
         $r \leftarrow$  payoff of  $i$ . Break
      else if  $\tau(h) = \text{chance}$  then
         $a \leftarrow$  sample according to chance
      else if  $s_i(h)$  not in search tree then
        Add  $s_i(h)$  to search tree.
         $r \leftarrow v(s_i(h))$ 
      else
         $a \leftarrow \text{MaxPUCT}(s_i(h), p)$ 
         $\mathcal{T} \leftarrow \mathcal{T} \cup \{(s_i(h), a)\}$ 
      end if
       $h.apply(a)$ 
    end while
    for  $(s, a) \in \mathcal{T}$  do
       $s.child(a).visits \leftarrow s.child(a).visits + 1$ 
       $s.child(a).value \leftarrow s.child(a).value + r$ 
       $s.total\_visits \leftarrow s.total\_visits + 1$ 
    end for
  end for
  return action  $a^*$  that receives max visits among children of  $s$ , and a policy  $\pi^*$  that represents the visit frequency of children of  $s$ 
end function

```

3 GenBR: Learning Best Response Search with a Generative Model

We propose Generative Best Response (GenBR), a new best response method based on AlphaZero-styled MCTS with $\Pr(h \mid s, \pi_{-i})$ learned by a deep generative model. On a high-level, GenBR is parameterized by three deep neural nets: a policy net p , a value net v and a generative net g . Just as in the AlphaZero training loop [Silver *et al.*, 2018], GenBR training loop generates multiple RL trajectories by calling GenBR search procedure at each decision point to gather data for training these neural nets. These neural nets will further guide and refine the search procedure, producing higher quality data for later training. During the search procedure, the world states are sampled directly from the model given only their information state descriptions, leading to a succinct representation of the posterior that generalizes to large state spaces. Next we explain our algorithms in more details.

The GenBR training loop (Algorithm 1) proceeds analogously to AlphaZero’s self-play based training, which trains a value net v , a policy net p , along with a generative network g using trajectories generated by search. We assume we are given an *offline opponent model* σ represented by a mixed strategy profile of the opponents. There are important differences from AlphaZero. Only one player is learning (e.g. player i). The (set of) opponents are fixed, sampled at the start of each episode from the opponent model σ_{-i} . Whenever it is player i ’s turn to play, since we are considering imperfect information games, it runs a POMDP search procedure based on Algorithm 2 from its current information state s_i . The search procedure produces a policy target π^* , and an action choice a^* that will be taken at s_i at that episode. Data about the final outcome and policy targets for player i are stored in data sets D_v and D_p , which are used to improve the value net and policy net that guide the search. Data about the history, h , in each information set, $s(h)$, reached is stored in a data set D_g , which is used to train the generative network g by supervised learning. We call the combination of v, p , and g as the policy-value-and-generative network (PVGN).

The GenBR MCTS search used (Algorithm 2) is based on IS-MCTS-BR in [Timbers *et al.*, 2022] (described in Section 2.1) and POMCP [Silver and Veness, 2010]. Here it utilizes value net v to truncate the search at an unexpanded node and policy net p for action selection at an expanded node s using the PUCT [Silver *et al.*, 2018] formula: $\text{MaxPUCT}(s, p) = \arg \max_{a \in \mathcal{A}(s)} \frac{s.child(a).value}{s.child(a).visits} + c_{uct} \cdot p(s, a) \cdot \frac{\sqrt{s.total_visits}}{s.child(a).visits+1}$, for some constant c_{uct} . Then at the end of the search call, it returns an action a^* which receives the most visits at the root node, and a policy π^* representing the action distribution of the search at the root node.

Algorithm 2 has two important differences from previous methods. First, rather than computing exact posteriors, we use the deep generative model g learned in Algorithm 1 to sample world states. As such, this approach may be capable of scaling to large domains where previous approaches such as particle filtering [Somani *et al.*, 2013] fail.

Second, the imperfect information of the underlying POMDP consists of both (i) the actual world state h and (ii)

opponents’ pure-strategy commitment π_{-i} . We make use of the fact $\Pr(h, \pi_{-i} \mid s, \sigma_{-i}) = \Pr(h \mid s, \sigma_{-i}) \Pr(\pi_{-i} \mid h, \sigma_{-i})$ such that we approximate $\Pr(h \mid s, \sigma_{-i})$ by g and compute $\Pr(\pi_{-i} \mid h, \sigma_{-i})$ exactly via Bayes’ rule. Computing $\Pr(\pi_{-i} \mid h, \sigma_{-i})$ can be viewed as a Bayesian learning procedure [Kreps and Wilson, 1982; Hernandez-Leal and Kaisers, 2017; Albrecht *et al.*, 2016; Kalai and Lehrer, 1993] that keeps updating an *online opponent model* $\Pr(\pi_{-i} \mid h, \sigma_{-i})$. Therefore, our agent is capable of performing test-time search while automatically inferring environmental state as well as opponents’ strategies during online decision making.

Algorithm 3 Opponent Modeling via PSRO and GenBR

```

function PSRO( $\mathcal{G}$ , MSS)
  Initialize strategy sets  $\forall i, \Pi_i = \{\pi_i^0\}$ , mixed
  strategies  $\sigma_i(\pi_i^0) = 1, \forall i$ , payoff tensor  $U^0$ .
  for  $t \in \{0, 1, 2 \dots, T\}$  do
    for  $i \in \mathcal{N}$  do
       $\Pi_i \leftarrow \Pi_i \cup \{\text{GenBR}(i, \sigma, \text{num\_eps})\}$ 
    end for
    Update missing entries in  $U^t$  via simulations
     $\sigma \leftarrow \text{MSS}(U^t)$ 
  end for
  return  $\Pi = (\Pi_1, \Pi_2, \dots, \Pi_N), \sigma$ 
end function

```

4 Game-Theoretic Opponent Modeling

In this section, we describe our complete training algorithm for opponent modeling. We use Policy Space Response Oracles to obtain an *offline opponent model* σ_{-i} for training GenBR in Algorithm 1. We first introduce empirical game-theoretic analysis (EGTA) and PSRO, and then propose new solution concepts in PSRO based on bargaining theory, and provide empirical results of our new meta-strategy solvers at the end of this section.

4.1 Empirical Game-Theoretic Analysis and Policy-Space Response Oracles

Empirical game-theoretic analysis (EGTA) [Wellman *et al.*, 2025] is an approach to reasoning about large sequential games through normal-form *empirical game* models, induced by simulating enumerated subsets of the players’ full policies in the sequential game. Policy-Space Response Oracles (PSRO) [Lanctot *et al.*, 2017] uses EGTA to incrementally build up each player’s set of policies (“oracles”) through repeated applications of approximate best response using RL. Each player’s initial set contains a single policy (*e.g.* uniform random) resulting in a trivial empirical game U^0 containing one cell. On epoch t , given N sets of policies Π_i^t for $i \in \mathcal{N}$, utility tensors for the empirical game U^t are estimated via simulation.

A *meta-strategy solver* (MSS) derives a profile σ^t , generally mixed, over the empirical game strategy space. A best response oracle, say $b_i^t(\sigma_{-i}^t)$, is then computed for each player i by training against policies sampled from opponent model σ_{-i}^t , and are added to strategy sets for the next

epoch: $\Pi_i^{t+1} = \Pi_i^t \cup \{b_i^t(\sigma_{-i}^t)\}$. Since the opponent policies are fixed, the oracle response step is a single-agent problem [Oliehoek and Amato, 2014]; RL and search can feasibly handle large state and policy spaces. Our full algorithm (Algorithm 3) employs GenBR as the oracle step in PSRO.

PSRO naturally fits our focus of automating opponent modeling as it generates opponent models σ_{-i} through pure game-theoretic reasoning and reinforcement learning. Furthermore, since each strategy (except the first ones) in the pool is a best response against an early-iteration opponent model (which itself consists of best responses), it in fact induces a cognitive hierarchy [Camerer *et al.*, 2004] of rationalizable strategies [Bernheim, 1984]. An important question is choosing which MSS¹ to compute an opponent mixture. Since our primary application domain of interest in this paper is negotiation game, it is natural to consider solution concepts from bargaining theory as MSSs. Next we introduce computational results of new MSSs based on Nash bargaining solution which were not investigated in previous works.

4.2 Empirical Game Nash Bargaining Solution

In contrast to non-cooperative game theory, bargaining theory considers scenarios where players’ utilities are not entirely in conflict, and need to negotiate to achieve a possible cooperative outcome. The *Nash Bargaining solution* (NBS) selects a Pareto-optimal payoff profile that uniquely satisfies axioms specifying desirable properties of invariance, symmetry, and independence of irrelevant alternatives [Nash, 1950; Ponsati and Watson, 1997]. The axiomatic characterization of NBS abstracts away the process by which said outcomes are obtained through strategic interaction.

Define the set of achievable payoffs as all expected utilities $u_i(\mathbf{x})$ under a joint-policy profile \mathbf{x} . Denote the disagreement outcome of player i , which is the payoff it gets if no agreement is achieved, as d_i . The NBS is the set of policies that maximizes the *Nash bargaining score* (A.K.A. *Nash product*):

$$\max_{\mathbf{x} \in \Delta(\Pi)} \prod_{i \in \mathcal{N}} (u_i(\mathbf{x}) - d_i), \quad (1)$$

which, when $N = 2$, leads to a quadratic program (QP) with the constraints derived from the policy space structure [Griffin, 2010]. However, even in this simplest case of two-player matrix games, the non-concave objective poses a problem for most QP solvers. Furthermore, scaling to N players requires higher-order polynomial solvers.

Instead of using higher-order polynomial solvers, we propose an algorithm based on (projected) gradient ascent [Singh *et al.*, 2000; Boyd and Vandenberghe, 2004]. Note that the Nash product is non-concave, so instead of maximizing it, we maximize the *log Nash product* $g(\mathbf{x}) =$

$$\log(\prod_{i \in \mathcal{N}} (u_i(\mathbf{x}) - d_i)) = \sum_{i \in \mathcal{N}} \log(u_i(\mathbf{x}) - d_i), \quad (2)$$

which has the same maximizers as (1), and is a sum of concave functions, hence concave. The process is depicted in

¹In App. G.1, we conduct extensive experiments over 16 MSSs on 12 different benchmark games on OpenSpiel [Lanctot *et al.*, 2019]. Appendices can be found in [Li *et al.*, 2023].

Algorithm 4 NBS by projected gradient ascent

Input: Initial iterate \mathbf{x} , payoff tensor U .
function NBS(\mathbf{x}^0, U)
 Let $g(\mathbf{x})$ be the log Nash product defined in eqn (2)
 for $t = 0, 1, 2 \dots, T$ **do**
 $\mathbf{y}^{t+1} \leftarrow \mathbf{x}^t + \alpha^t \nabla g(\mathbf{x}^t)$
 $\mathbf{x}^{t+1} \leftarrow \text{Proj}(\mathbf{y}^{t+1})$
 end for
 Return $\arg \max_{\mathbf{x}^{t=0:T}} g(\mathbf{x}^t)$
end function

Algorithm 4; Proj is the ℓ_2 projection onto the simplex. We can prove it has a convergence rate of $O(T^{-1/2})$. For a proof, see App. C.

Theorem 4.1. Assume any deal is better than no deal by $\kappa > 0$, i.e., $u_i(\mathbf{x}) - d_i \geq \kappa > 0$ for all i, \mathbf{x} . Let $\{\mathbf{x}^t\}$ be the sequence generated by Algorithm 4 with starting point $\mathbf{x}^0 = |\Pi|^{-1} \mathbf{1}$ and step size sequence $\alpha^t = \frac{\kappa \sqrt{(|\Pi|-1)/|\Pi|}}{u^{\max} N} (t+1)^{-1/2}$. Then, for all $t > 0$ one has

$$\max_{\mathbf{x} \in \Delta^{|\Pi|-1}} g(\mathbf{x}) - \max_{0 \leq s \leq t} g(\mathbf{x}^s) \leq \frac{u^{\max} N \sqrt{|\Pi|}}{\kappa \sqrt{t+1}} \quad (3)$$

where $u^{\max} = \max_{i, \mathbf{x}} u_i(\mathbf{x})$, $|\Pi|$ is the number of possible pure joint strategies, and \mathbf{x} is assumed to be a joint correlation device (μ).

Besides directly using NBS, we also consider (1) using NBS to select a correlated equilibrium (CE) and coarse correlated equilibrium (CCE) as an MSS, which we denote as max-NBS-(C)CE and (2) profile that maximizes social welfare. A comprehensive list of MSSs that we investigated in our experiments is in App. A.

4.3 Empirical Results on Colored Trails

Here we study the performance of our NBS-based MSSs on colored trails, a highly configurable negotiation game played on a grid [Gal *et al.*, 2010] of colored tiles, which has been actively studied by the AI community [Grosz *et al.*, 2004; Ficici *et al.*, 2008]. Colored Trails does not require search since the number of moves is small, so we use classical RL based oracles (DQN and Boltzmann DQN) to isolate the effects of the new meta-strategy solvers.

We use a three-player variant [Ficici *et al.*, 2008] depicted in Figure 2. At the start of each episode, an instance (a board and colored chip allocation per player) is randomly sampled from a database of strategically interesting and balanced configurations [de Jong *et al.*, 2011, Section 5.1]. There are two proposers (P1 and P2) and a responder (R). R can see all players’ chips, both P1 and P2 can see R’s chips; however, proposers cannot see each other’s chips. Each proposer, makes an offer to the receiver. The receiver then decides to accept one offer and trades chips with that player, or passes. Then, players spend chips to get as close to the flag as possible (each chip allows a player to move to an adjacent tile if it is the same color as the chip). For any configuration (player i at position p), define $\text{SCORE}(p, i) = (-25)d + 10t$, where d is the Manhattan distance between p and the flag, and t is the number of




Figure 2: Three-Player Colored Trails.




Figure 3: Empirical reduction in Pareto Gap on test game configurations, and example evolution toward Pareto front (right).

player i ’s chips. The utility for player i is their *gain*: score at the end of the game minus the score at the start. We compute the Pareto frontier for a subset of configurations, and define the Pareto Gap (P-Gap) as the minimal ℓ_2 distance from the outcomes to the outer surfaces of the convex hull of the Pareto front, which is then averaged over the set of configurations in the database.

Figure 3 shows representative results of PSRO agents with different MSSs on Colored Trails (for full graphs, and evolution of score diagrams, see App. G.2). The best-performing MSS is NBS-joint, beating the next best by a full 3 points. The NBS meta-strategy solvers comprise five of the six best MSSs under this evaluation. An example of the evolution of the expected score over PSRO iterations is also shown, moving toward the Pareto front, though not via a direct path.

5 Experiments

In this section, we report our major results on the Deal-or-No-Deal (DoND) negotiation game.

5.1 Negotiation Game: Deal or No Deal

“Deal or No Deal” (DoND) is a simple alternating-offer bargaining game with incomplete information, which has been used in many AI studies [Lewis *et al.*, 2017; Cao *et al.*, 2018]. Our focus is to train RL agents to play against humans *without human data*, similar to previous work [Strouse *et al.*, 2021].




Figure 4: Best response performance using different generative models, against (left) uniform random opponent, (middle) DQN response to uniform random, (right) self-play DQN opponent. **Uniform** samples a legal preference vector uniformly at random, **bad1** always samples the first legal instance in the database, **bad2** always samples the last legal instance in the database, **cheat** always samples the actual underlying world state, **exact** samples from the exact posterior, **simple learn** is the method described in Algorithm 1, and **DQN** is a simple DQN responder that does not use a generative model nor search. All results are averaged across 30 random seeds.

An example game of DoND is shown in Figure 1. Two players are assigned *private* preferences $w_1 \geq 0, w_2 \geq 0$ for three different items (books, hats, and basketballs). At the start of the game, there is a pool c of 5 to 7 items drawn randomly such that: (i) the total value for a player of all items is 10: $w_1 \cdot c = w_2 \cdot c = 10$, (ii) each item has non-zero value for at least one player: $w_1 + w_2 > 0$, (iii) some items have non-zero value for both players, $w_1 \odot w_2 \neq 0$, where \odot represents element-wise multiplication.

The players take turns proposing how to split the pool of items, for up to 10 turns (5 turns each). If an agreement is not reached, the negotiation ends and players both receive 0. Otherwise, the agreement represents a split of the items to each player, $o_1 + o_2 = c$, and player i receives a utility of $w_i \cdot o_i$. DoND is an imperfect information game because the other player’s preferences are private. We use a database of 6796 bargaining instances made publicly available in [Lewis *et al.*, 2017]. Deal or No Deal is a significantly large game, with an estimated $1.32 \cdot 10^{13}$ information states for player 1 and $5.69 \cdot 10^{11}$ information states for player 2 (see App. D.2 for details).

5.2 Generative World State Sampling

We now show that both the search and the generative model contribute to achieving higher reward than RL alone. The input of our deep generative model is one’s private values v_i and public observations, and the output is a distribution over v_{-i} (detailed in the Appendix). We compute approximate best responses to three opponents: uniform random, a DQN agent trained against uniform random, and a DQN agent trained in self-play. We compare different world state sampling models as well to DQN in Figure 4, where the deep generative model approach is denoted as *simple learn*.

The benefit of search is clear: the search methods achieve a high value in a few episodes, a level that takes DQN many more episodes to reach (against random and DQN response to random) and a value that is not reached by DQN against the self-play opponent. The best generative models are the true posterior (*exact*) and the actual underlying world state (*cheat*). However, the exact posterior is generally intractable and the underlying world state is not accessible to the agent at test-time, so these serve as idealistic upper-bounds. Uniform

seems to be a compromise between the bad and ideal models. The deep generative model approach is roughly comparable to uniform at first, but learns to approximate the posterior as well as the ideal models as data is collected. In contrast, DQN eventually reaches the performance of the uniform model against the weaker opponent but not against the stronger opponent even after 20000 episodes.

5.3 Studies with Human Participants

We recruited participants from Prolific [Pe’er *et al.*, 2021; Pe’er *et al.*, 2017] to evaluate the performance of our agents in DoND (overall 346; 41.4% female, 56.9% male, 0.9% trans or nonbinary; median age range: 30–40), following established ethical guidelines for research with human participants [McKee, 2024]. Crucially, participants played DoND for real monetary stakes, with an additional payout for each point earned in the game. Participants first read game instructions and completed a short comprehension test to ensure they understood key aspects of DoND’s rules. Participants then played five episodes of DoND with a randomized sequence of opponents. Episodes terminated after players reached a deal, after 10 moves without reaching a deal, or after 120 seconds elapsed. After playing all five episodes, participants completed a debrief questionnaire collecting standard demographic information and open-ended feedback on the study.

Training Details Our infrastructure restricts that each human participant can only play five matches with our bots. Therefore we decided to select five different agents so every participant can play each of these once. For comparison, we decided to include one independent RL agent and four search-improved PSRO agents of different playing styles. For the independent RL agent, we trained two classes of independent RL agents in self-play: (1) DQN [Mnih *et al.*, 2015] and Boltzmann DQN [Cui and Koeppl, 2021], and (2) policy gradient algorithms such as A2C, QPG, RPG and RMPG [Srinivasan *et al.*, 2018]. We fine-tuned their hyperparameters and eventually select an instance of self-play DQN based on both individual returns and social welfare performances.

For PSRO agents, we consider 16 different meta-strategy solvers, and 4 different back-propagating value types during the tree search procedure, making it 64 different combina-

Agent	\bar{u}_{Humans}		\bar{u}_{Agent}		\bar{u}_{Comb}		NBS
IndRL	5.86	[5.37, 6.40]	6.50	[5.93, 7.06]	6.18	[5.82, 6.56]	38.12
Comp1	5.14	[4.56, 5.63]	5.49	[4.87, 6.11]	5.30	[4.93, 5.76]	28.10
Comp2	6.00	[5.49, 6.55]	5.54	[4.96, 6.10]	5.76	[5.33, 6.12]	33.13
Coop	6.71	[6.23, 7.20]	6.17	[5.66, 6.64]	6.44	[6.11, 6.75]	41.35
Fair	7.39	[6.89, 7.87]	5.98	[5.44, 6.49]	6.69	[6.34, 7.01]	44.23

Table 1: Humans vs. agents performance with **129** human participants, **547** games total. \bar{u}_X refers to the average utility to group X (for the humans when playing the agent, or for the agent when playing the humans), Comb refers to Combined (human and agent). Square brackets indicate 95% confidence intervals. IndRL refers to Independent RL (DQN), Comp1 and Comp2 are the two top-performing competitive agents, Coop is the most cooperative agent, and Fair is fairest agent. NBS is the Nash bargaining score (Eq 1).

tion in total. Notice that the original MCTS algorithm (Algorithm 2) back-propagates individual rewards during each simulation phase for the search agent.

We consider two way of extracting the final agents given sets of policies Π produced by PSRO, one based on the final-iteration MSS mixture and another based on the final-iteration search-based best response (details are in App F). We trained over 100 PSRO agents with different combinations of MSS, back-propagation targets, and extraction methods. To select among these agents, we apply empirical game-theoretic analysis [Wellman *et al.*, 2025] and obtain a head-to-head empirical game matrix. We eventually selected: (i) two most competitive agents (Comp1, Comp2) (maximizing utility), (ii) the most cooperative agents (Coop) (maximizing social welfare), the (iii) the fairest agent (Fair) (minimizing social inequity [Fehr and Schmidt, 1999]); (iv) a separate top-performing independent RL agent (IndRL) trained in self-play (DQN). Both Coop and Fair are using Nash product as the back-propagating values during tree search, while Comp1 uses inequity aversion and Comp2 uses individual rewards. Comp1, Comp2 and Fair are trained using max-Gini correlated equilibrium notions [Marris *et al.*, 2021], while Coop uses uniform distribution as the MSS.

Results We collect data under two conditions: human vs. human (HvH), and human vs. agent (HvA). In the HvH condition, we collect 483 games: 482 end in deals made (99.8%), and achieve a return of 6.93 (95% c.i. [6.72, 7.14]), on expectation. We collect 547 games in the HvA condition: 526 end in deals made (96.2%; see Table 1). DQN achieves the highest individual return. By looking at the combined reward, it achieves this by aggressively reducing the human reward (down to 5.86)—possibly by playing a policy that is less human-compatible. The competitive PSRO agents seem to do the same, but without overly exploiting the humans, resulting in the lowest social welfare overall. The cooperative agent achieves significantly higher combined utility playing with humans. Better yet is Human vs. Fair, the only Human vs. Agent combination to achieve social welfare comparable to the Human vs. Human social welfare.

Another metric is the objective value of the empirical NBS from Eq. 1, over the symmetric game (randomizing the starting player) played between the different agent types. This metric favors Pareto-efficient outcomes, balancing between the improvement obtained by both sides. From App G.3, the NBS of Coop decreases when playing humans, from 44.51 \rightarrow 41.35—perhaps due to overfitting to agent-learned conven-

tions. Fair increases slightly (42.56 \rightarrow 44.23). The NBS of DQN rises from 23.48 \rightarrow 38.12. The NBS of the competitive agents also rises playing against humans (24.70 \rightarrow 28.10, and 25.44 \rightarrow 28.10), and also when playing with Fair (24.70 \rightarrow 29.63, 25.44 \rightarrow 28.73). The fair agent is both adaptive to many different types of agents, and cooperative, increasing the social welfare in all groups it negotiated with. This could be due to its MSS putting significant weight on many policies leading to Bayesian prior with high support, or its backpropagation of the product of utilities rather than individual return.

6 Conclusion

We proposed a general-purpose multiagent training regime that combines the power of MCTS search and a population-based training framework, for general-sum imperfect information domains. We developed a novel search technique that combines IS-MCTS with a deep belief learning module coupled with the RL training loop, which scale to large belief and state spaces. The outer loop of our algorithm is implemented by PSRO, which iteratively trains and adds search strategies guided by game-theoretic analysis. On one hand, search serves as a strong best response method within the PSRO loop, which provides an instance of the framework of its own interests. On the other hand, PSRO automatically produces a belief hierarchy over the opponents’ strategies, which endows the search with the capability of inferring opponent types during online decision makings. This dual view of the whole training architecture illustrates its effectiveness in producing agents that are capable of opponent modeling through game-theoretic analysis and planning forward at test-time.

Ethics Statement

We believe our GenBR method with the PSRO training loop advances the general opponent modeling and planning techniques in multi-agent systems with little domain knowledge. Our methods can be potentially deployed in a variety of applications, including automated bidding in auctions, negotiation, cybersecurity, warehouse robotics, and autonomous vehicle systems. All of these are multi-agent scenarios that involve general-sum, imperfect information elements.

One of the potential risks is value misalignment in negotiation. The method can produce strategies that are unpredictable and not easily explained, which could lead to exploitative behaviors in negotiation that are misaligned with

the users' intents. This could potentially cause harm in the economic system and reduce market efficiency. Any deployed use of artificial agents built using our algorithm would need to first be thoroughly tested, ideally by third party, and undergo a controlled private study with humans to identify any potentially harmful behavior.

References

- [Agrawal *et al.*, 2018] Akshay Agrawal, Robin Verschueren, Steven Diamond, and Stephen Boyd. A rewriting system for convex optimization problems. *Journal of Control and Decision*, 5(1):42–60, 2018.
- [Albrecht and Stone, 2018] Stefano V Albrecht and Peter Stone. Autonomous agents modelling other agents: A comprehensive survey and open problems. *Artificial Intelligence*, 258:66–95, 2018.
- [Albrecht *et al.*, 2016] Stefano V. Albrecht, Jacob W. Crandall, and Subramanian Ramamoorthy. Belief and truth in hypothesised behaviours. *Artificial Intelligence*, 235:63–94, 2016.
- [Baarslag *et al.*, 2016] Tim Baarslag, Mark JC Hendriks, Koen V. Hindriks, and Catholijn M. Jonker. Learning about the opponent in automated bilateral negotiation: a comprehensive survey of opponent modeling techniques. *Autonomous Agents and Multi-Agent Systems*, 30(5):849–898, 2016.
- [Balduzzi *et al.*, 2018] David Balduzzi, Karl Tuyls, Julien Perolat, and Thore Graepel. Re-evaluating evaluation. In *Thirty-Second International Conference on Neural Information Processing Systems*, pages 3272–3283, 2018.
- [Bard *et al.*, 2013] Nolan Bard, Michael Johanson, Neil Burch, and Michael Bowling. Online implicit agent modelling. In *Proceedings of the Twelfth International Conference on Autonomous Agents and Multi-Agent Systems*, 2013.
- [Beck and Teboulle, 2003] Amir Beck and Marc Teboulle. Mirror descent and nonlinear projected subgradient methods for convex optimization. *Operations Research Letters*, 31(3):167–175, 2003.
- [Bernheim, 1984] B. Douglas Bernheim. Rationalizable strategic behavior. *Econometrica*, 52:1007–1028, 1984.
- [Boyd and Vandenberghe, 2004] Stephen Boyd and Lieven Vandenberghe. *Convex Optimization*. Cambridge University Press, 2004.
- [Brown, 1951] George W. Brown. Iterative solution of games by fictitious play. *Activity Analysis of Production and Allocation.*, 13(1):374, 1951.
- [Camerer *et al.*, 2004] Colin F. Camerer, Teck-Hua Ho, and Juin-Kuan Chong. A cognitive hierarchy model of games. *Quarterly Journal of Economics*, 119(3):861–898, 2004.
- [Cao *et al.*, 2018] Kris Cao, Angeliki Lazaridou, Marc Lanctot, Joel Z. Leibo, Karl Tuyls, and Stephen Clark. Emergent communication through negotiation. In *Sixth International Conference on Learning Representations*, 2018.
- [Cowling *et al.*, 2012] Peter I. Cowling, Edward J. Powley, and Daniel Whitehouse. Information set Monte Carlo tree search. *IEEE Transactions on Computational Intelligence and AI in Games*, 4:120–143, 2012.
- [Cui and Koepl, 2021] Kai Cui and Heinz Koepl. Approximately solving mean field games via entropy-regularized deep reinforcement learning. In *Twenty-Fourth International Conference on Artificial Intelligence and Statistics*, 2021.
- [de Jong *et al.*, 2011] Steven de Jong, Daniel Hennes, Karl Tuyls, and Ya'akov Gal. Metastrategies in the colored trails game. In *Tenth International Conference on Autonomous Agents and Multi-Agent Systems*, pages 551–558, 2011.
- [Diamond and Boyd, 2016] Steven Diamond and Stephen Boyd. CVXPY: A Python-embedded modeling language for convex optimization. *Journal of Machine Learning Research*, 17(83):1–5, 2016.
- [Domahidi *et al.*, 2013] A. Domahidi, E. Chu, and S. Boyd. ECOS: An SOCP solver for embedded systems. In *European Control Conference*, pages 3071–3076, 2013.
- [Farina *et al.*, 2019] Gabriele Farina, Chun Kai Ling, Fei Fang, and Tuomas Sandholm. Correlation in extensive-form games: Saddle-point formulation and benchmarks. In *Thirty-Third International Conference on Neural Information Processing Systems*, 2019.
- [Fehr and Schmidt, 1999] E. Fehr and K. Schmidt. A theory of fairness, competition and cooperation. *Quarterly Journal of Economics*, 114:817–868, 1999.
- [Ficici *et al.*, 2008] Sevan G. Ficici, David C. Parkes, and Avi Pfeffer. Learning and solving many-player games through a cluster-based representation. In *Twenty-Fourth Conference on Uncertainty in Artificial Intelligence*, pages 188–195, 2008.
- [Gal *et al.*, 2010] Ya'akov Gal, Barbara Grosz, Sarit Kraus, Avi Pfeffer, and Stuart Shieber. Agent decision-making in open mixed networks. *Artificial Intelligence*, 174(18):1460–1480, 2010.
- [Gemp *et al.*, 2021] Ian Gemp, Rahul Savani, Marc Lanctot, Yoram Bachrach, Thomas W. Anthony, Richard Everett, Andrea Tacchetti, Tom Eccles, and János Kramár. Sample-based approximation of Nash in large many-player games via gradient descent. In *Twenty-First International Conference on Autonomous Agents and Multi-Agent Systems*, 2021.
- [Griffin, 2010] Christopher Griffin. Quadratic programs and general-sum games. In *Game Theory: Penn State Math 486 Lecture Notes*, pages 138–144. Online note., 2010. <https://docs.ufpr.br/~volmir/Math486.pdf>.
- [Grosz *et al.*, 2004] Barbara J. Grosz, Sarit Kraus, Shavit Talman, Boaz Stossel, and Moti Havlin. The influence of social dependencies on decision-making: Initial investigations with a new game. In *Third International Joint Conference on Autonomous Agents and Multi-Agent Systems*, pages 782–789, 2004.

- [Hart and Mas-Colell, 2000] S. Hart and A. Mas-Colell. A simple adaptive procedure leading to correlated equilibrium. *Econometrica*, 68(5):1127–1150, 2000.
- [Hernandez *et al.*, 2023] Daniel Hernandez, Hendrik Baier, and Michael Kaisers. Brexit: On opponent modelling in expert iteration. In *Thirty-Second International Joint Conference on Artificial Intelligence*, 2023.
- [Hernandez-Leal and Kaisers, 2017] Pablo Hernandez-Leal and Michael Kaisers. Learning against sequential opponents in repeated stochastic games. In *Third Multi-disciplinary Conference on Reinforcement Learning and Decision Making*, volume 25, 2017.
- [Johanson and Bowling, 2009] Michael Johanson and Michael Bowling. Data biased robust counter strategies. In *Proceedings of the Twelfth International Conference on Artificial Intelligence and Statistics*, pages 264–271, 2009.
- [Jordan *et al.*, 2007] Patrick R. Jordan, Christopher Kiekintveld, and Michael P. Wellman. Empirical game-theoretic analysis of the TAC supply chain game. In *Sixth International Joint Conference on Autonomous Agents and Multi-Agent Systems*, pages 1–8, 2007.
- [Kalai and Lehrer, 1993] Ehud Kalai and Ehud Lehrer. Rational learning leads to Nash equilibrium. *Econometrica: Journal of the Econometric Society*, pages 1019–1045, 1993.
- [Kitano *et al.*, 1998] Hiroaki Kitano, Milind Tambe, Peter Stone, Manuela Veloso, Silvia Coradeschi, Eiichi Osawa, Hitoshi Matsubara, Itsuki Noda, and Minoru Asada. The robocup synthetic agent challenge 97. In *RoboCup-97: Robot Soccer World Cup I 1*, pages 62–73, 1998.
- [Kreps and Wilson, 1982] David M. Kreps and Robert Wilson. Reputation and imperfect information. *Journal of Economic Theory*, 27(2):253–279, 1982.
- [Kuhn, 1953] H. W. Kuhn. Extensive games and the problem of information. *Annals of Mathematics Studies*, 28:193–216, 1953.
- [Lanctot *et al.*, 2017] Marc Lanctot, Vinicius Zambaldi, Audrunas Gruslys, Angeliki Lazaridou, Karl Tuyls, Julien Pérolat, David Silver, and Thore Graepel. A unified game-theoretic approach to multiagent reinforcement learning. In *Thirty-First International Conference on Neural Information Processing Systems*, pages 4190–4203, 2017.
- [Lanctot *et al.*, 2019] Marc Lanctot, Edward Lockhart, Jean-Baptiste Lespiau, Vinicius Zambaldi, Satyaki Upadhyay, Julien Pérolat, Sriram Srinivasan, Finbarr Timbers, Karl Tuyls, Shayegan Omidshafiei, Daniel Hennes, Dustin Morrill, Paul Muller, Timo Ewalds, Ryan Faulkner, János Kramár, Bart De Vylder, Brennan Saeta, James Bradbury, David Ding, Sebastian Borgeaud, Matthew Lai, Julian Schrittwieser, Thomas Anthony, Edward Hughes, Ivo Danihelka, and Jonah Ryan-Davis. Openspiel: A framework for reinforcement learning in games. *arXiv preprint arXiv:1908.09453*, 2019.
- [Lewis *et al.*, 2017] Mike Lewis, Denis Yarats, Yann N. Dauphin, Devi Parikh, and Dhruv Batra. Deal or no deal? end-to-end learning for negotiation dialogues. In *Conference on Empirical Methods in Natural Language Processing*, 2017.
- [Li *et al.*, 2023] Zun Li, Marc Lanctot, Kevin R McKee, Luke Marris, Ian Gemp, Daniel Hennes, Paul Muller, Kate Larson, Yoram Bachrach, and Michael P Wellman. Combining deep reinforcement learning and search with generative models for game-theoretic opponent modeling. *arXiv preprint arXiv:2302.00797*, 2023.
- [Lockhart *et al.*, 2019] Edward Lockhart, Marc Lanctot, Julien Pérolat, Jean-Baptiste Lespiau, Dustin Morrill, Finbarr Timbers, and Karl Tuyls. Computing approximate equilibria in sequential adversarial games by exploitability descent. In *Twenty-Eighth International Joint Conference on Artificial Intelligence*, 2019.
- [Marris *et al.*, 2021] Luke Marris, Paul Muller, Marc Lanctot, Karl Tuyls, and Thore Graepel. Multi-agent training beyond zero-sum with correlated equilibrium meta-solvers. In *Twenty-Eighth International Conference on Machine Learning*, 2021.
- [Marris *et al.*, 2022] Luke Marris, Marc Lanctot, Ian Gemp, Shayegan Omidshafiei, Stephen McAleer, Jerome Connor, Karl Tuyls, and Thore Graepel. Game theoretic rating in n -player general-sum games with equilibria. *arXiv preprint arXiv:2210.02205*, 2022.
- [McKee, 2024] Kevin R McKee. Human participants in AI research: Ethics and transparency in practice. *IEEE Transactions on Technology and Society*, 2024.
- [McKelvey and Palfrey, 1995] Richard D. McKelvey and Thomas R. Palfrey. Quantal response equilibria for normal form games. *Games and Economic Behavior*, 10(1):6–38, 1995.
- [McMahan *et al.*, 2003] H. Brendan McMahan, Geoffrey J. Gordon, and Avrim Blum. Planning in the presence of cost functions controlled by an adversary. In *Twentieth International Conference on International Conference on Machine Learning*, page 536–543, 2003.
- [Mnih *et al.*, 2015] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A. Rusu, Joel Veness, Marc G. Belle-mare, Alex Graves, Martin Riedmiller, Andreas K. Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharmashan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.
- [Muller *et al.*, 2020] Paul Muller, Shayegan Omidshafiei, Mark Rowland, Karl Tuyls, Julien Perolat, Siqi Liu, Daniel Hennes, Luke Marris, Marc Lanctot, Edward Hughes, Zhe Wang, Guy Lever, Nicolas Heess, Thore Graepel, and Remi Munos. A generalized training approach for multiagent learning. In *Eighth International Conference on Learning Representations*, 2020.

- [Murphy *et al.*, 2011] Ryan O Murphy, Kurt A Ackermann, and Michel Handgraaf. Measuring social value orientation. *Judgment and Decision making*, 6(8):771–781, 2011.
- [Nash, 1950] John Nash. The bargaining problem. *Econometrica*, 18(2):155–162, 1950.
- [O’Donoghue *et al.*, 2021] Brendan O’Donoghue, Eric Chu, Neal Parikh, and Stephen Boyd. SCS: Splitting conic solver, version 3.2.1. <https://github.com/cvxgrp/scs>, November 2021.
- [Oliehoek and Amato, 2014] Frans A. Oliehoek and Christopher Amato. Best response Bayesian reinforcement learning for multiagent systems with state uncertainty. In *Ninth AAMAS Workshop on Multi-Agent Sequential Decision Making in Uncertain Domains*, 2014.
- [Omidshafiei *et al.*, 2019] Shayegan Omidshafiei, Christos Papadimitriou, Georgios Piliouras, Karl Tuyls, Mark Rowland, Jean-Baptiste Lespiau, Wojciech M. Czarnecki, Marc Lanctot, Julien Perolat, and Remi Munos. α -rank: Multi-agent evaluation by evolution. *Scientific reports*, 9(1):1–29, 2019.
- [Ortiz *et al.*, 2007] Luis E. Ortiz, Robert E. Schapire, and Sham M. Kakade. Maximum entropy correlated equilibria. In *Eleventh International Conference on Artificial Intelligence and Statistics*, pages 347–354, 2007.
- [Pe’er *et al.*, 2017] Eyal Pe’er, Laura Brandimarte, Sonam Samat, and Alessandro Acquisti. Beyond the Turk: Alternative platforms for crowdsourcing behavioral research. *Journal of Experimental Social Psychology*, 70:153–163, 2017.
- [Pe’er *et al.*, 2021] Eyal Pe’er, David Rothschild, Andrew Gordon, Zak Evernden, and Ekaterina Damer. Data quality of platforms and panels for online behavioral research. *Behavior Research Methods*, pages 1–20, 2021.
- [Ponsati and Watson, 1997] Clara Ponsati and Joel Watson. Multiple-issue bargaining and axiomatic solutions. *International Journal of Game Theory*, 62:501–524, 1997.
- [Shoham and Leyton-Brown, 2009] Y. Shoham and K. Leyton-Brown. *Multiagent Systems: Algorithmic, Game-Theoretic, and Logical Foundations*. Cambridge University Press, 2009.
- [Silver and Veness, 2010] David Silver and Joel Veness. Monte-carlo planning in large pomdps. In *Twenty-Fourth International Conference on Neural Information Processing Systems*, volume 23, 2010.
- [Silver *et al.*, 2018] David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharmashan Kumaran, Thore Graepel, Timothy Lillicrap, Karen Simonyan, and Demis Hassabis. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.
- [Singh *et al.*, 2000] Satinder Singh, Michael Kearns, and Yishay Mansour. Nash convergence of gradient dynamics in general-sum games. In *Sixteenth Conference on Uncertainty in Artificial Intelligence*, 2000.
- [Sokota *et al.*, 2021] Samuel Sokota, Edward Lockhart, Finbarr Timbers, Elnaz Davoodi, Ryan D’Orazio, Neil Burch, Martin Schmid, Michael Bowling, and Marc Lanctot. Solving common-payoff games with approximate policy iteration. In *Thirty-Fifth AAAI Conference on Artificial Intelligence*, pages 9695–9703, 2021.
- [Somani *et al.*, 2013] Adhiraj Somani, Nan Ye, David Hsu, and Wee Sun Lee. Despot: Online pomdp planning with regularization. In *Twenty-Seventh International Conference on Neural Information Processing Systems*, volume 26, 2013.
- [Srinivasan *et al.*, 2018] Sriram Srinivasan, Marc Lanctot, Vinicius Zambaldi, Julien Pérolat, Karl Tuyls, Rémi Munos, and Michael Bowling. Actor-critic policy optimization in partially observable multiagent environments. In *Thirty-First International Conference on Neural Information Processing Systems*, 2018.
- [Strouse *et al.*, 2021] DJ Strouse, Kevin McKee, Matt Botvinick, Edward Hughes, and Richard Everett. Collaborating with humans without human data. In *Thirty-Fifth International Conference on Neural Information Processing Systems*, pages 14502–14515, 2021.
- [Timbers *et al.*, 2022] Finbarr Timbers, Nolan Bard, Edward Lockhart, Marc Lanctot, Martin Schmid, Neil Burch, Julian Schrittwieser, Thomas Hubert, and Michael Bowling. Approximate exploitability: Learning a best response in large games. In *Thirty-First International Joint Conference on Artificial Intelligence*, pages 3487–3493, 2022.
- [Wang *et al.*, 2021] Yongzhao Wang, Qiurui Ma, and Michael P Wellman. Evaluating strategy exploration in empirical game-theoretic analysis. In *Twentieth International Conference on Autonomous Agents and Multi-Agent Systems*, 2021.
- [Wang *et al.*, 2023] Tony Tong Wang, Adam Gleave, Nora Belrose, Tom Tseng, Joseph Miller, Kellin Pelrine, Michael D Dennis, Yawen Duan, Viktor Pogrebnik, Sergey Levine, and Stuart Russell. Adversarial policies beat superhuman Go AIs. In *Fortieth International Conference on Machine Learning*, 2023.
- [Wellman *et al.*, 2025] Michael P Wellman, Karl Tuyls, and Amy Greenwald. Empirical game theoretic analysis: A survey. *Journal of Artificial Intelligence Research*, 82:1017–1076, 2025.
- [Zinkevich *et al.*, 2008] Martin Zinkevich, Michael Johanson, Michael Bowling, and Carmelo Piccione. Regret minimization in games with incomplete information. In *Twentieth Conference on Neural Information Processing Systems*, pages 905–912, 2008.

A Meta-Strategy Solvers

In this section, we describe the algorithms used for the MSS step of PSRO, which computes a set of meta-strategies σ_i or a correlation device μ for the normal-form empirical game.

A.1 Joint-Space Meta-Strategy Solvers and Correlation Devices

A “correlation device”, $\mu \in \Delta(\Pi)$, is a distribution over the *joint* strategy space, which secretly recommends strategies to each player. Define $u_i(\pi'_i, \mu)$ to be the expected utility of i when it deviates to π'_i given that other players follow their recommendations from μ . Then, μ is **coarse-correlated equilibrium (CCE)** when no player i has an incentive to unilaterally deviate *before* receiving their recommendation: $u_i(\pi'_i, \mu) - u_i(\mu) \leq 0$ for all $i \in \mathcal{N}$, $\pi'_i \in \Pi_i$. Similarly, define $u_i(\pi'_i, \mu | \pi''_i)$ to be the expected utility of deviating to π'_i given that other players follow μ and player i has received recommendation π''_i from the correlation device. A **correlated equilibrium (CE)** is a correlation device μ where no player has an incentive to unilaterally deviate *after* receiving their recommendation: $u_i(\pi'_i, \mu | \pi''_i) - u_i(\mu | \pi''_i) \leq 0$ for all $i \in \mathcal{N}$, $\pi'_i \in \Pi_i$, $\pi''_i \in \Pi_i$.

A.2 Classic PSRO Meta-Strategy Solvers

Projected Replicator Dynamics (PRD) In the replicator dynamics, each player i used by mixed strategy σ_i^t , often interpreted as a distribution over population members using pure strategies. The continuous-time dynamic then describes a change in weight on strategy $\pi_k \in \Pi_i$ as a time derivative:

$$\frac{d\sigma_i^t(\pi_k)}{dt} = \sigma_i^t(\pi_k)[u_i(\pi_k, \sigma_{-i}) - u_i(\sigma)].$$

The projected variant ensures that the strategies stay within the exploratory simplex such σ_i^t remains a probability distribution, and that every elements is subject to a lower-bound $\frac{\gamma}{|\Pi_i|}$. In practice, this is simulated by small discrete steps in the direction of the time derivatives, and then projecting σ_i^t back to the nearest point in the exploratory simplex.

Exploratory Regret-Matching Regret-Matching is based on the algorithm described in [Hart and Mas-Colell, 2000] and used in extensive-form games for regret minimization [Zinkevich *et al.*, 2008]. Regret-matching is an iterative solver that tabulates cumulative regrets $R_i^T(\pi)$, which initially start at zero. At each trial t , player i would receive $u_i(\sigma_i^t, \sigma_{-i}^t)$ by playing their strategy σ_i^t . The instantaneous regret of *not* playing pure strategy $\pi_k \in \Pi_i$ is

$$r^t(\pi_k) = u_i(\pi_k, \sigma_{-i}^t) - u_i(\sigma_i^t, \sigma_{-i}^t).$$

The cumulative regret over T trials for the pure strategy is then defined to be:

$$R_i^T(\pi_k) = \sum_{t=1}^T r^t(\pi_k).$$

Define $(x)^+ = \max(0, x)$. The policy at time $t + 1$ is derived entirely by these regrets:

$$\sigma_{i, RM}^{t+1}(\pi_k) = \frac{R_i^{T,+}(\pi_k)}{\sum_{\pi'_k \in \Pi_i} R_i^{T,+}(\pi'_k)},$$

if the denominator is positive, or $\frac{1}{|\Pi_i|}$ otherwise. As in original PSRO, in this work we also add exploration:

$$\sigma_i^{t+1} = \gamma \text{UNIFORM}(\Pi_i) + (1 - \gamma) \sigma_{i, RM}^{t+1}.$$

Finally, the meta-strategy returned for all players at time t is their average strategy $\bar{\sigma}^T$.

A.3 Joint and Correlated Meta-Strategy Solvers

The jointly correlated meta-strategy solvers were introduced in [Marris *et al.*, 2021], which was the first to propose computing equilibria in the joint space of the empirical game. In general, a correlated equilibrium (and coarse-correlated equilibrium) can be found by satisfying a number of constraints, on the correlation device, so the question is what to use as the optimization criterion, which effectively selects the equilibrium.

One that maximizes Shannon entropy (ME(C)CE) seems like a good choice as it places maximal weight on all strategies, which could benefit PSRO due to added exploration among alternatives. However it was found to be slow on large games. Hence, Marris *et al.* [Marris *et al.*, 2021] propose to use a different but related measure, the Gini impurity, for correlation device μ ,

$$\text{GINIIMPURITY}(\mu) = 1 - \mu^T \mu,$$

which is a form of Tsallis entropy. The resulting equilibria Maximum Gini (Coarse) Correlated Equilibria (MG(C)CE) have linear constraints and can be computed by solving a quadratic program. Also, Gini impurity has similar properties to Shannon entropy: it is maximized at the uniform distribution and minimized when all the weight is placed on a single element.

In the Deal-or-no-Deal experiments, 4 of 5 selected winners of tournaments used MG(C)CE (see Section G.2, including the one that cooperated best with human players, and the other used uniform. Hence, it is possible that the exploration motivated my high-support meta-strategies indeed does help when playing against a population of agents, possibly benefiting the Bayesian inference implied by the generative model and resulting search.

Algorithm	Abbreviation	Independent/Joint	Solution Concepts	Description
α -Rank	—	Joint	MCC	[Omidshafiei <i>et al.</i> , 2019; Muller <i>et al.</i> , 2020]
ADIDAS	—	Independent	LLE/QRE	[Gemp <i>et al.</i> , 2021]
Max Entropy (C)CE	ME(C)CE	Joint	(C)CE	[Ortiz <i>et al.</i> , 2007]
Max Gini (C)CE	MG(C)CE	Joint	(C)CE	[Marris <i>et al.</i> , 2021]
Max NBS (C)CE	MN(C)CE	Joint	(C)CE	Sec B.1
Max Welfare (C)CE	MW(C)CE	Joint	(C)CE	[Marris <i>et al.</i> , 2021]
Nash Bargaining Solution (NBS)	NBS	Independent	P-E	Sec 4.2
NBS Joint	NBS_joint	Joint	P-E	Sec 4.2
Projected Replicator Dynamics	PRD	Independent	?	[Lanctot <i>et al.</i> , 2017; Muller <i>et al.</i> , 2020]
Regret Matching	RM	Independent	CCE	[Lanctot <i>et al.</i> , 2017]
Social Welfare	SW	Joint	MW	Sec B
Uniform	—	Independent	?	[Brown, 1951; Shoham and Leyton-Brown, 2009]

Table 2: Meta-strategy solvers. For each MSS, we indicate whether its output is over joint or individual strategy spaces, and the solution concept it captures. P-E stands for Pareto efficiency.

A.4 ADIDAS

Average Deviation Incentive with Adaptive Sampling (ADIDAS) [Gemp *et al.*, 2021] is an algorithm designed to approximate a particular Nash equilibrium concept called the *limiting logit equilibrium* (LLE). The LLE is unique in almost all N -player, general-sum, normal-form games and is defined via a homotopy [McKelvey and Palfrey, 1995]. Beginning with a quantal response (logit) equilibrium (QRE) under infinite temperature (known to be the uniform distribution), a continuum of QREs is then traced out by annealing the temperature. The LLE, aptly named, is the QRE defined in the limit of zero temperature. ADIDAS approximates this path in a way that avoids observing or storing the entire payoff tensor. Instead, it intelligently queries specific entries from the payoff tensor by leveraging techniques from stochastic optimization.

B New Meta-Strategy Solvers

Recall from Section 2 that a meta-strategy solver (MSS) selects a strategy profile from the current empirical game for use as best-response target. This target can take the form of either: (i) μ , a joint distribution over Π , or (ii) $(\sigma_1, \sigma_2, \dots, \sigma_N)$, a set of (independent) distributions over Π_i , respectively. These distributions (μ_{-i} or σ_{-i}) are used to sample opponents when player i is computing an approximate best response. We use many MSSs: several new and from previous work, summarized in App. A and Table 2. We present several new MSSs for general-sum games inspired by bargaining theory, which we now introduce.

B.1 Max-NBS (Coarse) Correlated Equilibria

The second new MSS we propose uses NBS to select a (C)CE. For all normal-form games, valid (C)CEs are a convex polytope of joint distributions in the simplex defined by the linear constraints. Therefore, maximizing any strictly concave function can uniquely select an equilibrium from this space (for example Maximum Entropy [Ortiz *et al.*, 2007], or Maximum Gini [Marris *et al.*, 2021]). The log Nash product (Equation (2)) is concave but not, in general, strictly concave. Therefore to perform unique equilibrium selection, a small additional strictly concave regularizer (such as maximum entropy) may be needed to select a uniform mixture over distributions with equal log Nash product. We use existing off-the-shelf exponential cone constraints solvers (e.g., ECOS [Domahidi *et al.*, 2013], SCS [O’Donoghue *et al.*, 2021]) which are available in simple frameworks (CVXPY [Diamond and Boyd, 2016; Agrawal *et al.*, 2018]) to solve this optimization problem.

NBS is a particularly interesting selection criterion. Consider the game of chicken in where players are driving head-on; each may continue (C), which may lead to a crash, or swerve (S), which may make them look cowardly. Many joint distributions in this game are valid (C)CE equilibria (Figure 5). The optimal outcome in terms of both welfare and fairness is to play SC and CS each 50% of the time. NBS selects this equilibrium. Similarly in Bach-or-Stravinsky where players coordinate but have different preferences over events: the fairest maximal social welfare outcome is a compromise, mixing equally between BB and SS.

B.2 Social Welfare

This MSS selects the pure joint strategy of the empirical game that maximizes the estimated social welfare.

C Nash Bargaining Solution of Normal-form games via Projected Gradient Ascent

In this section, we elaborate on the method proposed in Section 4.2. As an abuse of notation, let u_i denote the payoff tensor for player i flattened into a vector; similarly, let \mathbf{x} be a vector as well. Let d be the number of possible joint strategies, e.g., M^N for a game with N agents, each with M pure strategies. Let Δ^{d-1} denote the $(d-1)$ -simplex, i.e., $\sum_{k=1}^d \mathbf{x}_k = 1$ and $\mathbf{x}_k \geq 0$ for all $k \in \{1, \dots, d\}$. We first make an assumption.

Assumption C.1. Any agreement is better than no agreement by a positive constant κ , i.e.,

$$u_i^\top \mathbf{x} - d_i \geq \kappa > 0 \quad \forall i \in \{1, \dots, N\}, \mathbf{x} \in \Delta^{d-1}. \quad (4)$$




Figure 5: (C)CE polytopes in Chicken (left) and Bach-or-Stravinsky (right) showing NBS equilibrium selection.

Lemma C.2. *Given Assumption C.1, the negative log-Nash product, $f(\mathbf{x}) = -\sum_i \log(u_i^\top \mathbf{x} - d_i)$, is convex with respect to the joint distribution \mathbf{x} .*

Proof. We prove $f(\mathbf{x})$ is convex by showing its Hessian is positive semi-definite. First, we derive the gradient:

$$\nabla f(\mathbf{x}) = -\sum_i \frac{u_i}{u_i^\top \mathbf{x} - d_i}. \quad (5)$$

We then derive the Jacobian of the gradient to compute the Hessian. The kl -th entry of the Hessian is

$$H_{kl} = \sum_i \frac{u_{ik} u_{il}}{(u_i^\top \mathbf{x} - d_i)^2}. \quad (6)$$

We can write the full Hessian succinctly as

$$H = \sum_i \frac{u_i u_i^\top}{(u_i^\top \mathbf{x} - d_i)^2} = \sum_i \frac{u_i u_i^\top}{\gamma_i^2}. \quad (7)$$

Each outer product $u_i u_i^\top$ is positive semi-definite with eigenvalues $\|u_i\|^2$ (with multiplicity 1) and 0 (with multiplicity $M^N - 1$).

Each γ_i is positive by Assumption C.1, therefore, H , which is the weighted sum of $u_i u_i^\top$ is positive semi-definite as well. \square

We also know the following.

Lemma C.3. *Given Assumption C.1, the infinity norm of the gradients of the negative log-Nash product are bounded by $\frac{u^{\max} N}{\kappa}$ where $u^{\max} = \max_{i,k} [u_{ik}]$.*

Proof. As derived in Lemma C.2, the gradient of $f(\mathbf{x})$ is

$$\nabla f(\mathbf{x}) = -\sum_i \frac{u_i}{u_i^\top \mathbf{x} - d_i}. \quad (8)$$

Using triangle inequality, we can upper bound the infinity (max) norm of the gradient as

$$\|\nabla f(\mathbf{x})\|_\infty = \left\| \sum_i \frac{u_i}{u_i^\top \mathbf{x} - d_i} \right\|_\infty \quad (9)$$

$$\leq \sum_i \left\| \frac{u_i}{u_i^\top \mathbf{x} - d_i} \right\|_\infty \quad (10)$$

$$= \sum_i \frac{\|u_i\|_\infty}{\gamma_i} \quad (11)$$

$$\leq \frac{u^{\max} N}{\kappa} \quad (12)$$

where $u^{\max} = \max_{i,k} [u_{ik}]$. \square

Game	N	Type	Description From
Kuhn poker (2P)	2	2P Zero-sum	[Lockhart <i>et al.</i> , 2019]
Leduc poker (2P)	2	2P Zero-sum	[Lockhart <i>et al.</i> , 2019]
Liar's dice	2	2P Zero-sum	[Lockhart <i>et al.</i> , 2019]
Kuhn poker (3P)	3	NP Zero-sum	[Lockhart <i>et al.</i> , 2019]
Kuhn poker (4P)	4	NP Zero-sum	[Lockhart <i>et al.</i> , 2019]
Leduc poker (3P)	3	NP Zero-sum	[Lockhart <i>et al.</i> , 2019]
Trade Comm	2	Common-payoff	[Sokota <i>et al.</i> , 2021; Lanctot <i>et al.</i> , 2019]
Tiny Bridge (2P)	2	Common-payoff	[Sokota <i>et al.</i> , 2021; Lanctot <i>et al.</i> , 2019]
Battleship	2	General-sum	[Farina <i>et al.</i> , 2019]
Goofspiel (2P)	2	General-sum	[Lockhart <i>et al.</i> , 2019]
Goofspiel (3P)	3	General-sum	[Lockhart <i>et al.</i> , 2019]
Sheriff	2	General-Sum	[Farina <i>et al.</i> , 2019]

Table 3: Benchmark games. N is the number of players.

Theorem C.4. Let $\{\mathbf{x}^t\}$ be the sequence generated by Algorithm 4 with starting point $\mathbf{x}^0 = d^{-1}\mathbf{1}$ and step size sequence $\alpha^t = \frac{\sqrt{(d-1)/d}}{\|g'(\mathbf{x}^s)\|_2} (t+1)^{-1/2}$. Then, for all $t > 0$ one has

$$\max_{\mathbf{x} \in \Delta^{d-1}} g(\mathbf{x}) - \max_{0 \leq s \leq t} g(\mathbf{x}^s) \leq \frac{\sqrt{2B_\psi(\mathbf{x}^*, \mathbf{x}^0)} \|g'(\mathbf{x}^s)\|_2}{\sqrt{t+1}} \quad (13)$$

$$\leq \frac{\sqrt{\frac{d-1}{d}} \|g'(\mathbf{x}^s)\|_2}{\sqrt{t+1}} \quad (14)$$

$$\leq \frac{\sqrt{d} \|g'(\mathbf{x}^s)\|_\infty}{\sqrt{t+1}}. \quad (15)$$

where $g(x) = -f(x)$ is the log-Nash product defined in Sec 4.2.

Proof. Given Assumption C.1, $f(x)$ is convex (Lemma C.2) and its gradients are bounded in norm (Lemma C.3). We then apply Theorem 4.2 of [Beck and Teboulle, 2003] with $f(x) = -g(x)$, $\psi(\mathbf{x}) = \frac{1}{2}\|\mathbf{x}\|_2^2$ and note that $B_\psi(\mathbf{x}^*, \mathbf{x}^0) \leq \frac{1}{2}(d-1)/d$ to achieve the desired result. \square

Theorem C.5. Let $\{\mathbf{x}^t\}$ be the sequence generated by EMDA [Beck and Teboulle, 2003] with starting point $\mathbf{x}^0 = d^{-1}\mathbf{1}$ and step size sequence $\alpha^t = \frac{\sqrt{2 \log(d)}}{\|g'(\mathbf{x}^s)\|_\infty} (t+1)^{-1/2}$. Then, for all $t > 0$ one has

$$\max_{\mathbf{x} \in \mathcal{X}} g(\mathbf{x}) - \max_{0 \leq s \leq t} g(\mathbf{x}^s) \leq \frac{\sqrt{2 \log d} \|g'(\mathbf{x}^s)\|_\infty}{\sqrt{t+1}} \quad (16)$$

where $g(x) = -f(x)$ is the log-Nash product defined in Sec 4.2.

Proof. Given Assumption C.1, $f(x)$ is convex (Lemma C.2) and its gradients are bounded in norm (Lemma C.3). We then apply Theorem 5.1 of [Beck and Teboulle, 2003] with $f(x) = -g(x)$. \square

This argument concerns the regret of the joint version of the NBS where \mathbf{x} is a correlation device. However, it also makes sense to try compute a Nash bargaining solution where players use independent strategy profiles (without any possibility of correlation across players), $\sigma = (\sigma_1 \times \dots \times \sigma_N)$. In this case, \mathbf{x} represents a concatenation of the individual strategies σ_i and the projection back to the simplex is applied to each player separately. Ensuring convergence is trickier in this case, because the expected utility may not be a linear function of the parameters which may mean the function is nonconcave.

D Game Domain Descriptions and Details

This section contains descriptions of the benchmark games and a size estimate for Deal-or-no-Deal.

D.1 Benchmark Games

In this section, we describe the benchmark games used in this chapter. The game list is show in Table 3. As they have been used in several previous works, and are openly available, we simply copy the descriptions here citing the sources in the table.

Kuhn Poker Kuhn poker is a simplified poker game first proposed by Harold Kuhn. Each player antes a single chip, and gets a single private card from a totally-ordered $(n + 1)$ -card deck, e.g. J, Q, K for the $(n = 2)$ two-player case. There is a single betting round limited to one raise of 1 chip, and two actions: pass (check/fold) or bet (raise/call). If a player folds, they lose their commitment (2 if the player made a bet, otherwise 1). If no player folds, the player with the higher card wins the pot. The utility for each player is defined as the number of chips after playing minus the number of chips before playing.

Leduc Poker Leduc poker is significantly larger game with two rounds and a two suits with $(N + 1)$ cards each, e.g. JS, QS, KS, JH, QH, KH in the $(N = 2)$ two-player case. Like Kuhn, each player initially antes a single chip to play and obtains a single private card and there are three actions: fold, call, raise. There is a fixed bet amount of 2 chips in the first round and 4 chips in the second round, and a limit of two raises per round. After the first round, a single public card is revealed. A pair is the best hand, otherwise hands are ordered by their high card (suit is irrelevant). Utilities are defined similarly to Kuhn poker.

Liar's Dice Liar's Dice(1,1) is dice game where each player gets a single private die in $\{1, \dots, 6\}$, rolled at the beginning of the game. The players then take turns bidding on the outcomes of both dice, i.e. with bids of the form $q-f$ referring to quantity and face, or calling "Liar". The bids represent a claim that there are at least q dice with face value f among both players. The highest die value, 6, counts as a wild card matching any value. Calling "Liar" ends the game, then both players reveal their dice. If the last bid is not satisfied, then the player who called "Liar" wins. Otherwise, the other player wins. The winner receives +1 and loser -1.

Trade Comm Trade Comm is a common-payoff game about communication and trading of a hidden item. It proceeds as follows.

1. Each player is independently dealt one of num items with uniform chance.
2. Player 1 makes one of num utterances utterances, which is observed by player 2.
3. Player 2 makes one of num utterances utterances, which is observed by player 1.
4. Both players privately request one of the num items \times num items possible trades.

The trade is successful if and only if both player 1 asks to trade its item for player 2's item and player 2 asks to trade its item for player 1's item. Both players receive a reward of 1 if the trade is successful and 0 otherwise. We use num items = num utterances = 10.

Tiny Bridge A very small version of bridge, with 8 cards in total, created by Edward Lockhart, inspired by a research project at University of Alberta by Michael Bowling, Kate Davison, and Nathan Sturtevant.

This smaller game has two suits (hearts and spades), each with four cards (Jack, Queen, King, Ace). Each of the four players gets two cards each.

The game comprises a bidding phase, in which the players bid for the right to choose the trump suit (or for there not to be a trump suit), and perhaps also to bid a 'slam' contract which scores bonus points.

The play phase is not very interesting with only two tricks being played, so it is replaced with a perfect-information result, which is computed using minimax on a two-player perfect-information game representing the play phase.

The game comes in two varieties - the full four-player version, and a simplified two-player version in which one partnership does not make any bids in the auction phase.

Scoring is as follows, for the declaring partnership:

- +10 for making 1H/S/NT (+10 extra if overtrick)
- +30 for making 2H/S
- +35 for making 2NT
- -20 per undertrick

Doubling (only in the 4p game) multiplies all scores by 2. Redoubling by a further factor of 2.

An abstracted version of the game is supported, where the 28 possible hands are grouped into 12 buckets, using the following abstractions:

- When holding only one card in a suit, we consider J/Q/K equivalent
- We consider KQ and KJ in a single suit equivalent
- We consider AK and AQ in a single suit equivalent (but not AJ)

Battleship Sheriff is a general-sum variant of the classic game Battleship. Each player takes turns to secretly place a set of ships S (of varying sizes and value) on separate grids of size $H \times W$. After placement, players take turns firing at their opponent—ships which have been hit at all the tiles they lie on are considered destroyed. The game continues until either one player has lost all of their ships, or each player has completed r shots. At the end of the game, the payoff of each player is computed as the sum of the values of the opponent's ships that were destroyed, minus γ times the value of ships which they lost, where $\gamma \geq 1$ is called the loss multiplier of the game.

In this work we use $\gamma = 2$, $H = 2$, $W = 2$, and $r = 3$. The OpenSpiel game string is:

Hyperparameter Name	Values in DoND	Values in CT (PSRO w/ DQN BR)
AlphaZero training episodes num_eps	10^4	10^4
Network input representation	an infoset vector $\in \mathbb{R}^{309}$ implemented in [Lanctot <i>et al.</i> , 2019]	an infoset vector $\in \mathbb{R}^{463}$
Network size for policy & value nets	[256, 256] for the shared torso	[1024, 512, 256]
Network optimizer	SGD	SGD
UCT constant c_{uct}	20 for IR and IE, 40 for SW, 100 for NP	
Returned policy type	greedy towards v	argmax over learned q-net
# simulations in search	300	
Learning rate for policy & value net	2e-3 for IR and IE, 1e-3 for SW, 5e-4 for NP	1e-3
Delayed # episodes for replacing v, p, g	200	200
Replay buffer size $ D $	2^{16}	
Batch size	64	128
PSRO empirical game entries # simulation	200	2000
L2 coefficient in evaluator c_1	1e-3	
Network size for generator net	[300, 100] MLP	
Learning rate for generator net	1e-3	
L2 coefficient in generator net c_2	1e-3	
PSRO minimum pure-strategy mass lower bound	0.005	0.005

Table 4: Hyper-parameters.

```
battleship(board_width=2, board_height=2,
ship_sizes=[1;2], ship_values=[1.0;1.0],
num_shots=3, loss_multiplier=2.0)
```

Goofspiel Goofspiel or the Game of Pure Strategy, is a bidding card game where players are trying to obtain the most points. shuffled and set face-down. Each turn, the top point card is revealed, and players simultaneously play a bid card; the point card is given to the highest bidder or discarded if the bids are equal. In this implementation, we use a fixed deck of decreasing points. In this work, we an imperfect information variant where players are only told whether they have won or lost the bid, but not what the other player played. The utility is defined as the total value of the point cards achieved.

In this work we use $K = 4$ card decks. So, e.g. the OpenSpiel game string for the three-player game is:

```
goofspiel(imp_info=True, returns_type=total_points,
players=3, num_cards=4)
```

Sheriff Sheriff is a simplified version of the Sheriff of Nottingham board game. The game models the interaction of two players: the Smuggler—who is trying to smuggle illegal items in their cargo— and the Sheriff— who is trying to stop the Smuggler. At the beginning of the game, the Smuggler secretly loads his cargo with $n \in \{0, \dots, n_{max}\}$ illegal items. At the end of the game, the Sheriff decides whether to inspect the cargo. If the Sheriff chooses to inspect the cargo and finds illegal goods, the Smuggler must pay a fine worth $p \cdot n$ to the Sheriff. On the other hand, the Sheriff has to compensate the Smuggler with a utility if no illegal goods are found. Finally, if the Sheriff decides not to inspect the cargo, the Smuggler’s utility is $v \cdot n$ whereas the Sheriff’s utility is 0. The game is made interesting by two additional elements (which are also present in the board game): bribery and bargaining. After the Smuggler has loaded the cargo and before the Sheriff chooses whether or not to inspect, they engage in r rounds of bargaining. At each round $i = 1, \dots, r$, the Smuggler tries to tempt the Sheriff into not inspecting the cargo by proposing a bribe $b_i \in \{0, \dots, b_{max}\}$, and the Sheriff responds whether or not they would accept the proposed bribe. Only the proposal and response from round r will be executed and have an impact on the final payoffs—that is, all but the r^{th} round of bargaining are non-consequential and their purpose is for the two players to settle on a suitable bribe amount. If the Sheriff accepts bribe b_r , then the Smuggler gets $p \cdot n - b_r$, while the Sheriff gets b_r .

In this work we use values of $n_{max} = 10$, $b_{max} = 2$, $p = 1$, $v = 5$, and $r = 2$. The OpenSpiel game string is:

```
sheriff(item_penalty=1.0, item_value=5.0,
max_bribe=2, max_items=2, num_rounds=2,
sheriff_penalty=1.0)
```

D.2 Approximate Size of Deal or No Deal

To estimate the size of Deal or No Deal described in Section 5.1, we first verified that there are 142 unique preference vectors per player. Then, we generated 10,000 simulations of trajectories using uniform random policy computing the average branching factor (number of legal actions per player at each state) as $b \approx 23.5$.

Since there are 142 different information states for player 1’s first decision, about 142*bb* player 1’s second decision, etc. leading to $142(1 + b^2 + b^4 + b^8) \approx 13.2 \times 10^{12}$ information states. Similarly, player 2 has roughly $142(1 + b^1 + b^3 + b^5 + b^7) = 5.63 \times 10^{11}$ information states.

E Hyper-parameters and Algorithm Settings

We provide detailed description of our algorithm in this section. Our implementation differs from the original ABR [Timbers *et al.*, 2022] and AlphaZero [Silver *et al.*, 2018] in a few places. First, instead of using the whole trajectory as a unit of data for

training, we use per-state pair data. We maintain separate data buffers for policy net, value net, and generate net, and collect corresponding (s_i, r) , (s_i, p) , (s_i, h) to them respectively. On each gradient step we will sample a batch from each of these data buffer respectively. The policy net and value net shared a torso part, while we keep a separate generative net (detailed in Section E.1). The policy net and value net are trained by minimizing loss $(r - v)^2 - \pi^{*T} \log p + c_1 \|\theta\|_2^2$, where (1) π^* are the policy targets output by the MCTS search, (2) p are the output by the policy net, (3) v are the output by the value net, (4) r are the outcome value for the trajectories (5) θ are the neural parameters. During selection phase the algorithm select the child that maximize the following PUCT [Silver *et al.*, 2018] term: $\text{MaxPUCT}(s, \mathbf{p}) = \arg \max_{a \in \mathcal{A}(s)} \frac{s.\text{child}(a).\text{value}}{s.\text{child}(a).\text{visits}} + c_{uct_c} \cdot \mathbf{p}(s)_a \cdot \frac{\sqrt{s.\text{total.visits}}}{s.\text{child}(a).\text{visits}+1}$. Other hyperparameters are listed in Table 4.

E.1 Generative Models

Deal or No Deal In DoND given an information state, the thing we only need to learn is the opponent’s hidden utilities. And since the utilities are integers from 0 to 10, we design our generative model as a supervised classification task. Specifically, we use the 309-dimensional state s_i as input and output three heads. Each head corresponds to one item of the game. each head consists of 11 logits corresponding to each of 11 different utility values. Then each gradient step we sample a batch of (s_i, h) from the data buffer. And then do one step of gradient descent to minimize the cross-entropy loss $-h^T \log \mathbf{g}(s) + c_2 \|\theta'\|_2^2$, where here we overload h to represent a one-hot encoding of the actual opponent utility vectors. And each time we need to generate a new state at information state s_i , we just feed forward s_i and sample the utilities according to the output logits. But since we have a constraints $\mathbf{v}_1 \cdot \mathbf{p} = \mathbf{v}_2 \cdot \mathbf{p} = 10$, the sampled utilities may not always be feasible under this constraint. Then we will do an additional L2 projection on to all feasible utility vector space and then get the final results.

F Extracting a Final Agent at Test Time

How can a single decision-making agent be extracted from Π ? The naive method samples $\pi_i \sim \sigma_i$ at the start of each episode, then follows σ_i for the episode. The **self-posterior** method *resamples* a new oracle $\pi_i \in \Pi_i^T$ at information states each time an action or decision is requested at s . At information state s , the agent samples an oracle π_i from the posterior over its own oracles: $\pi_i \sim \Pr(\pi_i | s, \sigma_i)$, using reach probabilities of its own actions along the information states leading to s where i acted, and then follows π_i . The self-posterior method is based on the equivalent behavior strategy distribution that Kuhn’s theorem [Kuhn, 1953] derives from the mixed strategy distribution over policies. The **aggregate policy** method takes this a step further and computes the average (expected self-posterior) policy played at each information state, $\bar{\pi}_i^T(s)$, exactly (rather than via samples); it is described in detail in [Lanctot *et al.*, 2017, Section E.3]. The **rational planning** method enables decision-time search instantiated with the final oracles: it assumes the opponents at test time exactly match the σ_{-i} of training time, and keeps updating the posterior $\Pr(h, \pi_{-i} | s, \sigma_{-i})$ during an online play. Whenever it needs to take an action at state s at test time, it employs Algorithm 2 to search against this posterior. This method combines online Bayesian opponent modeling and search-based best response, which resembles the rational learning process [Kalai and Lehrer, 1993].

G Additional Results

G.1 Overview of Approximate Nash equilibrium solving using PSRO

Here we evaluate the capacity of PSRO with different meta-strategy solvers² to act as a general Nash equilibrium solver for sequential N -player games. For these initial experiments, we run PSRO on its own without search. Since these are benchmark games, they are small enough to compute exact exploitability, or the Nash gap (called NASHCONV by [Lanctot *et al.*, 2017; Lanctot *et al.*, 2019]), and search is not necessary. We run PSRO using 16 different meta-strategy solvers across 12 different benchmark games (three 2P zero-sum games, three N -player zero-sum games, two common-payoff games, and four general-sum games): instances of Kuhn and Leduc poker, Liar’s dice, Trade Comm, Tiny Bridge, Battleship, Goofspiel, and Sheriff. These games have recurred throughout previous work, so we describe them in App. D; they are all partially-observable and span a range of different types of games.

A representative sample of the results is shown in Figure 6, whereas all the results are shown below. $\text{NASHCONV}(\bar{\pi}) = \sum_{i \in \mathcal{N}} u_i(b_i(\bar{\pi}_{-i}), \bar{\pi}_{-i}) - u_i(\bar{\pi})$, where b_i is an exact best response, and $\bar{\pi}$ is the exact average policy using the aggregator method described in Section F. A value of zero means $\bar{\pi}$ is Nash equilibrium, and values greater than zero correspond to an gap from Nash equilibrium. Social welfare is defined as $\text{SW}(\bar{\pi}) = \sum_i u_i(\bar{\pi})$.

Most of the meta-strategy solvers seem to reduce NASHCONV faster than a completely uninformed meta-strategy solver (uniform) corresponding to fictitious play, validating the EGTA approach taken in PSRO. In three-player (3P) Leduc, the NashConv achieved for the exact best response is an order of magnitude smaller than when using DQN. ADIDAS, regret-matching, and PRD are a good default choice of MSS in competitive games. The correlated equilibrium meta-strategy solvers are surprisingly good at reducing NASHCONV in the competitive setting, but can become unstable and even fail when the

²For simplicity we use the same MSS for both guiding the BR step (strategy exploration) and evaluating NASHCONV at each iteration. Firmer conclusions about relative effectiveness for strategy exploration would require defining a fixed solver for evaluation purposes [Wang *et al.*, 2021].




Figure 6: NASHCONV and social welfare along PSRO iterations across game types. NASHCONV in 3P Leduc poker using (a) DQN oracles vs. (d) exact oracles. NASHCONV (b) and (e) social welfare in Sheriff. NASHCONV (c) and social welfare (f) in 2P Tiny Bridge.

empirical game becomes large in the exact case. In the general-sum game Sheriff, the reduction of NASHCONV is noisy, with several of the meta-strategy solvers having erratic graphs, with RM and PRD performing best. Also in Sheriff, the Nash bargaining (and social welfare) meta-strategy solvers achieve significantly higher social welfare than most meta-strategy solvers. Similarly in the cooperative game of Tiny Bridge, the MSSs that reach closest to optimal are NBS (independent and joint), social welfare, RM, PRD, and Max-NBS-(C)CE. Many of these meta-strategy solvers are not *guaranteed* to compute an approximate Nash equilibrium (even in the empirical game), but any limiting logit equilibrium (QRE) solver can get arbitrarily close. ADIDAS does not require the storage of the meta-tensor U^t , only samples from it. So, as the number of iterations grow ADIDAS might be one of the safest and most memory-efficient choice for reducing NASHCONV long-term.

The full analysis of empirical convergence to approximate Nash equilibrium and social welfare are shown for various settings:

- Two-player Zero-Sum Games: Figure 7.
- N -player Zero-Sum Games: Figure 8.
- Common Payoff Games: Figure 9.
- General-Sum Games: Figure 10.

Full Results

The full Pareto gap graphs as a function of training time is shown in Figure 11. Some examples of the evolution of expected outcomes over the course of PSRO training are shown in Figure 12.

G.2 Deal or No Deal

In this section, we described how we train and select the agents in DoND human behavioral studies.

For DQN and Boltzmann DQN, we used replay buffer sizes of 10^5 , ϵ decayed from $0.9 \rightarrow 0.1$ over 10^6 steps, a batch size of 128, and swept over learning rates of $\{0.01, 0.02, 0.005\}$. For Boltzmann DQN, we varied the temperature $\eta \in \{0.25, 0.5, 1\}$. For all self-play policy gradient methods we used a batch size of 128, and swept over critic learning rate in $\{0.01, 0.001\}$, policy learning rate in $\{.001, 0.0005, 0.0001\}$, number of updates to the critic before updating the policy in $\{1, 4, 8\}$, and entropy cost in $\{0.01, 0.001\}$. DQN trained with the settings above and a learning rate of 0.005 was the agent we found to achieve highest individual returns (and social welfare, and Nash bargaining score), so we select it as the representative agent for the independent RL category.

Due the experimental limitation, we can only select 5 of our agents to human experiments. For convenience from now on we label a PSRO agent as $(MSS, BACKPROP_TYPE, FINAL_TYPE)$ if it is trained under meta-strategy solver MSS , its back-propagation type is $BACKPROP_TYPE$ and we use $FINAL_TYPE$ as its decision architecture. We apply standard empirical game theoretic analysis [Wellman *et al.*, 2025] on our agent pool: we create a 113×113 symmetric empirical game by simulating head to head results between every pair of our agents. During each simulation we toss a coin to assign the roles (first-mover or second-mover in DoND) to our agents. Then we decide the selected agents based on this empirical game matrix.




Figure 7: Empirical Convergence to Nash Equilibria using Exact vs. DQN Best Response versus in Two-Player Zero-Sum Benchmark Games.




Figure 8: Empirical Convergence to Nash Equilibria using Exact vs. DQN Best Response in N -Player Zero-Sum Benchmark Games.

Specifically, we want to select: (1) the most competitive agents (2) the most collaborative agents and (3) the fairest agent in our pool in a principled way. Now we explain how we approach these criteria one by one.

For (1), we apply our competitive MSSs (e.g., ADIDAS, CE/CCE solvers) on this empirical game matrix and solve for a symmetric equilibrium. Then we rank the agents according to their expected payoff when the opponents are playing according to this equilibrium. This approach is inspired by Nash-response ranking in [Jordan *et al.*, 2007] and Nash averaging in [Balduzzi *et al.*, 2018] which is recently generalized to any N -player general-sum games [Marris *et al.*, 2022]. We found that Independent DQN, (MGCE, IA, SP) (denoted as Comp1), (MGCCE, IR, SP) (denoted as Comp2) rank at the top under almost all competitive MSS.

For (2), we create two collaborative games where the payoffs of agent1 v.s. agent2 are their social welfare/Nash product. We conduct the same analysis as in (1), and found the agent (uniform, NP, RP) normally ranks the first (thus we label it as Coop agent).

For (3), we create an empirical game where the payoffs of agent1 v.s. agent2 are the negative of their absolute payoff difference, and apply the same analysis. We also conduct a Borda voting scheme: we rank the agent pairs in increasing order of their absolute payoff difference. Each of these agent pairs will get a Borda voting score. Then the score of an agent is the summation of the scores of agents pairs that this agent is involved in. In both approaches, we find the agent (MGCE, NP, RP) ranks the top. Therefore we label it as Fair agent.

To summary, the five agents we finally decided to conduct human experiments are (1) DQN trained through self-play (IndRL)

Agent \ Opponent	IndRL	Com1	Com2	Coop	Fair
IndRL	4.85	4.98	5.02	7.05	6.96
Com1	3.75	4.97	4.66	7.19	6.70
Com2	3.20	5.30	5.04	6.84	6.86
Coop	5.63	4.43	4.32	6.67	6.64
Fair	5.47	4.43	4.19	6.59	6.52

Table 5: Head-to-head empirical game matrix among our selected agents . The (i, j) -th entry is the payoff of the i -th agent when it is playing with the j -th agent.

Agent \ Opponent	IndRL	Com1	Com2	Coop	Fair
IndRL	9.70	8.73	8.22	12.68	12.42
Com1	8.73	9.94	9.96	11.62	11.12
Com2	8.22	9.96	10.09	11.16	11.05
Coop	12.68	11.62	11.16	13.34	13.22
Fair	12.42	11.12	11.05	13.22	13.05

Table 6: Head-to-head empirical social welfare matrix among our selected agents . The (i, j) -th entry is the social welfare of when i -th agent is playing with the j -th agent.

(2) (MGCE, IA, SP) (Comp1) (3) (MGCCE, IR, SP) (Comp2) (4) (uniform, NP, RP) (Coop) (5) (MGCE, NP, RP) (Fair).

We show the head-to-head empirical game between these five agents in Table 5, social-welfare in Table 6, empirical Nash product in Table 7.

H Human Behavioral Studies

H.1 Study Design

The protocol for the human behavioral studies underwent independent ethical review and received a favorable opinion from the Human Behavioural Research Ethics Committee at DeepMind (#19/004). All participants provided informed consent before joining the study.

We collected data through “tournaments” of Deal or No Deal games in two different conditions: Human vs. Human (HvH) and Human vs. Agent (HvA). Upon joining the study, participants were randomly assigned to one of the two conditions. Participants in both conditions proceeded through the following sequence of steps:

1. Read study instructions and gameplay tutorial (Figures 13–17).
2. Take comprehension test (Figures 18 & 19).
3. Wait for random assignment to a tournament with five other participants (HvH) or wait for agents to load for a tournament (HvA; Figure 20).
4. Play episode of Deal or No Deal game (Figure 21).
5. See score confirmation for last episode and wait for next episode (Figure 22a).
6. Repeat steps 4 and 5 for four additional episodes.
7. Note total earnings and transition to post-game questionnaire (Figure 22b).

We required participants to answer all four questions in the comprehension test correctly to continue to the rest of the study. The majority of participants (71.4%) passed the test and were randomly sorted into tournaments in groups of $n = 6$ (for the HvH condition) or $n = 1$ (for the HvA condition). We provided the remainder a show-up payment for the time they spent on the study tutorial and test.

The participants played DoND for real monetary stakes, receiving an additional \$0.10 of bonus for each point they earned in the study. To ensure that one non-responsive participant did not disrupt the study for any other participants in their tournament, episodes had a strict time limit of 120 seconds. After the time limit for a given episode elapsed, all uncompleted games were marked as “timed out” and any participants in the tournament were moved to the next step of the study.

We apply two exclusion criteria to build our final datasets of game episodes: first, exclude all episodes that timed out before reaching a deal or exhausting all turns; and second, exclude all episodes involving a participant who was non-responsive during the tournament (i.e., did not take a single action in a episode).

In the HvH condition, 228 participants passed the comprehension test and were sorted into tournaments. Eleven participants were non-responsive and an additional 6.3% of games timed out before reaching a deal or exhausting all turns, resulting in a final sample of $N = 217$ participants (39.5% female, 59.1% male, 0.9% trans or nonbinary; median age range: 30–40).

Agent \ Opponent	IndRL	Com1	Com2	Coop	Fair
IndRL	23.48	18.69	16.05	39.66	38.02
Com1	18.69	24.70	24.68	31.84	29.63
Com2	16.05	24.68	25.44	29.57	28.73
Coop	39.66	31.84	29.57	44.51	43.70
Fair	38.02	29.63	28.74	43.70	42.56

Table 7: Head-to-head empirical Nash product matrix among our selected agents . The (i, j) -th entry is the Nash product when i -th agent is playing with the j -th agent.

In HvH tournaments, each participant plays one episode against each of the five other participants in their group. We use a round-robin structure to efficiently match participants for each episode, ensuring each game involves two participants who have not interacted before. We randomize player order in each game. The final HvH dataset contains $k = 483$ games.

In the HvA condition, 130 participants passed the comprehension test and were sorted into tournaments. One participant was non-responsive and an additional 15.2% of games timed out before reaching a deal or exhausting all turns, resulting in a final sample of $N = 129$ participants (44.5% female, 53.1% male, 0.8% trans or nonbinary; median age range: 30–40).

In HvA tournaments, each participant plays one episode against each of the five agents evaluated in the study. We randomize agent order in each tournament and player order in each game. The final HvA dataset contains $k = 547$ games.

During each episode of the HvA tournaments, agent players waited a random amount of time after participant actions to send their own actions. The agents randomly sampled their time delays from a normal distribution with a mean of 10 seconds and a standard deviation of 3 seconds.

After completing all episodes in their tournament, participants proceeded to complete a post-task questionnaire that included the slider measure of Social Value Orientation [Murphy *et al.*, 2011], demographic questions, and open-ended questions soliciting feedback on the study.

Participants completed the study in an average of 18.2 minutes. The base pay for the study was \$2.50, with an average performance bonus of \$3.70.

H.2 Analysis

We fit linear mixed- and random-effects models to estimate and compare the average returns generated by our agents and by study participants.

We first fit a linear mixed-effects model using just the HvA data, predicting human return from each episode with one fixed effect (a categorical variable representing each type of agent playing in the episode) and one random effect (representing each participant in the HvA condition). The effect estimates (the mean points earned by a human player against each agent) are shown in the \bar{u}_{Humans} column of Table 1. We estimate 95% confidence intervals for the individual effects through bootstrapping with 500 resamples.

We next fit a linear mixed-effects model using just the HvA data, predicting agent return from each episode with one fixed effect (a categorical variable representing each type of agent playing in the episode) and one random effect (representing each participant in the HvA condition). The effect estimates (the mean points earned by each agent) are shown in the \bar{u}_{Agent} column of Table 1. We estimate 95% confidence intervals for the individual effects through bootstrapping with 500 resamples.

We similarly fit a linear mixed-effects model using just the HvA data, predicting social welfare (average return) from each episode with one fixed effect (a categorical variable representing each type of agent playing in the episode) and one random effect (representing each participant in the HvA condition). The effect estimates (the mean social welfare catalyzed by each agent) are shown in the \bar{u}_{Comb} column of Table 1. We estimate 95% confidence intervals for the individual effects through bootstrapping with 500 resamples.

We then fit a linear random-effects model using just the HvH data, predicting the return for one player (randomly selected) in each episode with one random effect (representing each participant in the HvH condition). Participants in the HvH condition achieve an individual return of 6.93 [6.72, 7.14], on expectation. We estimate the 95% confidence interval for this effect through bootstrapping with 500 resamples.




Figure 9: Empirical Convergence to Nash Equilibria and Social Welfare in Common Payoff Benchmark Games.







Figure 10: Empirical Convergence to Nash Equilibria and Social Welfare in General-Sum Benchmark Games.




(a)



(b)



(c)



(d)

Figure 11: Average Pareto gap using DQN best response (top: (a) and (b)) and Boltzmann DQN (bottom: (c) and (d)), training gap (left: (a) and (c)) and gap on held-out test boards (right: (b) and (d)).






Figure 12: Evolution of the expected outcomes of the PSRO agents using the DQN best response type and social welfare MSS. Each diagram depicts the outcome of the agent for a single configuration of Colored Trails: circles represent the rational outcomes (pure joint strategies where players have non-negative gain). The outer surface of the convex hull represents the Pareto front/envelope. To make a 2D image, the proposers' gains are aggregated and only the winning proposer's value is included in the outcome computation. The blue directed path represents the PSRO agents' expected outcomes at iterations $t \in \{0, 1, \dots, 15\}$, where each point estimated from 100 samples. Note that values can be negative due to sampling approximation but also due to choosing legal actions that result in negative gain.




(a) Screen 1: Welcome participants to the experiment.




(b) Screen 2: Explain study length and player matching.

Figure 13: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant reads general study information. (b) The participant reads tutorial information about the game.




(a) Screen 3: Explain items.




(b) Screen 4: Explain the goal of item distribution.

Figure 14: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant reads tutorial information about the game. (b) The participant reads tutorial information about the game.



(a) Screen 5: Explain points.



(b) Screen 6: Explain other player’s points.




Figure 15: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant reads tutorial information about the game. (b) The participant reads tutorial information about the game.

Tutorial (6/8)

You will negotiate with each other on a deal by sending proposals. You will take turns sending proposals.

When it is your turn, you can enter a proposal and share it by pressing "Share proposal". If you agree on a deal the other player has proposed, you can press "Confirm deal" and it will succeed. Likewise, if the other player agrees on a deal you have proposed, they can confirm the deal and it will succeed.

You and the other player will have 10 turns to agree to a deal (5 turns each).

Items available to divide:	Points you earn for this item:	Proposed deal (items you would get):
	0	<input type="text" value="0"/>
	1	<input type="text" value="1"/>
	2	<input type="text" value="1"/>

[BACK](#)




NEXT

(a) Screen 7: Explain actions.

Tutorial (7/8)


On the right side of the page, you will see the history of the deals you and the other player have proposed. The most recent proposal will appear outlined at the bottom.

You can see an example history with a single proposal below.

Items available to divide:	Points you earn for this item:	Proposed deal (items you would get):
	0	<input type="text" value="0"/>
	1	<input type="text" value="1"/>
	2	<input type="text" value="1"/>


BACK

NEXT




(b) Screen 8: Explain communication.

Figure 16: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant reads tutorial information about the game. (b) The participant reads tutorial information about the game.



(a) Screen 9: Explain episode length.



(b) Screen 10: Introduce comprehension test.

Figure 17: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant reads tutorial information about the game. (b) The participant reads information about the comprehension test.

Test (1/4)

You will play 5 rounds of the game. Who will you play each round of the game with?

☐ I'll be randomly matched with a player each round

☐ I'll play with the same player each round

NEXT

(a) Screen 11: Test on player matching.

Test (2/4)

Do you and the other player have to split the items?

☐ Yes, each item must go either to me or to the other player

☐ No, we can share items

NEXT

(b) Screen 12: Test on item distribution.

Figure 18: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant takes the comprehension test. (b) The participant takes the comprehension test.

Test (3/4)

Do you and the other player earn the same amount of points whenever you successfully make a deal?

☐ Yes, we earn the same points for each deal

☐ No, we do not earn the same amount of points for each deal

NEXT

(a) Screen 13: Test on general-sum nature of game.

Test (4/4)

When does a deal succeed?

☐ When the timer for the round runs out

☐ When I accept the other player's proposal or they accept my proposal

☐ When the other player and I run out of turns

NEXT

(b) Screen 14: Test on conditions for deal success.

Figure 19: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant takes the comprehension test. (b) The participant takes the comprehension test.






Figure 20: Screenshots of the participant interface for the “Deal or No Deal” study. The participant sees their results for the comprehension test. If they answered all four questions correctly, the participant waits to be randomly assigned to a game session.




(a) Game screen: Prompt participant to take their turn.




(b) Game screen: Wait for other player to take their turn.

Figure 21: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant proposes a deal to the other player. (b) The other player chooses to confirm the deal or proposes a new deal.



(a) Game feedback screen: Show results from prior episode.



(b) Study feedback screen: Show bonus and introduce post-task questionnaire.

Figure 22: Screenshots of the participant interface for the “Deal or No Deal” study. (a) The participant waits for the next game to start. (b) The participant sees their bonus and waits to begin the post-task questionnaire.