



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
 Contact Factory (modshop@hammfg.com) for quotes
 Solid models of this enclosure available in .stp or .x_t
 (Part number and text placement/orientation on our products are subject to change,
 we do not recommend using them as a locating reference for modification purposes)

| NOTE | |
|--|--|
| Purchased assembly includes box, lid and 4 cover screws. | |
| Box and lid are made from Diecast Aluminum Alloy. | |
| EVA Gasket supplied with liquid resistant enclosure. | |
| Recommended Cover screw torque: 71-78 ozf.in / 50-55 cN.m | |
| Recommended Cover screw torque with gasket: 50-56 ozf.in / 35-40 cN.m | |

| PART NUMBERS | |
|--|--------------|
| 1550P Enclosure | |
| Natural Finish Enclosure | 1550B |
| Black Textured Enclosure | 1550BBK |
| 1550P Liquid Resistant Enclosure (Silicone Gasket) | |
| Natural Finish Enclosure | 1550WB |
| Black Textured Enclosure | 1550WBBK |
| ACCESSORIES | |
| Plated Cover Screws (Pkg 100) [M3.5-0.6 x 12mm] | 1550MS100 |
| Black Cover Screws (Pkg 100) [M3.5-0.6 x 12mm] | 1550MS100BK |
| Stainless Steel Cover Screws (Pkg 100) [M3.5 x 12mm, With O-Ring] | 1550WMS100 |
| Black Stainless Steel Cover Screws (Pkg 100) [M3.5 x 12mm, With O-Ring] | 1550WMS100BK |
| EVA Pre-formed Gasket Black | 1550BEGASKET |
| Silicone Pre-formed Gasket Black | 1550BSGASKET |

HAMMOND
 1550B
www.hammondmfg.com

Dimensions:
 mm
 [inches]