

ViBES: A Conversational Agent with Behaviorally-Intelligent 3D Virtual Body

Juze Zhang¹ Changan Chen¹ Xin Chen² Heng Yu¹ Tiange Xiang¹ Ali Sartaz Khan¹
 Shrinidhi K. Lakshmikanth¹ Ehsan Adeli¹
¹Stanford University ²ByteDance




Figure 1. We present a novel speech–language–behavior (SLB) model with a mixture–of–modality–experts (MoME) architecture that ingests audio, motion, or text and shares cross-modal information via speech–language–behavior Attention (SLB-Attn). Along with a 1,000-hour conversational behavior corpus that we curate, the model advances toward endowing AI agents with a unified 3D virtual body.

Abstract

Human communication is inherently multimodal and social: words, prosody, and body language jointly carry intent. Yet most prior systems model human behavior as a translation task—co-speech gesture or text-to-motion that maps a fixed utterance to motion clips—without requiring agentic decision-making about when to move, what to do, or how to adapt across multi-turn dialogue. This leads to brittle timing, weak social grounding, and fragmented stacks where speech, text, and motion are trained or inferred in isolation. We introduce **ViBES** (Voice in Behavioral Expression and Synchrony), a conversational 3D agent that jointly plans language and movement and executes dialogue-conditioned body actions. Concretely, ViBES is a speech–language–behavior (SLB) model with a mixture–of–modality–experts (MoME) backbone: modality-partitioned transformer experts for speech, facial expression, and body motion. The model processes interleaved multimodal token streams with hard routing by modality (parameters are split per expert), while sharing information through cross-expert attention. By leveraging strong pretrained speech-language models, the agent supports mixed-initiative interaction: users can speak, type, or issue body-action directives mid-conversation, and the system exposes controllable

behavior hooks for streaming responses. We further benchmark on multi-turn conversation with automatic metrics of dialogue–motion alignment and behavior quality, and observe consistent gains over strong co-speech and text-to-motion baselines. ViBES goes beyond “speech-conditioned motion generation” toward agentic virtual bodies where language, prosody, and movement are jointly generated, enabling controllable, socially competent 3D interaction. Code and data will be made available at: ai.stanford.edu/~juze/ViBES/

1. Introduction

Nowadays, chatbots can converse fluently, imitate voices, and perform surprising zero- and few-shot generalization across a wide range of tasks [1, 8, 17, 44, 51, 63, 93, 94, 110]. These capabilities have pushed the community toward a vision of agentic AI—systems that do more than respond: they plan, take initiative, and orchestrate tools over time [86]. While exciting, these powerful “digital brains” typically remain confined to text [1, 8, 63, 93, 94, 102] and audio [44]. On the other hand, human communication is not limited to voice and text – we also use our facial expression and body gesture to communicate with others. Empowering the agent with a body that can act like humans is thus

of vital importance. This also has important applications in robotics [5, 7, 22, 73, 123, 152] where robots need to communicate and react to humans in a human-like way.

A lot of recent work has focused on building conversational agents with either text or audio modality [6, 20, 24–26, 30, 42, 125, 135, 137–139, 141, 148] by training on thousands of hours of audio-text data to produce high-quality conversation abilities. Concurrently, there are two other lines of work that attempt to build conversational agents with a focus on motion: co-speech gesture generation [10, 11, 39, 64, 66, 67, 83, 128, 131] and text-to-motion [14, 35–37, 45, 62, 75, 75, 111, 112, 140, 146]. Both largely frame behavior as modality translation (e.g., audio/text to motion sequences via diffusion [14, 111] or Transformer models [45, 117] on SMPL [74, 87, 99] or human skeletons [35]), optimizing rhythmic entrainment and kinematics. While these methods can render human motion following some conditioning signals, they do not require behavior intelligence or agentic decision-making when the input prompt requires reasoning. How can we build a model that interfaces multi-modalities, reasons, and also generates human-like behaviors?

A seemingly promising workaround is to bolt a speech LLM onto a motion generator [11, 47]. In practice, this intuitive two-stage approach struggles: there is no unified policy over timing and selection, no shared conversational state, and thus no guarantee of cross-turn consistency or safety. The most relevant recent work, LoM [11] and SO-LAMI [47], primarily align speech with body motion under limited data; they emphasize modality alignment rather than preserving conversational intelligence. A true 3D conversational agent should not only produce co-speech gestures while answering, but also follow explicit action instructions (e.g., “Could you step back and wave?”)—capabilities existing systems do not currently have.

To address this issue, we present ViBES, a speech-language-behavior (SLB) model with a mixture-of-modality-experts (MoME) architecture that ingests audio, motion, or text and shares cross-modal information via speech-language-behavior attention (SLB-Attn) (Fig. 1). We utilize a strong pretrained audio-text backbone and interleave the newly added modality through an audio-text-motion pathway within a global cross-attention layer that operates over an interleaved token stream. Crucially, our approach does not require large-scale audio-text-motion pretraining. Instead, we leverage the pretrained capacity of speech LLMs [135] and attach a lightweight per-layer modality expert—a small Transformer block that produces face and body queries and reads the backbone’s key/value via cross-attention. Because these experts are side-car modules, the backbone’s architecture and weights remain intact, allowing us to utilize off-the-shelf checkpoints while adding new modalities with mini-

mal overhead. The design is “sparse” in that cross-modal interaction is restricted to attention reads (no heavy feature concatenation or write-back), and it scales by duplicating the expert across layers without retraining the language/speech core.

Training this model requires large-scale, time-aligned audio-text-motion datasets. However, today’s datasets are limited [35, 67, 79, 80]: we typically have only pairwise alignments (text-to-motion, audio-to-motion) rather than large-scale, time-synchronized audio-text-motion supervision. To overcome the data bottleneck, we curate a 1,000-hour dataset from complementary sources: in-the-wild YouTube conversation videos and existing motion datasets [35, 67, 79, 97, 105]. The YouTube portion spans interviews, podcasts, talks, and casual dialogues. For each video, we automatically recover monocular 3D human motion—body and hands when visible—and facial expressions using a single-view pipeline, then temporally align these signals with the speech and transcripts. The resulting corpus provides dense, time-synchronized audio-text-motion triplets, enabling, for the first time at this scale, large-scale training of a conversational agent’s body alongside its language and speech.

To evaluate our trained model, we introduce a new benchmark that jointly assesses dialogue understanding, social appropriateness, and motion quality, leveraging multi-modal LLM judges [44] together with task-specific metrics to cover the full spectrum of conversational behavior. We compare ViBES against a strong state-of-the-art system and several baselines and show that it outperforms prior methods across all metrics. We further evaluate on co-speech gesture generation and text-to-speech benchmarks [35, 67], where ViBES also achieves state-of-the-art results.

In summary, we present a unified sparse multi-modal model that integrates an unfrozen motion stack with a pretrained audio-text backbone via latent cross-attention, enabling dialogue-conditioned motion while preserving linguistic and prosodic intelligence. We also introduce a large-scale dataset of over 1,000 hours of synchronized audio-text-motion interactions and a benchmark suite evaluating dialogue-motion alignment, timing, kinematics, and social appropriateness. The model outperforms strong baselines in responsiveness, motion alignment, and social competence. We believe reframing non-verbal behavior as a core component of conversational intelligence and advancing toward socially adept 3D agents that communicate through language, voice, and movement.

2. Related Work

2.1. Conversational Avatar Generation

A conversational avatar fundamentally relies on two key components: a *speech module* to generate natural voice, and a *visual module* to synthesize realistic motion, including fa-

cial expressions and gestures, in either 2D or 3D form.

Speech dialog research splits into two paradigms: modular and end-to-end. Modular systems pair an LLM with a TTS/vocoder—LLM emits text or semantic tokens, TTS renders waveforms [20, 24–26, 77, 91, 134]. End-to-end voice agents integrate understanding and speech generation in a single model, tightly coupling semantics, prosody, and emotion [16, 42, 135].

In visual generation [12, 48, 58, 61, 78, 129], particularly 2D portrait animation, approaches are commonly grouped into video-driven and audio-driven formulations. Video-driven methods transfer motion from reference clips using explicit or implicit keypoints [38, 116, 127]. Audio-driven methods synthesize talking heads directly from speech, either end-to-end (e.g., Loopy [46], Emo [113]) or via two-stage designs (e.g., VASA-1 [126]), with related variants [118, 121]. Despite scaling gains, 2D representations limit applicability to interactive robotics and game engines and often degrade under viewpoint changes. Beyond 2D, 3D avatar generation boosts expressiveness: audio-to-face [15, 19, 28, 50, 85, 90, 105, 106] models target synchronization, and gesture generation emphasizes rhythmic and semantic alignment. Most works tackle face or gestures in isolation, whereas we aim to unify speech, facial expressions, and full-body motion.

2.2. Multi-modal Motion Generation

Human motion generation can be conditioned on text [14, 35, 37, 40, 45, 120, 133, 144, 146, 151], audio [10, 11, 39, 64, 66–68, 128, 131, 147], music [32, 43, 55, 56, 69, 71, 72, 103, 114, 115], and increasingly on multi-modal control [18, 54, 59, 124, 142, 143]. Text-driven methods are well studied, including diffusion-based models [14, 111], transformer-based autoregressive models [45, 117, 145, 151] and hybrid diffusion–transformer designs [151]. Audio-driven methods often address audio-to-motion synthesis, generating full-body motion from speech with an emphasis on rhythmic alignment [11, 67]. Recent work advances unified conditioning, enabling single models to respond to multiple signals (e.g., GenMo [54], LMM [142], RapVerse [13], LoM [11]). The closest, SOLAMI [47], aligns speech with body motion but lacks explicit text conditioning and an LLM reasoning backbone, and omits expressive facial motion. Building on this line, our framework seeks to unify multimodal control for avatar generation, combining audio, text, and conversational reasoning into a single model with question-answering capability.

2.3. Multimodal Large Language Models

Recent MLLMs highlight unified modeling across text, images, and audio [23, 53, 60, 109, 149]. Two fusion patterns dominate: single-stream models that concatenate multimodal tokens into one Transformer, and dual-stream/two-tower models that keep modality-specific backbones with

cross/co-attention (e.g., ViLBERT [76], LXMERT [107]). In generative vision, DiT and multimodal variants are now standard; Stable Diffusion 3 adopts MMDiT with separate image/language weights and joint attention for efficient bidirectional exchange [27, 89]. A complementary approach inserts gated cross-attention into a (partially) frozen LM to condition on visual tokens without full retraining [3].

Beyond dense fusion, expert-based designs scale by splitting parameters by modality and routing compute. MoME layers in VLMO and LIMoE select modality-aware experts via a router, yielding strong efficiency/accuracy trade-offs [4, 82]. Mixture-of-Transformers [60] decouples non-embedding parameters per modality while retaining global self-attention over mixed sequences, matching dense baselines with far fewer FLOPs. In robotics, VLA models link perception and policy via multimodal attention/adapters (e.g., RT-2, OpenVLA) [49, 119, 152]. Inspired by these trends, we adopt parameter-split Transformers with cross-modal fusion inside attention, supporting both autoregressive and diffusion generation for efficient pretraining and high-fidelity, controllable avatar synthesis.

3. Architecture

In this section, we present ViBES, an end-to-end architecture for a 3D conversational agent (Fig. 2). ViBES is an SLB model with MoME: three Transformer experts—a speech–language expert for understanding and generation, a facial-expression expert, and a body-motion expert—coupled via cross-modal attention to enforce speech, face and body synergy. Accordingly, ViBES comprises three main components: (i) a multimodal tokenizer that converts each sequential modality into multi-stream tokens while faithfully preserving fine-grained audio and motion dynamics; (ii) an LLM backbone that jointly models these token streams under the next-token prediction paradigm and exchanges information via SLB-Attn; and (iii) modality-aware fractional rotary positional embeddings (RoPE) that precisely encode cross-modal time alignment and relative positions.

3.1. Modality Representations & Tokenization

Precise cross-modal time alignment is critical for speaking agents. In practice, speech LLMs discretize audio at 12.5 [135], 25 [24] or 50 fps [41], whereas motion streams are typically 20 [140] or 30 fps [67], inducing systematic misalignment. We therefore standardize on a 25 fps universal clock: audio tokens are produced at 12.5 fps and all motion streams are resampled to 25 fps before fusion. We utilize three types of modality tokenization to convert each modality into a discrete token space.

Text and speech tokenization. We use Tiktoken, from GLM-4-9B [33] model, as text tokenizer to produce tokens $X = \{x_t\}_{t=1}^T$ (sub-word tokens with word timestamps for temporal alignment) where T is the window length. For




Figure 2. Model overview. The model adopts an autoregressive structure that converts all modalities into a unified token space. It consists of a Speech–Language–Behavior model with a Mixture-of-Modality-Experts (MoME) architecture, which processes audio, motion, and text inputs while sharing cross-modal information through the proposed Speech–Language–Behavior Attention (SLB-Attn) mechanism.

speech tokenization, the goal is two-fold: to preserve high-precision acoustic tokens with enough information to reconstruct the original audio and to preserve semantic information that captures the speaker’s emotion. Here, we adopt the 12.5Hz speech tokenizer variant from GLM-4-voice [135]. The speech tokenizer was fine-tuned on a pretrained automatic speech whisper-large-v3 in the Whisper family [96] with an additional pooling layer and a vector quantization layer in the middle of the encoder.

Face and body tokenization. We represent facial motion with the 3D morphable model FLAME [57] and body motion with the parametric model SMPL-X [87]. For each frame of the speaking sequence, the face is parameterized by shape $\beta_f \in \mathbb{R}^{100}$, expression $\psi_f \in \mathbb{R}^{100}$, and a 6D pose vector $\theta_f \in \mathbb{R}^6$ (continuous rotation); the body is parameterized by shape $\beta_b \in \mathbb{R}^{300}$ and joint poses $\theta_b \in \mathbb{R}^{55}$. Two representation conventions are prevalent in the community: the *skeletal* representation popularized by HumanML3D [35] and the *rotation-based* representation for expressive motion [67]. These choices hinder direct cross-paper comparison. To ensure fairness, we export motion in *both* formats and tokenize them accordingly—(i) skeletal sequences following HumanML3D and (ii) rotation-space sequences, each aligned to our 25 fps clock and used for evaluation against their respective baselines. For faces, we adopt the facial tokenizer introduced in LoM [11] and fine-tune it on our data without latent downsampling, yielding 25 fps face tokens; for expressive body motion, we use compositional tokenizer (upper body, lower body, hands) without additional fine-tuning and apply $\times 4$ temporal downsampling, resulting in 6.25 fps body tokens; for the HumanML3D setting, we follow MotionGPT [45], which likewise produces

6.25 fps tokens. All streams are aligned to a 25 fps master clock via a token–frame map for multimodal fusion.

3.2. Speech–Language–Behavior Model

ViBES adopts a Mixture-of-Modality-Experts (MoME) with three modality-specific FFN experts and LayerNorms: a text–speech(TS) expert operating on text and speech tokens for language comprehension and speech generation, a facial expert for facial-expression synthesis, and a body expert for upper, lower body, and hands. Unlike sparse MoE architectures with learned routers [101], we use hard routing that deterministically assigns tokens to experts by modality. Tokens are interleaved in the sequence. Each expert has its own FFN and LayerNorm and we employ modality-specific projections ($W_{ts}^{Q,K,V,O}$, $W_{face}^{Q,K,V,O}$, $W_{body}^{Q,K,V,O}$); attention is computed only over allowed modality pairs. Our architecture is heavily motivated by similar architectures from MOT [60], MMDit [27], and BAGEL [21]. Let the *interleaved* sequence be $\mathbf{x} = (x_1^{m_1}, \dots, x_T^{m_T})$ with modality labels $m_t \in \mathcal{M} = \{\text{text, speech, face, upper, lower, hands}\}$; layer input $\mathbf{h}^{(\ell)} \in \mathbb{R}^{T \times d}$ (batch omitted), and $\mathbf{h}^{(0)}$ the embedding of $\mathbf{x}$. Define subsets $\mathcal{M}_{ts} = \{\text{text, speech}\}$, $\mathcal{M}_{face} = \{\text{face}\}$, $\mathcal{M}_{body} = \{\text{upper, lower, hands}\}$.

Speech and text branch. Only text and speech tokens route to this expert, which has its own LN_{ts} and FFN_{ts} (initialized from GLM-4-Voice and frozen). TS queries attend only to TS keys and values with TS-specific projections:

$$\begin{aligned} \mathbf{Q}_{ts} &= \text{LN}_{\text{attn}}(\mathbf{h}_{ts}^{(\ell)})W_{ts}^Q, \\ \mathbf{K}_{ts} &= \text{LN}_{\text{attn}}(\mathbf{h}_{ts}^{(\ell)})W_{ts}^K, \\ \mathbf{V}_{ts} &= \text{LN}_{\text{attn}}(\mathbf{h}_{ts}^{(\ell)})W_{ts}^V. \end{aligned} \tag{1}$$

The TS attention update is

$$\tilde{\mathbf{h}}_{\text{ts}}^{(\ell)} = \mathbf{h}_{\text{ts}}^{(\ell)} + \text{Softmax}\left(\frac{\mathbf{Q}_{\text{ts}}\mathbf{K}_{\text{ts}}^\top}{\sqrt{d_h}}\right)\mathbf{V}_{\text{ts}}W_{\text{ts}}^O. \quad (2)$$

Then the TS expert applies its *own* normalization and FFN:

$$\mathbf{h}_t^{(\ell+1)} = \tilde{\mathbf{h}}_t^{(\ell)} + \text{FFN}_{\text{ts}}(\text{LN}_{\text{ts}}(\tilde{\mathbf{h}}_t^{(\ell)})), \text{ for } m_t \in \mathcal{M}_{\text{ts}}. \quad (3)$$

Face and body branch. Facial tokens route to $(\text{LN}_{\text{face}}, \text{FFN}_{\text{face}})$; body tokens (upper, lower and hands) route to $(\text{LN}_{\text{body}}, \text{FFN}_{\text{body}})$. Queries use **their own** projections, but keys/values come *only* from the TS stream (no Face $\leftrightarrow$ Body attention):

$$\begin{aligned} \mathbf{Q}_{\text{face}} &= \text{LN}_{\text{attn}}(\mathbf{h}_{\text{face}}^{(\ell)})W_{\text{face}}^Q, \\ \mathbf{Q}_{\text{body}} &= \text{LN}_{\text{attn}}(\mathbf{h}_{\text{body}}^{(\ell)})W_{\text{body}}^Q. \end{aligned} \quad (4)$$

Facial and body attention updates (to TS keys/values) are

$$\begin{aligned} \tilde{\mathbf{h}}_{\text{face}}^{(\ell)} &= \mathbf{h}_{\text{face}}^{(\ell)} + \text{Softmax}\left(\frac{\mathbf{Q}_{\text{face}}\mathbf{K}_{\text{ts}}^\top}{\sqrt{d_h}}\right)\mathbf{V}_{\text{ts}}W_{\text{face}}^O, \\ \tilde{\mathbf{h}}_{\text{body}}^{(\ell)} &= \mathbf{h}_{\text{body}}^{(\ell)} + \text{Softmax}\left(\frac{\mathbf{Q}_{\text{body}}\mathbf{K}_{\text{ts}}^\top}{\sqrt{d_h}}\right)\mathbf{V}_{\text{ts}}W_{\text{body}}^O. \end{aligned} \quad (5)$$

Finally, each expert applies its own normalization and FFN to its positions (tokens remain interleaved in the global sequence):

$$\mathbf{h}_t^{(\ell+1)} = \begin{cases} \tilde{\mathbf{h}}_t^{(\ell)} + \text{FFN}_{\text{face}}(\text{LN}_{\text{face}}(\tilde{\mathbf{h}}_t^{(\ell)})), & \text{if } m_t \in \mathcal{M}_{\text{face}}, \\ \tilde{\mathbf{h}}_t^{(\ell)} + \text{FFN}_{\text{body}}(\text{LN}_{\text{body}}(\tilde{\mathbf{h}}_t^{(\ell)})), & \text{if } m_t \in \mathcal{M}_{\text{body}}. \end{cases} \quad (6)$$

It is worth noting that Eqs. (1)–(5) employ modality-specific projections: TS attends to TS, whereas facial/body queries attend only to TS. In ablations, enabling face and body attention yields no measurable improvement; once conditioned on TS, the face and body streams appear largely independent. We therefore disable face and body attention by design; see Ablation Study 5 for more details.

3.3. Multi-modal Fractional RoPE

Interleaved-token mixed training has been shown to efficiently align modalities—especially for sequential data [3, 109, 135, 150]. In conversational agents, each modality is inherently sequential and thus requires precise cross-modal synchronization. Thus, we encode interleaved multi-modal tokens on a *single* rotary timeline by assigning each token a scalar (possibly non-integer) index $s_t \in \mathbb{R}$ that preserves cross-modal timing. The timeline is anchored by the text–speech (TS) stream, consistent with our attention topology where keys/values originate from TS.

Setup and anchors. Let the interleaved sequence be $\{x_t^{m_t}\}_{t=1}^T$ with $m_t \in \mathcal{M} = \{\text{text, speech, face, upper, lower, hands}\}$. Denote the

TS subset $\mathcal{M}_{\text{ts}} = \{\text{text, speech}\}$ and the motion subset $\mathcal{M}_{\text{mo}} = \mathcal{M} \setminus \mathcal{M}_{\text{ts}}$. Let $\mathcal{A} = \{a_0 < \dots < a_{L-1}\}$ be the indices of tokens whose modality lies in $\mathcal{M}_{\text{ts}}$ (TS anchors). Each anchor receives an *integer* index

$$s_{a_i} = i, \quad i = 0, \dots, L-1.$$

Assume each token carries a wall-clock timestamp $u(t)$ (e.g., audio frame time; text aligned by ASR/forced alignment). Let $\Delta_i = u(a_{i+1}) - u(a_i)$ be the anchor interval length and $\bar{\Delta}$ the median of $\{\Delta_i\}$ for extrapolation.

Fractional indices for motion tokens. For a motion token at position t with $m_t \in \mathcal{M}_{\text{mo}}$, find i such that $u(a_i) \leq u(t) < u(a_{i+1})$. Its fractional index is the linear interpolation between the surrounding TS anchors:

$$\alpha_t = \frac{u(t) - u(a_i)}{u(a_{i+1}) - u(a_i)} \in [0, 1), \quad s_t = s_{a_i} + \alpha_t. \quad (7)$$

If $u(t) < u(a_0)$ (left tail), use a left extrapolation with step $\bar{\Delta}$:

$$s_t = s_{a_0} - \frac{u(a_0) - u(t)}{\bar{\Delta}}. \quad (8)$$

If $u(t) \geq u(a_{L-1})$ (right tail), use a right extrapolation:

$$s_t = s_{a_{L-1}} + \frac{u(t) - u(a_{L-1})}{\bar{\Delta}}. \quad (9)$$

This construction yields a globally ordered sequence of indices $\{s_t\}_{t=1}^T$ in which TS positions are integers and motion positions fall at fractional locations aligned to TS time.

Optional per-modality offset and scale. To stabilize training with interleaved streams of different frame rates, we optionally apply a modality-specific phase offset $\delta_m \in \mathbb{R}$ and a phase scale $\gamma_m > 0$:

$$\hat{s}_t = \gamma_{m_t} s_t + \delta_{m_t}. \quad (10)$$

Typical choices set $\gamma_{\text{ts}} = 1$, and small offsets for motion (e.g., $\delta_{\text{face}} < 0 < \delta_{\text{body}}$) to reduce collision at anchor boundaries. When not used, take $\gamma_m = 1$ and $\delta_m = 0$.

Rotary positional encoding. Let d_{rot} be the rotary dimension (even), and $L = d_{\text{rot}}/2$ the number of frequency channels. With base $b > 1$, define the inverse-frequency ladder

$$\omega_j = b^{-\frac{2j}{d_{\text{rot}}}}, \quad j = 0, \dots, L-1. \quad (11)$$

Given the (possibly fractional) index $\hat{s}_t$ from (10), the phase for channel j is $\theta_{t,j} = \hat{s}_t \omega_j$. Denote by $\text{rot}(\cdot; \theta)$ the 2D rotation applied to coordinate pairs $(2j, 2j+1)$ of queries/keys. For a query $\mathbf{q}_t$ and a key $\mathbf{k}_i$, RoPE applies

$$\mathbf{q}_t^{\text{rope}} = \text{rot}(\mathbf{q}_t; \theta_{t,:}), \quad \mathbf{k}_i^{\text{rope}} = \text{rot}(\mathbf{k}_i; \theta_{i,:}), \quad (12)$$

after which attention uses the standard dot-product with these rotated vectors. Stacking phases in matrix form with $\boldsymbol{\omega} = [\omega_0, \dots, \omega_{L-1}]^\top$ and $\hat{\mathbf{s}} = [\hat{s}_1, \dots, \hat{s}_T]^\top$ gives $\Theta = \hat{\mathbf{s}} \boldsymbol{\omega}^\top \in \mathbb{R}^{T \times L}$.

Table 1. Comparison of Converse3D with existing datasets. We report the duration of Converse3D as N/A, since it is constructed by combining web YouTube videos and other datasets, making a direct comparison in hours less meaningful.

Datasets	Duration (hours)	Q&A	Facial	Upper Body	Lower Body	Mesh	Description
TED [132]	106.1	×	×	✓	×	×	×
TED-Ex [70]	100.8	×	×	✓	×	×	×
EGGS [31]	2	×	×	✓	✓	×	×
BEAT [65]	76	×	×	✓	✓	✓	×
SHOW [130]	26.9	×	✓	✓	×	✓	×
TWH16.2 [50]	17	×	×	✓	✓	✓	×
BEAT2 [67]	60	×	✓	✓	✓	✓	×
DND [81]	6	×	×	✓	✓	×	×
Photoreal [84]	8	×	✓	✓	✓	×	×
GES-Inter [92]	8	✓	✓	✓	×	✓	×
Embod3D [80]	500	✓	×	✓	✓	✓	✓
Seamless Interaction [2]	4,065	✓	×	✓	×	✓	×
Converse3D (Ours)	NA	✓	✓	✓	✓	✓	✓

4. The Converse3D Dataset

A significant bottleneck for developing 3D conversational agents is the lack of large-scale, time-aligned audio–text–motion datasets. Existing datasets are typically fragmented, providing only pairwise alignments (e.g., text-to-motion, text-to-speech) and limited coverage. To overcome this, we introduce Converse3D, a corpus of roughly 1,000 hours designed for 3D conversational agents, curated from three complementary sources: (i) in-the-wild YouTube conversations spanning interviews, podcasts, talks, and casual dialogues; (ii) high-quality motion datasets with text or audio annotations; and (iii) carefully controlled synthesis to complete missing modalities. All motion is represented in SMPL-X [87] and FLAME [57], and different streams (text, face, body, hands) are temporally aligned to a unified 25 fps clock to support streaming training and inference.

4.1. Data Collection from the YouTube Corpus

We curate long-form conversational videos (interviews, roundtables, talks with audience interaction) and process them with a unified pipeline. Voice activity detection [108], word-level ASR [96], and speaker diarization segment multi-party audio into utterance windows. For each window, we estimate SMPL-X body and hands and FLAME face parameter representations using robust monocular methods [29, 34, 88], then resample all streams to 25 fps with per-frame timestamps and token–frame maps. Quality control filters low-confidence geometry (high reprojection error, self-intersection), enforces visibility checks before completion, and verifies audio/text integrity (SNR, WER) and temporal alignment consistency.

4.2. Consolidating Existing Motion Datasets

While most motion datasets cover only subsets of modalities, their scale and fidelity are valuable for cross-modal learning. We integrate HumanML3D (~24K text–motion pairs), BEAT2 (~70 hours audio–motion), Embod3D (~50 hours audio with full body), and TFHP (audio with facial annotations). All sequences are retargeted to a com-

mon SMPL-X/FLAME parameters, then resampled to 25 fps.

4.3. Synthesizing Tri-Modal Supervision from Fragmented Sources

To close residual modality gaps, we synthesize missing signals conservatively. ARTalk [15] refines lip sync on a small subset, producing FLAME trajectories aligned to audio; LoM [11] completes occluded hands only to avoid altering global dynamics. When only motion and a caption are available, GPT-4o [44] generates situational prompts that we render with a high-fidelity TTS, yielding paired audio–text queries aligned with the motion.

5. Experiments

In this section, we first introduce a new benchmark to evaluate agentic conversational behavior for ViBES and several baselines. We then demonstrate the versatility of our model on several downstream tasks: talking-head synthesis, co-speech gesture generation, and text-to-motion, and compare against state-of-the-art methods on existing benchmarks.

5.1. Benchmark for Conversational Behavior

Evaluating conversational motion generation is challenging: body movement during speech is inherently one-to-many, and standard motion-text retrieval metrics conflate two distinct capabilities—producing semantically specific actions (e.g., “wave your right hand”) and generating plausible conversational gestures for open-ended questions (e.g., “What does happiness mean to you?”). We address this with a balanced R-Precision protocol on the Converse3D test set (4,921 samples: 3,128 motion-descriptive from AMASS and 1,793 conversational from BEAT2). A Question-to-Motion (Q2M) contrastive evaluator, built on a CLIP-style architecture with a Transformer motion encoder and a frozen CLIP [95] text encoder, maps both questions and motions (22 body joints in 6D rotation plus root velocity). Each evaluation batch contains 16 motion-descriptive and 16 conversational samples. For motion-descriptive queries, we apply strict 1-to-1 matching: the model must retrieve the exact paired motion. For conversational queries, we apply relaxed matching: retrieval of any conversational gesture in the batch counts as correct, reflecting the genuine ambiguity of co-speech gesture. We report the balanced R-Precision (weighted average of both types), type-specific R-Precision, Matching Distance, FID against GT motion embeddings, and Diversity. We report the conversational behavior benchmark in Table 2. ViBES achieves stronger question-to-motion alignment, indicating that joint training within the speech–language–behavior framework provides clear performance gains over prior co-speech gesture generation and text-to-motion baselines.

Table 2. Benchmarking conversational behavior. “↑” indicates that higher values are better. The best results are in **bold**.

Methods	Input	R1-Balanced ↓	R1-Motion ↓	R1-Conv ↓	R3-Balanced ↓	MM Dist ↓	FID ↓	Div →
Ground Truth	NA	0.712	0.546	0.999	0.883	2.342	0.0	11.05
<i>Co-speech gesture generation methods</i>								
SynTalker [10]	Response audio	0.288	0.025	0.744	0.390	3.650	406.3	1.70
EMAGE [67]	Response audio	0.258	0.025	0.663	0.378	3.639	371.7	2.37
LOM [11]	Response audio	0.323	0.025	0.621	0.498	3.435	373.8	2.49
<i>Text-to-motion generation methods</i>								
T2M [35]	Question text	0.223	0.180	0.297	0.476	3.682	306.2	6.14
MotionGPT [45]	Question text	0.244	0.123	0.452	0.475	3.734	262.2	7.40
MoMask [37]	Question text	0.293	0.159	0.524	0.528	3.675	265.5	7.38
<i>Speech–Language–Behavior Unified Models</i>								
Ours	Question text	0.467	0.308	0.745	0.671	3.178	93.9	10.73

Table 3. Quantitative results on speech metrics. “↑” indicates higher-is-better; best values are in **bold**.

Methods	Context Relevance ↑	Character Consistency ↑
SynMSI [47] (GroundTruth)	4.838	4.893
LLM+Speech (Llama2)	3.859	3.157
AnyGPT [136] (fine-tune)	3.803	-
DLP [9] (MotionGPT)	3.577	3.785
SOLAMI(LoRA) [47]	0.824	3.634
SOLAMI(full params) [47]	0.824	3.634
Ours(from GLM-4-Voice [135] weight)	4.584	4.376




Figure 3. Qualitative examples of conversational behavior. We show one example for text-based interaction (top) and one example for audio-based interaction (bottom).

For speech performance, Table 3 shows that ViBES achieves significant gains across metrics and, on several, approaches the dataset’s ground-truth upper bound, suggesting that the text–speech branch effectively inherits and preserves competence from the pretrained backbone. Qualitative examples in Fig. 3 demonstrate multi-turn interactions via both text and speech with coherent responses and appropriate conversational behavior.

5.2. Talking-Head Synthesis

In addition to generating full conversational behavior, ViBES also supports audio-to-face task by feeding target audio tokens and decoding facial motion. We evaluate on

Table 4. Results on talking-head synthesis. We use colors to denote the first and second places respectively. * indicates that the method was not trained on TFHP [105].

Method	LVE ↓	MOD ↓	FDD ↓	Type
CodeTalker* [122]	13.17	4.74	24.45	Audio → Face
SelfTalk* [90]	13.93	3.04	19.81	Audio → Face
FaceDiffuser* [104]	14.10	3.03	22.22	Audio → Face
MultiTalk* [106]	11.66	2.35	15.68	Audio → Face
ScanTalk* [85]	13.88	3.24	40.57	Audio → Face
UniTalker* [28]	14.37	3.24	24.58	Audio → Face
DiffPoseTalk [105]	11.01	2.55	37.68	Audio → Face
ARTalk [15]	11.67	2.46	20.77	Audio → Face
Ours	10.87	2.29	6.05	Multi Task




Figure 4. Qualitative comparison with prior methods on the speech-driven 3D head animation task (head pose held fixed). Since most existing models were trained on TFHP, using this dataset ensures a fair comparison.

the test split of the TFHP dataset using standard metrics, including Lip Vertex Error (LVE) for lip synchronization [98],

Upper-Face Dynamic Deviation (FDD) for expressive stability [122], and Mouth Opening Distance (MOD) for mouth-style similarity [105]. The lip and upper-face regions are defined using the official FLAME masks [57]. We note that the computation of LVE is inconsistent across the literature. For example, CodeTalker [122] reports the mean per-frame maximum squared ℓ_2 distance in raw mesh coordinates, whereas ARTalk applies a square root and converts the values to millimeters before evaluation. Such differences in formulation and unit scaling make direct cross-method LVE comparisons unreliable. Therefore, we follow the evaluation protocol of ARTalk using their released code, and recompute all baselines using their provided checkpoints. For fairness, since some baselines are trained only on TFHP, we additionally train a separate version of our model using only the TFHP training split. The results are reported in Table 4. Although the ViBES is not explicitly designed for audio-to-face alignment, we surprisingly find that our method achieves state-of-the-art quantitative performance. Compared with strong audio-driven baselines, our model attains competitive LVE and improved FDD/MOD, indicating better dynamic stability and mouth-style similarity. We provide additional qualitative comparisons in Fig. 4. Our method shows better alignment with the ground truth in terms of mouth dynamics and lip synchronization.

5.3. Co-Speech Gesture Generation

ViBES also supports audio-to-motion by conditioning on speech tokens and decoding full-body SMPL-X parameters. We evaluate the model on BEATv2 benchmark [67] using the standard speaker-independent split, reporting Fréchet Gesture Distance (FGD), Beat Correlation (BC) [55], and diversity [52]. Baselines include LoM [11], EMAGE [67], and recent transformer-based audio-to-motion models. For fairness, ViBES is trained only on the BEATv2 training split without external data. Results are in Table 5. ViBES has lower FGD and higher BC while maintaining diversity, showing that the cross-modal attention strengthens alignment across modalities.

5.4. Text-to-Motion

As discussed in Sec. 3, most text-to-motion benchmarks operate in the skeletal HumanML3D representation rather than expressive rotation formats. For a fair comparison, we instantiate a ViBES variant that outputs HumanML3D tokens and train it on the HumanML3D training split without using external data. We compare with strong baselines, including MotionGPT [45], LoM [11], and MoMask [37], and provide qualitative examples in Fig. 5. Benefiting from the pretrained language backbone, ViBES shows stronger linguistic grounding and handles rare or long-form instructions more reliably.

Table 5. Co-speech gesture generation results on BEATv2 benchmark. We report FGD $\times 10^{-1}$, BC $\times 10^{-1}$.

Methods	FGD $\downarrow$	BC $\uparrow$	Diversity $\uparrow$
DisCo [64]	9.417	6.439	9.912
CaMN [66]	6.644	6.769	10.860
DiffStyleGesture [128]	8.811	7.241	11.490
Habibie et al. [39]	9.040	7.716	8.213
TalkSHOW [131]	6.209	6.947	13.470
SynTalker [10]	6.413	7.971	12.721
EMAGE [67]	5.512	7.724	13.060
LOM [11]	5.301	7.780	15.167
Ours	5.257	8.103	13.028




Figure 5. Qualitative comparison for text-to-motion. While ViBES targets conversational behavior, its autoregressive design also supports text-to-motion generation for fair comparison with existing methods.

6. Conclusion and Discussion

We present ViBES, a unified speech–language–behavior model for 3D conversational agents, together with Converse3D, a large-scale audio–text–motion corpus. The model improves conversational behavior while remaining strong on talking-head synthesis, co-speech gesture generation, and text-to-motion tasks. Nevertheless, several limitations remain. The current dataset scale is still limited for fully training a speech-LLM backbone, and our framework does not yet exploit the full reasoning capability of modern LLMs. Because the dataset is constructed from web videos, it also inherits artifacts from monocular reconstruction. Finally, conversational behavior remains difficult to evaluate; building a preference model aligned with human preferences could provide a more reliable evaluation signal.

Acknowledgments: This project was partially funded by NIH grant R01AG089169, R33AG084471, and UST. The authors would also like to thank Yao Feng and Yue Zhao for their valuable discussion. The authors would also like to thank Jenny Xu for her help in discovering that TalkNet is useful for separating speaking segments.

References

- [1] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- [2] Vasu Agrawal, Akinniyi Akinyemi, Kathryn Alvero, Morteza Behrooz, Julia Buffalini, Fabio Maria Carlucci, Joy Chen, Junming Chen, Zhang Chen, Shiyang Cheng, et al. Seamless interaction: Dyadic audiovisual motion modeling and large-scale dataset. *arXiv preprint arXiv:2506.22554*, 2025.
- [3] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *Advances in neural information processing systems*, 35: 23716–23736, 2022.
- [4] Hangbo Bao, Wenhui Wang, Li Dong, Qiang Liu, Owais Khan Mohammed, Kriti Aggarwal, Subhojit Som, Songhao Piao, and Furu Wei. Vlmoe: Unified vision-language pre-training with mixture-of-modality-experts. *Advances in neural information processing systems*, 35: 32897–32912, 2022.
- [5] Kevin Black, Noah Brown, Danny Driess, Adnan Esmail, Michael Equi, Chelsea Finn, Niccolo Fusai, Lachy Groom, Karol Hausman, Brian Ichter, et al. $\pi 0$: A vision-language-action flow model for general robot control. corr, abs/2410.24164, 2024. doi: 10.48550. *arXiv preprint ARXIV.2410.24164*.
- [6] Boson AI. Higgs Audio V2: Redefining Expressiveness in Audio Generation. <https://github.com/boson-ai/higgs-audio>, 2025. GitHub repository. Release blog available at <https://www.boson.ai/blog/higgs-audio-v2>.
- [7] Anthony Brohan, Noah Brown, Justice Carbajal, Yevgen Chebotar, Joseph Dabis, Chelsea Finn, Keerthana Gopalakrishnan, Karol Hausman, Alex Herzog, Jasmine Hsu, et al. Rt-1: Robotics transformer for real-world control at scale. *arXiv preprint arXiv:2212.06817*, 2022.
- [8] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.
- [9] Zhongang Cai, Jianping Jiang, Zhongfei Qing, Xinying Guo, Mingyuan Zhang, Zhengyu Lin, Haiyi Mei, Chen Wei, Ruisi Wang, Wanqi Yin, et al. Digital life project: Autonomous 3d characters with social intelligence. In *CVPR*, pages 582–592, 2024.
- [10] Bohong Chen, Yumeng Li, Yao-Xiang Ding, Tianjia Shao, and Kun Zhou. Enabling synergistic full-body control in prompt-based co-speech motion generation. In *Proceedings of the 32nd ACM International Conference on Multimedia*, pages 6774–6783, 2024.
- [11] Changan Chen, Juzhe Zhang, Shrinidhi K Lakshmikanth, Yusu Fang, Ruizhi Shao, Gordon Wetzstein, Li Fei-Fei, and Ehsan Adeli. The language of motion: Unifying verbal and non-verbal language of 3d human motion. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 6200–6211, 2025.
- [12] Jiaben Chen, Zixin Wang, Ailing Zeng, Yang Fu, Xueyang Yu, Siyuan Cen, Julian Tanke, Yihang Chen, Koichi Saito, Yuki Mitsufuji, et al. Talkcuts: A large-scale dataset for multi-shot human speech video generation. *arXiv preprint arXiv:2510.07249*, 2025.
- [13] Jiaben Chen, Xin Yan, Yihang Chen, Siyuan Cen, Zixin Wang, Qinwei Ma, Haoyu Zhen, Kaizhi Qian, Lie Lu, and Chuang Gan. Rapverse: Coherent vocals and whole-body motion generation from text. In *ICCV*, pages 10097–10107, 2025.
- [14] Xin Chen, Biao Jiang, Wen Liu, Zilong Huang, Bin Fu, Tao Chen, and Gang Yu. Executing your commands via motion diffusion in latent space. In *CVPR*, pages 18000–18010, 2023.
- [15] Xuangeng Chu, Nabarun Goswami, Ziteng Cui, Hanqin Wang, and Tatsuya Harada. Artalk: Speech-driven 3d head animation via autoregressive model. *arXiv preprint arXiv:2502.20323*, 2025.
- [16] Yunfei Chu, Jin Xu, Qian Yang, Haojie Wei, Xipin Wei, Zhifang Guo, Yichong Leng, Yuanjun Lv, Jinzheng He, Junyang Lin, et al. Qwen2-audio technical report. *arXiv preprint arXiv:2407.10759*, 2024.
- [17] Gheorghe Comanici, Eric Bieber, Mike Schaeckermann, Ice Pasupat, Naveen Sachdeva, Inderjit Dhillon, Marcel Blstein, Ori Ram, Dan Zhang, Evan Rosen, et al. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*, 2025.
- [18] Peishan Cong, Yiteng Xu, Yiming Ren, Juzhe Zhang, Lan Xu, Jingya Wang, Jingyi Yu, and Yuexin Ma. Weakly supervised 3d multi-person pose estimation for large-scale scenes based on monocular camera and single lidar. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 461–469, 2023.
- [19] Radek Daněček, Carolin Schmitt, Senya Polikovsky, and Michael J Black. Supervising 3d talking head avatars with analysis-by-audio-synthesis. *arXiv preprint arXiv:2504.13386*, 2025.
- [20] Alexandre Défossez, Laurent Mazaré, Manu Orsini, Amélie Royer, Patrick Pérez, Hervé Jégou, Edouard Grave, and Neil Zeghidour. Moshi: a speech-text foundation model for real-time dialogue. *arXiv preprint arXiv:2410.00037*, 2024.
- [21] Chaorui Deng, Deyao Zhu, Kunchang Li, Chenhui Gou, Feng Li, Zeyu Wang, Shu Zhong, Weihao Yu, Xiaonan Nie, Ziang Song, et al. Emerging properties in unified multimodal pretraining. *arXiv preprint arXiv:2505.14683*, 2025.

- [22] Danny Driess, Fei Xia, Mehdi SM Sajjadi, Corey Lynch, Aakanksha Chowdhery, Ayzaan Wahid, Jonathan Tompson, Quan Vuong, Tianhe Yu, Wenlong Huang, et al. Palm-e: An embodied multimodal language model. 2023.
- [23] Songcheng Du, Yang Zou, Zixu Wang, Xingyuan Li, Ying Li, Changjing Shang, and Qiang Shen. Unsupervised hyperspectral image super-resolution via self-supervised modality decoupling. *International Journal of Computer Vision*, 134:152, 2026.
- [24] Zhihao Du, Qian Chen, Shiliang Zhang, Kai Hu, Heng Lu, Yexin Yang, Hangrui Hu, Siqi Zheng, Yue Gu, Ziyang Ma, et al. Cosyvoice: A scalable multilingual zero-shot text-to-speech synthesizer based on supervised semantic tokens. *arXiv preprint arXiv:2407.05407*, 2024.
- [25] Zhihao Du, Yuxuan Wang, Qian Chen, Xian Shi, Xiang Lv, Tianyu Zhao, Zhifu Gao, Yexin Yang, Changfeng Gao, Hui Wang, et al. Cosyvoice 2: Scalable streaming speech synthesis with large language models. *arXiv preprint arXiv:2412.10117*, 2024.
- [26] Zhihao Du, Changfeng Gao, Yuxuan Wang, Fan Yu, Tianyu Zhao, Hao Wang, Xiang Lv, Hui Wang, Xian Shi, Keyu An, et al. Cosyvoice 3: Towards in-the-wild speech generation via scaling-up and post-training. *arXiv preprint arXiv:2505.17589*, 2025.
- [27] Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, et al. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first international conference on machine learning*, 2024.
- [28] Xiangyu Fan, Jiaqi Li, Zhiqian Lin, Weiye Xiao, and Lei Yang. Unitalker: Scaling up audio-driven 3d facial animation through a unified model. In *ECCV*, pages 204–221. Springer, 2024.
- [29] Panagiotis P. Filntisis, George Retsinas, Foivos Paraperas-Papantoniou, Athanasios Katsamanis, Anastasios Roussos, and Petros Maragos. Visual speech-aware perceptual 3d facial expression reconstruction from videos, 2022.
- [30] Xingyu Fu, Siyi Liu, YINUO Xu, Pan Lu, Guangqiuse Hu, Tianbo Yang, Taran Anantasagar, Christopher Shen, Yikai Mao, Yuanzhe Liu, et al. Learning human-perceived fakeness in ai-generated videos via multimodal llms. *arXiv preprint arXiv:2509.22646*, 2025.
- [31] Saeed Ghorbani, Ylva Ferstl, Daniel Holden, Nikolaus F Troje, and Marc-André Carbonneau. Zeroeggs: Zero-shot example-based gesture generation from speech. In *Computer Graphics Forum*, pages 206–216. Wiley Online Library, 2023.
- [32] Anindita Ghosh, Bing Zhou, Rishabh Dabral, Jian Wang, Vladislav Golyanik, Christian Theobalt, Philipp Slusallek, and Chuan Guo. Duetgen: Music driven two-person dance generation via hierarchical masked modeling. In *Proceedings of the Special Interest Group on Computer Graphics and Interactive Techniques Conference Conference Papers*, pages 1–11, 2025.
- [33] Team GLM, Aohan Zeng, Bin Xu, Bowen Wang, Chenhui Zhang, Da Yin, Dan Zhang, Diego Rojas, Guanyu Feng, Hanlin Zhao, et al. Chatglm: A family of large language models from glm-130b to glm-4 all tools. *arXiv preprint arXiv:2406.12793*, 2024.
- [34] Shubham Goel, Georgios Pavlakos, Jathushan Rajasegaran, Angjoo Kanazawa, and Jitendra Malik. Humans in 4D: Reconstructing and tracking humans with transformers. In *ICCV*, 2023.
- [35] Chuan Guo, Shihao Zou, Xinxin Zuo, Sen Wang, Wei Ji, Xingyu Li, and Li Cheng. Generating diverse and natural 3d human motions from text. In *CVPR*, pages 5152–5161, 2022.
- [36] Chuan Guo, Xinxin Zuo, Sen Wang, and Li Cheng. Tm2t: Stochastic and tokenized modeling for the reciprocal generation of 3d human motions and texts. In *ECCV*, pages 580–597. Springer, 2022.
- [37] Chuan Guo, Yuxuan Mu, Muhammad Gohar Javed, Sen Wang, and Li Cheng. Momask: Generative masked modeling of 3d human motions. In *CVPR*, pages 1900–1910, 2024.
- [38] Jianzhu Guo, Dingyun Zhang, Xiaoqiang Liu, Zhizhou Zhong, Yuan Zhang, Pengfei Wan, and Di Zhang. Live-portrait: Efficient portrait animation with stitching and re-targeting control. *arXiv preprint arXiv:2407.03168*, 2024.
- [39] Ikhsanul Habibie, Weipeng Xu, Dushyant Mehta, Lingjie Liu, Hans-Peter Seidel, Gerard Pons-Moll, Mohamed Elgharib, and Christian Theobalt. Learning speech-driven 3d conversational gestures from video. In *Proceedings of the 21st ACM international conference on intelligent virtual agents*, pages 101–108, 2021.
- [40] Ruibing Hou, Mingshuang Luo, Hongyu Pan, Hong Chang, and Shiguang Shan. Motionverse: A unified multimodal framework for motion comprehension, generation and editing. *arXiv preprint arXiv:2509.23635*, 2025.
- [41] Wei-Ning Hsu, Benjamin Bolte, Yao-Hung Hubert Tsai, Kushal Lakhotia, Ruslan Salakhutdinov, and Abdelrahman Mohamed. Hubert: Self-supervised speech representation learning by masked prediction of hidden units. *IEEE/ACM transactions on audio, speech, and language processing*, 29:3451–3460, 2021.
- [42] Ailin Huang, Boyong Wu, Bruce Wang, Chao Yan, Chen Hu, Chengli Feng, Fei Tian, Feiyu Shen, Jingbei Li, Mingrui Chen, et al. Step-audio: Unified understanding and generation in intelligent speech interaction. *arXiv preprint arXiv:2502.11946*, 2025.
- [43] Zikai Huang, Xuemiao Xu, Cheng Xu, Huaidong Zhang, Chenxi Zheng, Jing Qin, and Shengfeng He. Beat-it: Beat-synchronized multi-condition 3d dance generation. In *European conference on computer vision*, pages 273–290. Springer, 2024.
- [44] Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.
- [45] Biao Jiang, Xin Chen, Wen Liu, Jingyi Yu, Gang Yu, and Tao Chen. Motiongpt: Human motion as a foreign language. *NeurIPS*, 36:20067–20079, 2023.

- [46] Jianwen Jiang, Chao Liang, Jiaqi Yang, Gaojie Lin, Tianyun Zhong, and Yanbo Zheng. Loopy: Taming audio-driven portrait avatar with long-term motion dependency. *arXiv preprint arXiv:2409.02634*, 2024.
- [47] Jianping Jiang, Weiye Xiao, Zhengyu Lin, Huaizhong Zhang, Tianxiang Ren, Yang Gao, Zhiqian Lin, Zhongang Cai, Lei Yang, and Ziwei Liu. Solami: Social vision-language-action modeling for immersive interaction with 3d autonomous characters. In *CVPR*, 2025.
- [48] Jianwen Jiang, Weihong Zeng, Zerong Zheng, Jiaqi Yang, Chao Liang, Wang Liao, Han Liang, Yuan Zhang, and Mingyuan Gao. Omnihuman-1.5: Instilling an active mind in avatars via cognitive simulation. *arXiv preprint arXiv:2508.19209*, 2025.
- [49] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, et al. Openvla: An open-source vision-language-action model. *arXiv preprint arXiv:2406.09246*, 2024.
- [50] Gilwoo Lee, Zhiwei Deng, Shugao Ma, Takaaki Shiratori, Siddhartha S Srinivasa, and Yaser Sheikh. Talking with hands 16.2 m: A large-scale dataset of synchronized body-finger motion and audio for conversational motion analysis and synthesis. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 763–772, 2019.
- [51] Boyi Li, Yifan Shen, Yuanzhe Liu, Yifan Xu, Jiateng Liu, Xinzhuo Li, Zhengyuan Li, Jingyuan Zhu, Yunhan Zhong, Fangzhou Lan, et al. Toward cognitive supersensing in multimodal large language model. *arXiv preprint arXiv:2602.01541*, 2026.
- [52] Jing Li, Di Kang, Wenjie Pei, Xuefei Zhe, Ying Zhang, Zhenyu He, and Linchao Bao. Audio2gestures: Generating diverse gestures from speech audio with conditional variational autoencoders. In *ICCV*, pages 11293–11302, 2021.
- [53] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pages 19730–19742. PMLR, 2023.
- [54] Jiefeng Li, Jinkun Cao, Haotian Zhang, Davis Rempe, Jan Kautz, Umar Iqbal, and Ye Yuan. Genmo: A GENeralist model for human MOTion. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.
- [55] Ruilong Li, Shan Yang, David A. Ross, and Angjoo Kanazawa. Ai choreographer: Music conditioned 3d dance generation with aist++. In *ICCV*, 2021.
- [56] Ronghui Li, Junfan Zhao, Yachao Zhang, Mingyang Su, Zeping Ren, Han Zhang, Yansong Tang, and Xiu Li. Finedance: A fine-grained choreography dataset for 3d full body dance generation. In *ICCV*, pages 10234–10243, 2023.
- [57] Tianye Li, Timo Bolkart, Michael J. Black, Hao Li, and Javier Romero. Learning a model of facial shape and expression from 4D scans. *ACM Transactions on Graphics, (Proc. SIGGRAPH Asia)*, 36(6):194:1–194:17, 2017.
- [58] Xiaodi Li, Pan Xie, Yi Ren, Qijun Gan, Chen Zhang, Fangyuan Kong, Xiang Yin, Bingyue Peng, and Zehuan Yuan. Infinityhuman: Towards long-term audio-driven human. *arXiv preprint arXiv:2508.20210*, 2025.
- [59] Han Liang, Chengyu Huang, Yuecheng Xu, Cheng Tang, Weicai Ye, Juze Zhang, Xin Chen, Jingyi Yu, and Lan Xu. Llava-slt: Visual language tuning for sign language translation. *arXiv preprint arXiv:2412.16524*, 2024.
- [60] Weixin Liang, Lili Yu, Liang Luo, Srinivasan Iyer, Ning Dong, Chunting Zhou, Gargi Ghosh, Mike Lewis, Wen-tau Yih, Luke Zettlemoyer, et al. Mixture-of-transformers: A sparse and scalable architecture for multi-modal foundation models. *arXiv preprint arXiv:2411.04996*, 2024.
- [61] Gaojie Lin, Jianwen Jiang, Jiaqi Yang, Zerong Zheng, Chao Liang, Yuan Zhang, and Jingtuo Liu. Omnihuman-1: Rethinking the scaling-up of one-stage conditioned human animation models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 13847–13858, 2025.
- [62] Jing Lin, Ruisi Wang, Junzhe Lu, Ziqi Huang, Guorui Song, Ailing Zeng, Xian Liu, Chen Wei, Wanqi Yin, Qingping Sun, et al. The quest for generalizable motion generation: Data, model, and evaluation. *arXiv preprint arXiv:2510.26794*, 2025.
- [63] Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, et al. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*, 2024.
- [64] Haiyang Liu, Naoya Iwamoto, Zihao Zhu, Zhengqing Li, You Zhou, Elif Bozkurt, and Bo Zheng. Disco: Disentangled implicit content and rhythm learning for diverse co-speech gestures synthesis. In *Proceedings of the 30th ACM International Conference on Multimedia*, pages 3764–3773, 2022.
- [65] Haiyang Liu, Zihao Zhu, Naoya Iwamoto, Yichen Peng, Zhengqing Li, You Zhou, Elif Bozkurt, and Bo Zheng. Beat: A large-scale semantic and emotional multi-modal dataset for conversational gestures synthesis. In *ECCV*, pages 612–630. Springer, 2022.
- [66] Haiyang Liu, Zihao Zhu, Naoya Iwamoto, Yichen Peng, Zhengqing Li, You Zhou, Elif Bozkurt, and Bo Zheng. Beat: A large-scale semantic and emotional multi-modal dataset for conversational gestures synthesis. In *ECCV*, 2022.
- [67] Haiyang Liu, Zihao Zhu, Giorgio Becherini, Yichen Peng, Mingyang Su, You Zhou, Xuefei Zhe, Naoya Iwamoto, Bo Zheng, and Michael J. Black. Emage: Towards unified holistic co-speech gesture generation via expressive masked audio gesture modeling. In *CVPR*, 2024.
- [68] Lianlian Liu, YongKang He, Zhaojie Chu, Xiaofen Xing, and Xiangmin Xu. Mimicparts: Part-aware style injection for speech-driven 3d motion generation. *arXiv preprint arXiv:2510.13208*, 2025.
- [69] Mengyuan Liu, Sheng Yan, Yong Wang, Yingjie Li, Guibin Bian, and Hong Liu. Mosa: Motion generation with scalable autoregressive modeling. *arXiv preprint arXiv:2511.01200*, 2025.

- [70] Xian Liu, Qianyi Wu, Hang Zhou, Yinghao Xu, Rui Qian, Xinyi Lin, Xiaowei Zhou, Wayne Wu, Bo Dai, and Bolei Zhou. Learning hierarchical cross-modal association for co-speech gesture generation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10462–10472, 2022.
- [71] Xinran Liu, Xu Dong, Diptesh Kanojia, Wenwu Wang, and Zhenhua Feng. Gcdance: Genre-controlled 3d full body dance generation driven by music. *arXiv preprint arXiv:2502.18309*, 2025.
- [72] Xinran Liu, Zhenhua Feng, Diptesh Kanojia, and Wenwu Wang. Dgfm: Full body dance generation driven by music foundation models. *arXiv preprint arXiv:2502.20176*, 2025.
- [73] Yuanzhe Liu, Jingyuan Zhu, Yuchen Mo, Gen Li, Xu Cao, Jin Jin, Yifan Shen, Zhengyuan Li, Tianjiao Yu, Wenzhen Yuan, et al. Palm: Progress-aware policy learning via affordance reasoning for long-horizon robotic manipulation. *arXiv preprint arXiv:2601.07060*, 2026.
- [74] Matthew Loper, Naureen Mahmood, Javier Romero, Gerard Pons-Moll, and Michael J. Black. SMPL: A skinned multi-person linear model. *ACM Trans. Graphics (Proc. SIGGRAPH Asia)*, 34(6):248:1–248:16, 2015.
- [75] Yunhong Lou, Linchao Zhu, Yaxiong Wang, Xiaohan Wang, and Yi Yang. Diversemotion: Towards diverse human motion generation via discrete diffusion. *arXiv preprint arXiv:2309.01372*, 2023.
- [76] Jiasen Lu, Dhruv Batra, Devi Parikh, and Stefan Lee. Vilm: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. *Advances in neural information processing systems*, 32, 2019.
- [77] Xiang Lyu, Yuxuan Wang, Tianyu Zhao, Hao Wang, Huadai Liu, and Zhihao Du. Build llm-based zero-shot streaming tts system with cosyvoice. In *ICASSP 2025-2025 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 1–2. IEEE, 2025.
- [78] Yue Ma, Zexuan Yan, Hongyu Liu, Hongfa Wang, Heng Pan, Yingqing He, Junkun Yuan, Ailing Zeng, Chengfei Cai, Heung-Yeung Shum, et al. Follow-your-emoji-faster: Towards efficient, fine-controllable, and expressive freestyle portrait animation. *arXiv preprint arXiv:2509.16630*, 2025.
- [79] Naureen Mahmood, Nima Ghorbani, Nikolaus F. Troje, Gerard Pons-Moll, and Michael J. Black. AMASS: Archive of motion capture as surface shapes. In *International Conference on Computer Vision*, pages 5442–5451, 2019.
- [80] Claire McLean, Makenzie Meendering, Tristan Swartz, Orri Gabbay, Alexandra Olsen, Rachel Jacobs, Nicholas Rosen, Philippe de Bree, Tony Garcia, Gadsden Merrill, et al. Embody 3d: A large-scale multimodal motion and behavior dataset. *arXiv preprint arXiv:2510.16258*, 2025.
- [81] Muhammad Hamza Mughal, Rishabh Dabral, Ikhsanul Habibie, Lucia Donatelli, Marc Habermann, and Christian Theobalt. ConvoFusion: Multi-modal conversational diffusion for co-speech gesture synthesis. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 1388–1398, 2024.
- [82] Basil Mustafa, Carlos Riquelme, Joan Puigcerver, Rodolphe Jenatton, and Neil Houlsby. Multimodal contrastive learning with limoe: the language-image mixture of experts. *Advances in Neural Information Processing Systems*, 35:9564–9576, 2022.
- [83] Rajmund Nagy, Hendric Voss, Thanh Hoang-Minh, Mihail Tsakov, Teodor Nikolov, Zeyi Zhang, Tenglong Ao, Sicheng Yang, Shaoli Huang, Yongkang Cheng, et al. Gesture generation (still) needs improved human evaluation practices: Insights from a community-driven state-of-the-art benchmark. *arXiv preprint arXiv:2511.01233*, 2025.
- [84] Evonne Ng, Javier Romero, Timur Bagautdinov, Shaojie Bai, Trevor Darrell, Angjoo Kanazawa, and Alexander Richard. From audio to photoreal embodiment: Synthesizing humans in conversations. In *CVPR*, pages 1001–1010, 2024.
- [85] Federico Nocentini, Thomas Besnier, Claudio Ferrari, Sylvain Arguillere, Stefano Berretti, and Mohamed Daoudi. Scantalk: 3d talking heads from unregistered scans. In *ECCV*, pages 19–36. Springer, 2024.
- [86] Joon Sung Park, Joseph O’Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulators of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pages 1–22, 2023.
- [87] Georgios Pavlakos, Vasileios Choutas, Nima Ghorbani, Timo Bolkart, Ahmed A. Osman, Dimitrios Tzionas, and Michael J. Black. Expressive body capture: 3d hands, face, and body from a single image. In *Proceedings IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2019.
- [88] Georgios Pavlakos, Dandan Shan, Ilija Radosavovic, Angjoo Kanazawa, David Fouhey, and Jitendra Malik. Reconstructing hands in 3D with transformers. In *CVPR*, 2024.
- [89] William Peebles and Saining Xie. Scalable diffusion models with transformers. In *ICCV*, pages 4195–4205, 2023.
- [90] Ziqiao Peng, Yihao Luo, Yue Shi, Hao Xu, Xiangyu Zhu, Hongyan Liu, Jun He, and Zhaoxin Fan. Selftalk: A self-supervised commutative training diagram to comprehend 3d talking faces. In *ACMMM*, pages 5292–5301, 2023.
- [91] Zhiliang Peng, Jianwei Yu, Wenhui Wang, Yaoyao Chang, Yutao Sun, Li Dong, Yi Zhu, Weijiang Xu, Hangbo Bao, Zehua Wang, et al. Vibevoice technical report. *arXiv preprint arXiv:2508.19205*, 2025.
- [92] Xingqun Qi, Yatian Wang, Hengyuan Zhang, Jiahao Pan, Wei Xue, Shanghang Zhang, Wenhan Luo, Qifeng Liu, and Yike Guo. Co3 gesture: Towards coherent concurrent co-speech 3d gesture generation with interactive diffusion. *ICLR*, 2025.
- [93] Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training. 2018.
- [94] Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. 2019.
- [95] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry,

- Amanda Askill, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PmLR, 2021.
- [96] Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. In *International conference on machine learning*, pages 28492–28518. PMLR, 2023.
- [97] Andrew Reece, Gus Cooney, Peter Bull, Christine Chung, Bryn Dawson, Casey Fitzpatrick, Tamara Glazer, Dean Knox, Alex Liebscher, and Sebastian Marin. The candor corpus: Insights from a large multimodal dataset of naturalistic conversation. *Science Advances*, 9(13):eadf3197, 2023.
- [98] Alexander Richard, Michael Zollhöfer, Yandong Wen, Fernando De la Torre, and Yaser Sheikh. Meshtalk: 3d face animation from speech using cross-modality disentanglement. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 1173–1182, 2021.
- [99] Javier Romero, Dimitrios Tzionas, and Michael J. Black. Embodied hands: Modeling and capturing hands and bodies together. *ACM Transactions on Graphics, (Proc. SIG-GRAPH Asia)*, 36(6), 2017.
- [100] Runway AI, Inc. Runway: Ai video generation platform. <https://runwayml.com>, 2025. Accessed: 2025-11-20.
- [101] Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarczyk, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. *arXiv preprint arXiv:1701.06538*, 2017.
- [102] Yifan Shen, Yuanzhe Liu, Jingyuan Zhu, Xu Cao, Xiaofeng Zhang, Yixiao He, Wenming Ye, James Matthew Rehg, and Ismini Lourentzou. Fine-grained preference optimization improves spatial reasoning in vlms. *NeurIPS 2025*, 2025.
- [103] Li Siyao, Xintong Yu, and et al. Bailando: 3d dance generation by actor-critic gpt with choreographic memory. In *CVPR*, 2022.
- [104] Stefan Stan, Kazi Injamamul Haque, and Zerrin Yumak. Facediffuser: Speech-driven 3d facial animation synthesis using diffusion. In *Proceedings of the 16th ACM SIG-GRAPH Conference on Motion, Interaction and Games*, pages 1–11, 2023.
- [105] Zhiyao Sun, Tian Lv, Sheng Ye, Matthieu Lin, Jenny Sheng, Yu-Hui Wen, Mingjing Yu, and Yong-jin Liu. Diffposetalk: Speech-driven stylistic 3d facial animation and head pose generation via diffusion models. *ACM Transactions on Graphics (TOG)*, 43(4):1–9, 2024.
- [106] Kim Sung-Bin, Lee Chae-Yeon, Gihun Son, Oh Hyun-Bin, Janghoon Ju, Suekyeong Nam, and Tae-Hyun Oh. Multitalk: Enhancing 3d talking head generation across languages with multilingual video dataset. *arXiv preprint arXiv:2406.14272*, 2024.
- [107] Hao Tan and Mohit Bansal. Lxmert: Learning cross-modality encoder representations from transformers. *arXiv preprint arXiv:1908.07490*, 2019.
- [108] Ruijie Tao, Zexu Pan, Rohan Kumar Das, Xinyuan Qian, Mike Zheng Shou, and Haizhou Li. Is someone speaking? exploring long-term temporal features for audio-visual active speaker detection. In *ACMMM*, page 3927–3935, 2021.
- [109] Chameleon Team. Chameleon: Mixed-modal early-fusion foundation models. *arXiv preprint arXiv:2405.09818*, 2024.
- [110] Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.
- [111] Guy Tevet, Sigal Raab, Brian Gordon, Yoni Shafir, Daniel Cohen-or, and Amit Haim Bermano. Human motion diffusion model. In *The Eleventh International Conference on Learning Representations*, 2023.
- [112] Guy Tevet, Sigal Raab, Setareh Cohan, Daniele Reda, Zhengyi Luo, Xue Bin Peng, Amit H Bermano, and Michiel van de Panne. Closd: Closing the loop between simulation and diffusion for multi-task character control. *arXiv preprint arXiv:2410.03441*, 2024.
- [113] Linrui Tian, Qi Wang, Bang Zhang, and Liefeng Bo. Emo: Emote portrait alive generating expressive portrait videos with audio2video diffusion model under weak conditions. In *ECCV*, pages 244–260. Springer, 2024.
- [114] Jonathan Tseng, Rodrigo Castellon, and Karen Liu. Edge: Editable dance generation from music. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 448–458, 2023.
- [115] Qing Wang, Xiaohang Yang, Yilan Dong, Naveen Raj Govindaraj, Gregory Slabaugh, and Shanxin Yuan. Dancechat: Large language model-guided music-to-dance generation. *arXiv preprint arXiv:2506.10574*, 2025.
- [116] Ting-Chun Wang, Arun Mallya, and Ming-Yu Liu. One-shot free-view neural talking-head synthesis for video conferencing. In *CVPR*, 2021.
- [117] Yuan Wang, Di Huang, Yaqi Zhang, Wanli Ouyang, Jile Jiao, Xuetao Feng, Yan Zhou, Pengfei Wan, Shixiang Tang, and Dan Xu. Motiongpt-2: A general-purpose motion-language model for motion generation and understanding. *arXiv preprint arXiv:2410.21747*, 2024.
- [118] Huawei Wei, Zejun Yang, and Zhisheng Wang. Aniportrait: Audio-driven synthesis of photorealistic portrait animation. *arXiv preprint arXiv:2403.17694*, 2024.
- [119] John Won, Kyungmin Lee, Huiwon Jang, Dongyoung Kim, and Jinwoo Shin. Dual-stream diffusion for world-model augmented vision-language-action model. *arXiv preprint arXiv:2510.27607*, 2025.
- [120] Yiming Wu, Wei Ji, Kecheng Zheng, Zicheng Wang, and Dong Xu. Mote: Learning motion-text diffusion model for multiple generation tasks. *arXiv preprint arXiv:2411.19786*, 2024.
- [121] You Xie, Tianpei Gu, Zenan Li, Chenxu Zhang, Guoxian Song, Xiaochen Zhao, Chao Liang, Jianwen Jiang, Hongyi Xu, and Linjie Luo. X-streamer: Unified human world modeling with audiovisual interaction. *arXiv preprint arXiv:2509.21574*, 2025.

- [122] Jinbo Xing, Menghan Xia, Yuechen Zhang, Xiaodong Cun, Jue Wang, and Tien-Tsin Wong. Codetalker: Speech-driven 3d facial animation with discrete motion prior. In *CVPR*, pages 12780–12790, 2023.
- [123] Feng Xu, Guangyao Zhai, Xin Kong, Tingzhong Fu, Daniel FN Gordon, Xueli An, and Benjamin Busam. Stare-vla: Progressive stage-aware reinforcement for fine-tuning vision-language-action models. *arXiv preprint arXiv:2512.05107*, 2025.
- [124] Guowei Xu, Yuxuan Bian, Ailing Zeng, Mingyi Shi, Shaoli Huang, Wen Li, Lixin Duan, and Qiang Xu. Omnimotion-x: Versatile multimodal whole-body motion generation. *arXiv preprint arXiv:2510.19789*, 2025.
- [125] Jin Xu, Zhifang Guo, Jinzheng He, Hangrui Hu, Ting He, Shuai Bai, Keqin Chen, Jialin Wang, Yang Fan, Kai Dang, Bin Zhang, Xiong Wang, Yunfei Chu, and Junyang Lin. Qwen2.5-omni technical report. *arXiv preprint arXiv:2503.20215*, 2025.
- [126] Sicheng Xu, Guojun Chen, Yu-Xiao Guo, Jiaolong Yang, Chong Li, Zhenyu Zang, Yizhong Zhang, Xin Tong, and Baining Guo. Vasa-1: Lifelike audio-driven talking faces generated in real time. *Advances in Neural Information Processing Systems*, 37:660–684, 2024.
- [127] Zunnan Xu, Zhentao Yu, Zixiang Zhou, Jun Zhou, Xiaoyu Jin, Fa-Ting Hong, Xiaozhong Ji, Junwei Zhu, Chengfei Cai, Shiyu Tang, et al. Hunyuanportrait: Implicit condition control for enhanced portrait animation. In *CVPR*, pages 15909–15919, 2025.
- [128] Sicheng Yang, Zhiyong Wu, Minglei Li, Zhensong Zhang, Lei Hao, Weihong Bao, Ming Cheng, and Long Xiao. Diffusestylegesture: Stylized audio-driven co-speech gesture generation with diffusion models. In *Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence, IJCAI-23*, pages 5860–5868. International Joint Conferences on Artificial Intelligence Organization, 2023.
- [129] Yuhang Yang, Ke Fan, Shangkun Sun, Hongxiang Li, Ailing Zeng, FeiLin Han, Wei Zhai, Wei Liu, Yang Cao, and Zheng-Jun Zha. Videogen-eval: Agent-based system for video generation evaluation. *arXiv preprint arXiv:2503.23452*, 2025.
- [130] Hongwei Yi, Hualin Liang, Yifei Liu, Qiong Cao, Yandong Wen, Timo Bolkart, Dacheng Tao, and Michael J Black. Generating holistic 3d human motion from speech. In *CVPR*, pages 469–480, 2023.
- [131] Hongwei Yi, Hualin Liang, Yifei Liu, Qiong Cao, Yandong Wen, Timo Bolkart, Dacheng Tao, and Michael J. Black. Generating holistic 3d human motion from speech. In *CVPR*, 2023.
- [132] Youngwoo Yoon, Bok Cha, Joo-Haeng Lee, Minsu Jang, Jaeyeon Lee, Jaehong Kim, and Geehyuk Lee. Speech gesture generation from the trimodal context of text, audio, and speaker identity. *ACM Transactions on Graphics (TOG)*, 39(6):1–16, 2020.
- [133] Heng Yu, Juze Zhang, Changan Chen, Tiange Xiang, Yusu Fang, Juan Carlos Niebles, and Ehsan Adeli. Socialgen: Modeling multi-human social interaction with language models. *arXiv preprint arXiv:2503.22906*, 2025.
- [134] Wenyi Yu, Siyin Wang, Xiaoyu Yang, Xianzhao Chen, Xiaohai Tian, Jun Zhang, Guangzhi Sun, Lu Lu, Yuxuan Wang, and Chao Zhang. Salmonn-omni: A codec-free llm for full-duplex speech understanding and generation. *arXiv preprint arXiv:2411.18138*, 2024.
- [135] Aohan Zeng, Zhengxiao Du, Mingdao Liu, Kedong Wang, Shengmin Jiang, Lei Zhao, Yuxiao Dong, and Jie Tang. Glm-4-voice: Towards intelligent and human-like end-to-end spoken chatbot. *arXiv preprint arXiv:2412.02612*, 2024.
- [136] Jun Zhan, Junqi Dai, Jiasheng Ye, Yunhua Zhou, Dong Zhang, Zhigeng Liu, Xin Zhang, Ruibin Yuan, Ge Zhang, Linyang Li, et al. Anygpt: Unified multimodal llm with discrete sequence modeling. *arXiv preprint arXiv:2402.12226*, 2024.
- [137] Juze Zhang, Jingya Wang, Ye Shi, Fei Gao, Lan Xu, and Jingyi Yu. Mutual adaptive reasoning for monocular 3d multi-person pose estimation. In *Proceedings of the 30th ACM international conference on multimedia*, pages 1788–1796, 2022.
- [138] Juze Zhang, Haimin Luo, Hongdi Yang, Xinru Xu, Qianyang Wu, Ye Shi, Jingyi Yu, Lan Xu, and Jingya Wang. Neuraldome: A neural modeling pipeline on multi-view human-object interactions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8834–8845, 2023.
- [139] Juze Zhang, Ye Shi, Yuexin Ma, Lan Xu, Jingyi Yu, and Jingya Wang. Ikol: Inverse kinematics optimization layer for 3d human pose and shape estimation via gauss-newton differentiation. In *Proceedings of the AAAI conference on artificial intelligence*, pages 3454–3462, 2023.
- [140] Jianrong Zhang, Yangsong Zhang, Xiaodong Cun, Yong Zhang, Hongwei Zhao, Hongtao Lu, Xi Shen, and Ying Shan. Generating human motion from textual descriptions with discrete representations. In *CVPR*, pages 14730–14740, 2023.
- [141] Juze Zhang, Jingyan Zhang, Zining Song, Zhanhe Shi, Chengfeng Zhao, Ye Shi, Jingyi Yu, Lan Xu, and Jingya Wang. Hoi-m³: Capture multiple humans and objects interaction within contextual environment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 516–526, 2024.
- [142] Mingyuan Zhang, Daisheng Jin, Chenyang Gu, Fangzhou Hong, Zhongang Cai, Jingfang Huang, Chongzhi Zhang, Xinying Guo, Lei Yang, Ying He, and Ziwei Liu. Large motion model for unified multi-modal motion generation. In *ECCV*, 2024.
- [143] Ruichen Zhang, Wen Wang, et al. Unimomo: Unified text, music and motion generation. *arXiv preprint arXiv:2410.04534*, 2024.
- [144] Wenqian Zhang, Molin Huang, Yuxuan Zhou, Juze Zhang, Jingyi Yu, Jingya Wang, and Lan Xu. Both2hands: Inferring 3d hands from both text prompts and body dynamics. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2393–2404, 2024.
- [145] Yaqi Zhang, Di Huang, Bin Liu, Shixiang Tang, Yan Lu, Lu Chen, Lei Bai, Qi Chu, Nenghai Yu, and Wanli Ouyang.

- Motiongpt: Finetuned llms are general-purpose motion generators. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 7368–7376, 2024.
- [146] Zeyu Zhang, Yiran Wang, Wei Mao, Danning Li, Rui Zhao, Biao Wu, Zirui Song, Bohan Zhuang, Ian Reid, and Richard Hartley. Motion anything: Any to motion generation. *arXiv preprint arXiv:2503.06955*, 2025.
 - [147] Zeyi Zhang, Yanju Zhou, Heyuan Yao, Tenglong Ao, Xiaohang Zhan, and Libin Liu. Social agent: Mastering dyadic nonverbal behavior generation via conversational llm agents. *arXiv preprint arXiv:2510.04637*, 2025.
 - [148] Chengfeng Zhao, Juze Zhang, Jiasen Du, Ziwei Shan, Junye Wang, Jingyi Yu, Jingya Wang, and Lan Xu. I’m hoi: Inertia-aware monocular capture of 3d human-object interactions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 729–741, 2024.
 - [149] Yue Zhao, Yuanjun Xiong, and Philipp Krähenbühl. Image and video tokenization with binary spherical quantization. *arXiv preprint arXiv:2406.07548*, 2024.
 - [150] Chunting Zhou, Lili Yu, Arun Babu, Kushal Tirumala, Michihiro Yasunaga, Leonid Shamis, Jacob Kahn, Xuezhe Ma, Luke Zettlemoyer, and Omer Levy. Transfusion: Predict the next token and diffuse images with one multi-modal model. *arXiv preprint arXiv:2408.11039*, 2024.
 - [151] Bingfan Zhu, Biao Jiang, Sunyi Wang, Shixiang Tang, Tao Chen, Linjie Luo, Youyi Zheng, and Xin Chen. Motiongpt3: Human motion as a second modality. *arXiv preprint arXiv:2506.24086*, 2025.
 - [152] Brianna Zitkovich, Tianhe Yu, Sichun Xu, Peng Xu, Ted Xiao, Fei Xia, Jialin Wu, Paul Wohlhart, Stefan Welker, Ayzaan Wahid, et al. Rt-2: Vision-language-action models transfer web knowledge to robotic control. In *Conference on Robot Learning*, pages 2165–2183. PMLR, 2023.

7. Supplementary Material

In this supplementary material, we provide additional details about:

1. Supplementary video for qualitative examples.
2. Application cases of ViBES.
3. Additional implementation details of ViBES.
4. Additional details on the YouTube data processing pipeline (referenced in Sec. 4).
5. Additional details on constructing conversational motion from the AMASS dataset (referenced in Sec. 4).
6. Additional qualitative example of talking head generation and text-to-motion.

7.1. Supplementary Video

We provide a supplementary video to illustrate our method and results. The video presents: 1) the background and motivation of this work; 2) an explanation of the overall framework; and 3) detailed qualitative comparisons across different tasks, including conversational behavior generation, talking-head generation, co-speech gesture generation, and text-to-motion generation. We recommend watching the video with headphones, as it offers a more comprehensive understanding of our approach.

7.2. Application Cases of ViBES

Benefiting from the 3D representation, our conversational agent naturally extends into the spatial domain. And also, it can be used to drive more realistic video avatars. As illustrated in Fig. 7, we use an off-the-shelf video generation tool powered by Runway AI [100] to synthesize avatar videos, conditioned on our generated head motions.

7.3. Additional Implementation Details of ViBES

The original GLM-4 model [33] consists of 40 transformer layers with a hidden size of 4096 and an FFN dimension of 13,696, for a total of roughly 9B parameters. For our face and motion branches, directly duplicating this architecture would be inefficient. Instead, we adopt a lightweight variant with 40 layers, a hidden size of 512, and an FFN dimension of 4096, resulting in approximately 430M parameters for each branch. We train ViBES on 4 L40S GPUs for about one week with a learning rate of 1×10^{-4} .

For the motion tokenizer, as discussed in the main manuscript, two popular paradigms of motion representation are widely used. For most experiments in this paper, we adopt a compositional motion tokenizer [11, 67]. In addition, we train a separate HumanML3D representation [35] to enable fair comparison with existing text-to-motion models that rely on this convention.




Figure 6. Overview of our YouTube data processing pipeline. The raw videos are processed to obtain high-quality 3D poses using automatic algorithms.

7.4. Additional details on the YouTube data processing pipeline

In this section, we give a detailed explanation of the data processing pipeline of our Converse3D dataset. We summarize the acquisition, processing, and filtering of our Converse3D dataset into two main procedures: automatic and manual processing steps, as illustrated in Fig 6. To build a high-quality 3D co-speech gesture dataset with concurrent and interactive body dynamics, we collect a considerable number of videos. They are then processed using automated methods to extract both audio and motion information.

Raw Video Downloading and Processing We crawl in-the-wild conversational videos from YouTube, targeting couple-interview channels, sports conversations, autobiographical interviews, entertainment talk shows, and news discussions on social topics. Using keywords such as *talk show*, *conversation*, and *interview*, we retrieve videos together with their metadata (duration, frame resolution, audio sampling rate, etc.); the keyword distribution is visualized in Fig. 8. In total we collect over 2,000 hours of raw footage and retain 1,095 hours of conversational clips after automatic filtering and light manual cleaning. We discard videos that do not satisfy our requirements on category, visual quality, language, or body visibility. In particular, we only keep English dialogues and download each video at its maximum available resolution to better recover facial and body motion. Most retained clips contain a clearly visible




Figure 9. Additional qualitative comparisons with prior methods on the speech-driven 3D head animation task (with head pose held fixed). Since most existing models are trained on TFHP [105], we evaluate on this dataset to ensure a fair comparison.










Text	A person walks forward then turns completely around and does a cartwheel.	A person taking a huge diagonal step	A person tries to clean the floor
Ours			
MotionGPT			
LoM			
MoMask			

Figure 10. Additional qualitative examples for text-to-motion generation. Given a text caption, we compare the 3D motion generated by our method with those generated by state-of-the-art methods, including MotionGPT [45], LoM [11], and MoMask [37]. Our model produces smooth, natural, and sometimes better motion in comparison with existing methods, which do not model the conversation behavior.

System Prompt for Motion-conditioned Conversational Answer Generation

System Promopt.

< |system| > User will provide you with a text instruction. Do it step by step. First, think about the instruction and respond in a interleaved manner, with 13 text token followed by 26 audio tokens. Please follow these steps carefully: Think about the instruction first. Respond in an interleaved manner: output 13 text tokens followed by 26 audio tokens. In your reply, imagine that you have a body and are already moving, pretending to perform 'the motion required by the question. Make sure your answer aligns with both the question and the motion being asked. Remember: the motion is imaginary (pretend), not real. If you describe the motion, use the first-person perspective (e.g., 'my hand,' 'my body,' 'my movement'). Please reply as if you are experiencing and expressing the motion yourself."

Figure 11. System prompt for motion-conditioned conversational answer generation. We instruct the model to generate answers as if the avatar had its own body and were responding through both speech and body movement.