

## CD32 Indoor Dome Camera

# Advanced 3MP Coverage for Monitoring Indoor Environments



## Overview

The CD32 dome camera provides advanced 3MP coverage in a variety of indoor spaces. With its 1 / 2.8" progressive CMOS image sensor and 15 meters / 49 feet of IR range, the CD32 delivers consistent visibility in a variety of lighting conditions. The CD32 includes an onboard CV25S Ambarella processor to support advanced analytics like AI-powered search, [occupancy trends](#), line crossing, loitering, and person of interest (POI) alerts. Designed to balance essential monitoring with analytics that accelerate investigations, the CD32 is optimal for covering areas like IT closets and merchandise racks where supplemental visibility is critical.

The CD32's sleek design and IK08 impact rating enable organizations to deploy a durable, tamper-resistant camera while also keeping aesthetics top-of-mind. Installation is simple and intuitive, and setup is easy to track with an LED status indicator. The included mount plate additionally allows the camera to be mounted to a wall or ceiling without any additional hardware.

## Key features

### Clear image quality

- 1 / 2.8" progressive CMOS image sensor
- 3MP resolution
- 15 meters / 49 feet of IR range for well-defined nighttime viewing

### Advanced analytics

- Onboard CV25S Ambarella processor enables people and vehicle analytics
- AI-powered search and AI-powered alerts
- Occupancy trends for operational insights

### Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 90 days (256GB - 768GB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

### Easy installation

- Mounting plate and screw pack included
- LED light status indicator
- Digital mute switch to quickly enable or disable audio



## CD32

## Tech specs

## Camera features

|                                              |                                                                      |                             |                                                           |
|----------------------------------------------|----------------------------------------------------------------------|-----------------------------|-----------------------------------------------------------|
| <b>Image sensor</b>                          | 1 / 2.8" Progressive CMOS                                            | <b>Shutter speed</b>        | 1 / 30 sec. to 1 / 10,000 sec.                            |
| <b>Sensor resolution<sup>1</sup></b>         | 3MP (2048 x 1536)                                                    | <b>Day/night</b>            | IR-cut filter for day and night function                  |
| <b>Lens type</b>                             | Fixed                                                                | <b>IR-cut filter</b>        | Yes                                                       |
| <b>Focal length</b>                          | 2.8mm                                                                | <b>IR range</b>             | 15m / 49ft                                                |
| <b>Aperture</b>                              | F1.6                                                                 | <b>Minimum illumination</b> | 0.009 lux @ F1.9 (Color)<br>0 lux with IR Illuminators on |
| <b>Iris</b>                                  | Fixed                                                                | <b>Onboard storage</b>      | Capacity: From 256GB to 768GB<br>Card: MicroSD, SDXC      |
| <b>Field of view (after LDC<sup>2</sup>)</b> | Horizontal: 97° (78°)<br>Vertical: 71° (63°)<br>Diagonal: 128° (91°) | <b>CPU</b>                  | Ambarella CV25S88                                         |
| <b>Sensor movement</b>                       | Tilt: 60°<br>Pan: 355°<br>Rotation: 180°                             |                             |                                                           |

## Standard video settings

|                               |              |                                  |                                                                                        |
|-------------------------------|--------------|----------------------------------|----------------------------------------------------------------------------------------|
| <b>Compression</b>            | H.265, H.264 | <b>Historical video settings</b> | Adaptive quality <sup>1</sup>                                                          |
| <b>Frame rate<sup>3</sup></b> | 24fps        | <b>Live streaming settings</b>   | High quality (HQ): Up to 3,000 Kbps (default)<br>Standard quality (SQ): Up to 600 Kbps |

## Standard audio settings

|                       |               |                        |                     |
|-----------------------|---------------|------------------------|---------------------|
| <b>Audio</b>          | Supported     | <b>Interface</b>       | Built-in microphone |
| <b>Audio capacity</b> | One-way audio | <b>Effective range</b> | 5m / 15ft           |

## Power and network

|                                      |                                                                                                              |                     |                                                                         |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------|---------------------|-------------------------------------------------------------------------|
| <b>Power input<sup>4</sup></b>       | With IR: IEEE 802.3af Type 1 PoE<br>Without IR: IEEE 802.3af Type 1 PoE<br>Extended temperature range: N/A   | <b>Connectivity</b> | RJ-45 cable connector for network/PoE connection; 10 / 100 Mbps         |
| <b>Power consumption<sup>4</sup></b> | With IR: 37-57V, 0.23-0.15A, 8.6W<br>Without IR: 37-57V, 0.11-0.07A, 4.3W<br>Extended temperature range: N/A | <b>RTSP</b>         | RTSP 1.0<br>RFC 2326<br>Max concurrent streams: 2<br>Audio support: Yes |

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>.

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below -10°C / 14°F and assumes IR will be enabled.



CD32

Tech specs



General

|                       |                                                                                                                  |                      |                                                                           |
|-----------------------|------------------------------------------------------------------------------------------------------------------|----------------------|---------------------------------------------------------------------------|
| Operating temperature | -10°C to 50°C / 14°F to 122°F                                                                                    | LED Indicator        | System power and status indicator                                         |
| Humidity              | 0 to 90%                                                                                                         | Warranty             | 10 years                                                                  |
| Certifications        | FCC, ICES, CE, UKCA, RCM, CB, VCCI, KCC, BIS, NOM, UL/cUL/IEC 62368-1, IK08 impact rating, FY2019 NDAA compliant | Included accessories | Setup guide, T10 security torx screwdriver, screw pack, mounting template |

Mechanical

|            |                                                                                                                          |      |                             |
|------------|--------------------------------------------------------------------------------------------------------------------------|------|-----------------------------|
| Weight     | Camera: 608g / 21.45oz<br>Mount plate: 140g / 4.94oz                                                                     | Body | Aluminum, plastic dome trim |
| Dimensions | Ø: 146.0mm / 5.75in, H: 104.3mm / 4.11in with mount plate<br>Ø: 146.0mm / 5.75in, H: 99.8mm / 3.93in without mount plate |      |                             |

Dimensions



Software capabilities

|                   |                                                                                                                                                                                      |                       |                                                                                                             |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-------------------------------------------------------------------------------------------------------------|
| Alerts            | Camera status, motion detection, people detection, vehicle detection, person of interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts | Streaming and storage | Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP |
| People analytics  | People search, attribute search, face search, occupancy trends, motion search, trajectory analysis, selective face blurring, AI-powered search                                       | Sharing and privacy   | Live links, live face blur, privacy regions, audit log                                                      |
| Vehicle analytics | Vehicle search, attribute search, motion search, trajectory analysis, occupancy trends, AI-powered search                                                                            |                       |                                                                                                             |



## Ordering information

### CD32 pricing

| Model number | MP <sup>1</sup> | WDR | Lens  | IR range   | Onboard storage | Maximum SQ onboard retention <sup>1</sup> | People/vehicle analytics | US cost (MSRP) <sup>USD</sup> | WW cost (MSRP) <sup>USD</sup> |
|--------------|-----------------|-----|-------|------------|-----------------|-------------------------------------------|--------------------------|-------------------------------|-------------------------------|
| CD32-256-HW  | 3MP             | ✓   | Fixed | 15m / 49ft | 256GB           | 30 Days                                   | ✓                        | \$999                         | \$899                         |
| CD32-512-HW  | 3MP             | ✓   | Fixed | 15m / 49ft | 512GB           | 60 Days                                   | ✓                        | \$1,699                       | \$1,599                       |
| CD32-768-HW  | 3MP             | ✓   | Fixed | 15m / 49ft | 768GB           | 90 Days                                   | ✓                        | \$2,399                       | \$2,299                       |

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>



## Ordering information

### Video Security Cloud License Pricing (new/capacity increase)

| Model number    | Description                               | US cost (MSRP) <sup>USD</sup> | WW cost(MSRP) <sup>USD</sup> |
|-----------------|-------------------------------------------|-------------------------------|------------------------------|
| LIC-CAM-1Y-CAP  | 1-year camera license, capacity increase  | \$249                         | \$249                        |
| LIC-CAM-3Y-CAP  | 3-year camera license, capacity increase  | \$659                         | \$659                        |
| LIC-CAM-5Y-CAP  | 5-year camera license, capacity increase  | \$1,099                       | \$1,099                      |
| LIC-CAM-10Y-CAP | 10-year camera license, capacity increase | \$2,199                       | \$2,199                      |

### Video Security Cloud License Pricing (renewal)

| Model number    | Description                     | US cost (MSRP) <sup>USD</sup> | WW cost(MSRP) <sup>USD</sup> |
|-----------------|---------------------------------|-------------------------------|------------------------------|
| LIC-CAM-1Y-RNW  | 1-year camera license, renewal  | \$249                         | \$249                        |
| LIC-CAM-3Y-RNW  | 3-year camera license, renewal  | \$659                         | \$659                        |
| LIC-CAM-5Y-RNW  | 5-year camera license, renewal  | \$1,099                       | \$1,099                      |
| LIC-CAM-10Y-RNW | 10-year camera license, renewal | \$2,199                       | \$2,199                      |



# Accessories

## Recommended accessories

| Model Number     | Description                              |
|------------------|------------------------------------------|
| ACC-CAM-SHIELD-1 | Camera Weather Shield                    |
| ACC-MNT-ANGLE-1  | Angle Mount                              |
| ACC-MNT-ARM-1    | Arm Mount                                |
| ACC-MNT-CJBOX-1  | Circle Junction Box Mount                |
| ACC-MNT-CLIP-1   | Tile Clip Mount                          |
| ACC-MNT-CORNER-1 | Corner Mount                             |
| ACC-MNT-LBRAC-1  | L-Bracket Mount                          |
| ACC-MNT-PEND-1   | Pendant Cap Mount                        |
| ACC-MNT-POLE-1   | Pole Mount                               |
| ACC-MNT-REC-2    | Recess Ceiling Mount                     |
| INJ-POE-PLUS     | PoE Plus (802.3at Type 2) Injector, GigE |