

CM22 Indoor Mini Dome Camera

Essential 3MP Coverage in a Compact Form Factor



Overview

The CM22 mini dome camera provides 3MP coverage in a compact form factor and is therefore well-suited for discreet deployments and small spaces. With a 1 / 2.8" progressive CMOS image sensor and 10 meters / 33 feet of IR range, the CM22 offers reliable visibility for organizations seeking quick and scalable installations. The CM22 also includes an onboard CV25S Ambarella processor to detect and alert on the presence of people and vehicles. The CM22 excels at covering areas such as small storage closets or store aisles where space is limited or subtlety is needed.

The CM22's sleek design and durability enable organizations to deploy a tamper-resistant camera in small spaces while also keeping aesthetics top-of-mind. Installation is simple and intuitive, and setup is easy to track with an LED status indicator. The included mount plate additionally allows the camera to be mounted to a wall or ceiling without any additional hardware.

Key features

Clear image quality

- 1 / 2.8" progressive CMOS image sensor
- 3MP resolution
- 10 meters / 33 feet of IR range for nighttime viewing

Essential detection

- Onboard CV25S Ambarella processor enables people and vehicle detection

Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 90 days (256GB - 768GB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

Easy installation

- Mounting plate and screw pack included
- LED light status indicator



CM22

Tech specs

Camera features

Image sensor	1 / 2.8" Progressive CMOS	Shutter speed	1 / 30 sec. to 1 / 10,000 sec.
Sensor resolution¹	3MP (2048 x 1536)	Day/night	IR-cut filter for day and night function
Lens type	Fixed	IR-cut filter	Yes
Focal length	2.8mm	IR range	10m / 33ft
Aperture	F1.6	Minimum illumination	0.009 lux @ F1.9 (Color) 0 lux with IR Illuminators on
Iris	Fixed	Onboard storage	Capacity: From 256GB to 768GB Card: MicroSD, SDXC
Field of view (after LDC²)	Horizontal: 95° (79°) Vertical: 69° (62°) Diagonal: 130° (96°)	CPU	Ambarella CV25S88
Sensor movement	Tilt: 60° Pan: 350° Rotation: 180°		

Standard video settings

Compression	H.265, H.264	Historical video settings	Adaptive quality ¹
Frame rate³	24fps	Live streaming settings	High quality (HQ): Up to 3,000 Kbps (default) Standard quality (SQ): Up to 600 Kbps
WDR technology	104 dB dynamic range, true WDR, dual exposure		

Standard audio settings

Audio	Not supported
--------------	---------------

Power and network

Power input⁴	With IR: IEEE 802.3af Type 1 PoE Without IR: IEEE 802.3af Type 1 PoE Extended temperature range: N/A	Connectivity	RJ-45 cable connector for network/PoE connection; 10 / 100 / 1000 Mbps
Power consumption⁴	With IR: 37-57V, 0.17-0.11A, 6.1W Without IR: 37-57V, 0.09-0.06A, 3.2W Extended temperature range: N/A	RTSP	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio support: No

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>.

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below -10°C / 14°F and assumes IR will be enabled.



CM22

Tech specs



General

Operating temperature	-10°C to 50°C / 14°F to 122°F	LED indicator	System power and status indicator
Humidity	0 to 90%	Warranty	5 years
Certifications	FCC, ICES, CE, UKCA, RCM, VCCI, KCC, BIS, NOM, NRKZI, EAC, EN 50155, UL/cUL/IEC 62368-1, FY2019 NDAA compliant	Included accessories	Setup guide, T10 security torx screwdriver, 3x wingnuts, 3x washers, 3x TP4.0 mount screws, 3x M4 wall screws, 3x wall anchors

Mechanical

Weight	Camera: 290g / 10.23oz Mount plate: 98g / 3.46oz	Body	Aluminum, plastic dome trim
Dimensions	Ø: 124.5mm / 4.90in, H: 71.5mm / 2.81in		

Dimensions



Software capabilities

Alerts	Camera status, motion detection, people detection, vehicle detection, crowd detection, line-crossing detection, loitering detection	Streaming and storage	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
People analytics	Motion search, trajectory analysis	Sharing and privacy	Live links, live face blur, privacy regions, audit log
Vehicle analytics	Motion search, trajectory analysis		



Ordering Information

CM22 pricing

Model number	MP ¹	WDR	Lens	IR range	Onboard storage	Maximum SQ onboard retention ¹	People/vehicle analytics	US cost (MSRP) ^{USD}	WW cost (MSRP) ^{USD}
CM22-256-HW	3MP	✓	Fixed	10m / 33ft	256GB	30 Days	–	\$699	\$599
CM22-512-HW	3MP	✓	Fixed	10m / 33ft	512GB	60 Days	–	\$1,399	\$1,299
CM22-768-HW	3MP	✓	Fixed	10m / 33ft	768GB	90 Days	–	\$2,099	\$1,999

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>



Ordering information

Video Security software license pricing (new/capacity increase)

Model number	Description	US cost (MSRP) ^{USD}	WW cost (MSRP) ^{USD}
LIC-CAM-1Y-CAP	Verkada 1-Year Camera License, Capacity Increase	\$249	\$249
LIC-CAM-3Y-CAP	Verkada 3-Year Camera License, Capacity Increase	\$659	\$659
LIC-CAM-5Y-CAP	Verkada 5-Year Camera License, Capacity Increase	\$1,099	\$1,099
LIC-CAM-10Y-CAP	Verkada 10-Year Camera License, Capacity Increase	\$2,199	\$2,199

Video Security software license pricing (renewal)

Model number	Description	US cost (MSRP) ^{USD}	WW cost (MSRP) ^{USD}
LIC-CAM-1Y-RNW	Verkada 1-Year Camera License, Renewal	\$249	\$249
LIC-CAM-3Y-RNW	Verkada 3-Year Camera License, Renewal	\$659	\$659
LIC-CAM-5Y-RNW	Verkada 5-Year Camera License, Renewal	\$1,099	\$1,099
LIC-CAM-10Y-RNW	Verkada 10-Year Camera License, Renewal	\$2,199	\$2,199



Accessories

Recommended accessories

Model Number	Description
ACC-MNT-ARM-1	Arm Mount
ACC-MNT-CLIP-1	Tile Clip Mount
ACC-MNT-CORNER-1	Corner Mount
ACC-MNT-MJBOX-1	Mini Junction Box Mount
ACC-MNT-MPEND-1	Mini Pendant Cap Mount
ACC-MNT-MREC-1	Mini Recess Mount
ACC-MNT-POLE-1	Pole Mount
ACC-MNT-SJBOX-1	Square Junction Box
INJ-POE-PLUS	PoE Plus (802.3at Type 2) Injector, GigE